

Marine 210D MPWC Fire Extinguisher

Part number 466636

Regular use

Disposable

UL Rated 5-B:C



Description

Suitable for use on Class B (liquids & gases) and Class C fires (energized electrical equipment).

The PWC unit is fitted with a "one touch" pressure check device to ensure reliable performance. It is manufactured from lightweight aluminum and a tough nylon valve assembly.

Features bilingual nameplate and carton.

Features

- Pressure check device to determine fire extinguisher's readiness status
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety clip
- Rust and impact resistant nylon handle
- 2.0 lb of fire extinguishing agent (Average)
- 2 year limited warranty
- UL approved bracket
- Powder coated cylinder for corrosion protection



At a Glance

- Model MPWC
- Regular Dry Chemical
- UL listed
- UL rated 5-B:C
- Sodium Bicarbonate
- 2 year limited warranty
- Suitable for use on liquid & energized electrical fires

For use on the following types of fire:



UPC: 0-47871-66636-2

Product Specification

Net agent weight (Average)	2.0 lb
Unit weight (Average)	3.1 lb
Diameter	2.9 inches
Height	12.75 inches
Discharge time	8-10 seconds
Discharge range	10-14 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Strap Bracket	U.S.C.G approved

Packaging Options



MASTER PACK