

Darley Portable Pumps

Also available in 10, 13, 18, or 24 hp & in 18 hp with Briggs Vanguard

Powered by Honda

instock@darley.com

- ▶ Dependable Honda engine
- ▶ Booster tank fill
- ▶ Multiple hand lines
- ▶ Wildland/Attack fire suppression

ALSO SEE MARINE VERSION FOR FIRE BOATS ON PAGE 284!

Features: Honda GX 620 4 cycle, V-twin, OHV, replaceable oil filter, 37.0 cu. in. displacement, 12-volt starter, 20 amp regulated alternator, recoil rope start back-up.

Options: Adapters, caps, control panel, etc.



HE 20H



2BE 20H

Model	Uses	Performance	Inlet	Outlet	Dimensions	Weight	Price
1-1/4AGE 20H	Pressure	60 gpm @ 250 psi 40 gpm @ 320 psi 20 gpm @ 360 psi	1 1/2" NPT	2-1 1/2" NPT	Length: 24" Width: 24" Height: 23"	145 lbs. (66 kg)	\$5,620.00
1-1/2AGE 20H	Pressure	120 gpm @ 130 psi 75 gpm @ 205 psi 25 gpm @ 300 psi	2" NPT	2-1 1/2" & 1-2 1/2" NPT	Length: 24" Width: 24" Height: 23"	145 lbs. (66 kg)	\$5,600.00
2BE 20H	Volume	380 gpm @ 25 psi 150 gpm @ 115 psi 100 gpm @ 135 psi	3" NPTF	2-1 1/2" NPT 1-2 1/2" NPT	Length: 24" Width: 24" Height: 23"	190 lbs. (86 kg)	\$5,750.00
HE 20H	Volume	500 gpm @ 20 psi 300 gpm @ 55 psi 100 gpm @ 65 psi	Assem. #1 - 4" NPTF Assem. #2 - 4" NH Assem. #3 - 4" NH	3" NPT 1-2 1/2" & 2-1 1/2" NPT 2-2 1/2" NH	Length: 26" Width: 21" Height: 20"	215 lbs. (98 kg)	Assem. #1 - \$6,610.00 Assem. #2 - \$6,980.00 Assem. #3 - \$7,510.00

23 HP Vanguard

Also available in 27 hp water-cooled

- ▶ Dependable Briggs & Stratton Vanguard engine
- ▶ Booster tank fill
- ▶ Multiple Hand Lines
- ▶ Wildland/Attack fire suppression
- ▶ 2-year engine, lifetime ignition warranty

PRICE SPECIAL

Features: Briggs & Stratton Vanguard 23 HP, OHV, air cooled, 4-cycle, V-Twin cylinder, vertical shaft, 2.97"x2.75" bore stroke, duel element air cleaner, electric start "Magnetron" w/recoil rope back-up, float fixed main jet carburetor, mechanical governor, ball bearing - PTO side replac. sleeve - mag side, aluminum, cast iron sleeve bore 90° V-Design cylinder, full pressure with spin-on oil filter lubrication, noise suppression package is standard.

Options: Illuminated gauge panel, adapters & caps, spark arrest muffler, battery kit, wrap around frame, and recoil rope.



2BE 23V

Model	Uses	Performance	Inlet	Outlet	Dimensions	Weight	Price
1-1/2AGE 23V	Pressure	120 gpm @ 145 psi 50 gpm @ 255 psi 20 gpm @ 265 psi	2" NPT	2-1 1/2" NPT	Length: 24" Width: 21" Height: 24"	180 lbs. (82 kg)	\$5,680.00
2-1/2AGE 23V	Pressure	290 gpm @ 45 psi 100 gpm @ 135 psi 50 gpm @ 175 psi	2 1/2" NPT	2-1 1/2" NPT and 1-2 1/2" NPT	Length: 24" Width: 21" Height: 24"	190 lbs. (86 kg)	\$5,780.00
2BE 23V	Volume	390 gpm @ 30 psi 200 gpm @ 110 psi 100 gpm @ 140 psi	3" NPT	2-1 1/2" NPT and 1-2 1/2" NPT	Length: 24" Width: 21" Height: 24"	195 lbs. (89 kg)	\$5,620.00
HE 23V	Volume	535 gpm @ 20 psi 200 gpm @ 85 psi 50 gpm @ 185 psi	Assem. #1 - 4" NPT Assem. #2 - 4" NH Assem. #3 - 4" NH	3" NPT 1-2 1/2" NPT & 2-1 1/2" NPT 2-2 1/2" NH	Length: 24" Width: 21" Height: 24"	220 lbs. (100 kg)	\$6,170.00 \$6,610.00 \$7,120.00