<u>PUMPS</u>

LDMBC Pump

AutoCAFS -Air Pressure Balancing Valve

Compact oil reservoir with

built-in oil separator

Available as a complete module Air Distribution Manifold

Electric "Hot Shift" Clutch

Air Compressor Intake Valve Vertical Mounted (Shown) Horizontal Mounted (Optional)

APPLICATIONS

- Aerial
- Pumper
- Rescue pumper
- Pumper tanker

STANDARD EQUIPMENT

- 4-2¹/₂" NH, ¹/₄ turn-ball valves
- 2-5 or 6" NH suction adapters and caps, discharge and suction companion flanges as needed
- 1610 or 1710 full round yokes standard
- Output shaft for AZ01803 220 cfm compressor package
- Remote packing adjustment cables

Features: 1000-1750 gpm, single stage, centrifugal, midship mounted pump forward.

Optional Equipment: Foam manifold, air distribution manifolds, CAFS valve packages, FoamPro system can be pre-installed and tested.





AutoCAFS Commander control system. Indicates and operates all CAFS functions and system information.

	Performance			
Model	Simultaneous Water	Simultaneous Compressed Air	Dimensions	Weight
LDMBC	1250 gpm @ 125 psi	220 cfm @ 125 psi	Length: 40" Width: 76"	2,200 lbs. (997 kg)
			Height: 46"	

LDMBC

Front View