# Deluge Tips, Smooth-Bore Tips and Devices



#### A. Deluge Tip

- ▶ 9" long ▶ 1<sup>1</sup>/<sub>2</sub>" orifice
- 21/2" base thread Hardcoat aluminum

Hardcoat aluminum

►Built-in stream straightener

► Hardcoat aluminum

► Hardcoat aluminum

\$216.95

Ship wt. 1 lb.

AJ524 Deluge Tip \$141.95

### E. 6" Smooth Bore Tip

- ▶6" long
- 11/2" base thread
- ►1<sup>1</sup>/<sub>8</sub>" orifice ► Hardcoat aluminum

Hardcoat aluminum

 $^{15}/_{16}{}^{\prime\prime}$  x  $^{1}/_{2}{}^{\prime\prime}$  orifice

Ship wt. 1 lb.

AJ530 6" Smooth Bore Tip \$99.95

# B. Discharge Pipe

Two sets of stream straightener fins ensure maximum reach and solid streams. For use on all monitors. Max. flow rate 1,750 GPM. Ship wt. 1 lb.

- ▶ 11" or 16" long
- ≥ 2<sup>1</sup>/<sub>2</sub>" inlet and discharge
- AJ525 Discharge Pipe, 11' \$195.95

Discharge Pipe, 16"

# C. Deluge Tip with Stream Straightener

▶ 11" long

AJ526

- ≥ 2<sup>1</sup>/<sub>2</sub>" base thread
- ▶ 1<sup>1</sup>/<sub>2</sub>" orifice

Ship wt. 1 lb.

Deluge Tip with Straightener \$194.95 AJ527

## F. Double Stack Tip

- ▶ 6<sup>3</sup>/<sub>4</sub>" long
- 11/2" base thread
- ▶ 1" female base thread
- Ship wt. 1 lb.

AJ533 Double Stack Tip \$152.95

#### G. Deluge Stack Tip

- ▶ 12" and 17" long
- 21/2" base thread
- Two middle threads, underwriters P.P.S. 2" NH
- 1¹/₂" top thread
- ► 1³/<sub>8</sub>", 1¹/<sub>2</sub>", 1³/<sub>4</sub>" orifices
- Hardcoat aluminum

Ship wt. 3 lbs.

AJ534 12" Triple Deluge Stack Tip \$251.95 AJ537 17" Quad Deluge Stack Tip \$301.95

# D. Stream Straightener

Use with all large-volume discharge devices for increased range and effective reach. Ship wt. 1 lb.

- ▶ 3" long
- ≥ 2<sup>1</sup>/<sub>2</sub>" inlet and outlet threads

Stream Straightener \$69.95

#### H. Triple Handline Stack Tip ▶ 1¹/₄" top thread

- ▶8<sup>1</sup>/<sub>2</sub>" long
- ▶11/2" base thread
- ▶11/2" middle thread
- ▶ 1", 11/8", 11/4" orifices
  - ▶ Hardcoat aluminum

Ship wt. 1 lb.

Triple Handline Stack Tip AJ536

\$226.95



# A. Underwriters & Factory Mutual Playpipes

Made with 21/2" base and 30" long. Screw nozzle, swivel handle, Marlin wound and painted red. Standard discharge tip 11/8". Ship. wt. 10 lbs.

288	Underwriters Playpipe, 30" NH	\$269.95
R661	Factory Mutual Playpipe, 15" NH	\$265.95
B45801	Underwriters Playpipe Tip	
	with 11/8" Discharge (Brass Tip Only)	\$56.95

## B. Hose Pipes

Cast Brass, for  $1^{\frac{1}{2}}$ " and  $2^{\frac{1}{2}}$ " fire hose. Ship. wt. 5 lbs.

E137	1 <sup>1</sup> / <sub>2</sub> " Pipe, Discharge <sup>1</sup> / <sub>2</sub> ", 10"L	\$27.95
E138	21/2" Pipe, Discharge 1", 12"L	\$54.95

# Straight Bore Nozzles

- ▶ 4<sup>1</sup>/<sub>2</sub>" in length
- Outlets available in: 1/2", 3/4", 15/16", 1, 11/16", and 11/8".
- 1¹/₂" Rigid Base NST

BB032 1/2" Outlet Straight Bore Nozzle \$87.95 BB033 3/4" Outlet Straight Bore Nozzle \$87.95

BB034 <sup>15</sup>/<sub>16</sub>" Outlet Straight Bore Nozzle \$87.95

BB035 1" Outlet Straight Bore Nozzle \$87.95

# Stacked Tips

Sold as a set, taper from 13/4" to 11/8" to 1" Constructed of anodized aluminum,

colored gold 11/2" Rigid Base NST

BB036 Stacked Tips, Outlet 13/4" to 11/8" to 1" (Set of 3) \$224.95

