

TankVision

Water/Foam Volume Indicators

The TankVision is your solution to tank volume monitoring. Available for both water and foam, each with distinctive color and styling. Mini-displays for remote in-cab mount are similarly color coded. A single TankVision primary display can drive an unlimited number of remote displays as well as in cab mini-displays. For remote warning, an optional Large Light Driver is available with current draw capability up to 5 amp per light. The TankVision uses a pressure transducer to provide a highly accurate liquid volume. *Ship. wt. 3 lbs.*

- ▶ Ultra Brite LEDs display exact water/foam remaining in tank
- ▶ Flashing warning when actual volume is below 25%
- ▶ Unit self-calibrates to any size/shape tank regardless of dimensions
- ▶ Rugged waterproof cast aluminum housing
- ▶ Easy-to-operate and install



AR317	TankVision Gauge Kit, with Master Display Sensor and 10' Cable	\$429.95
AS309	TankVision In-Cab Mini Display for Water	\$152.95
AS312	TankVision Remote Driver for "Large Lite" Display	\$255.95

Quint Water Level Monitor

Five-light readout that uses green, amber and red lenses with red flashing refill light. Complete unit consists of readout, bezel plate and stainless steel sensor. Additional readout available without sensor. *Ship. wt. 5 lbs.*

Specify: 12 or 24-volt, positive or negative ground and tank dimensions

X940	Quint Water Level Monitor	\$233.95
X942	Additional Readout	\$129.95

Service Kit for X940 includes: 5-domed lenses, 4-replacement bulbs, 1-flasher replacement bulb, 2-plate screws and 1-bulb extracting tool

AB017	Service Kit for Quint Level Monitor	\$24.95
--------------	-------------------------------------	---------



Water Level Monitor

Easy-to-read indicator. Water Level Monitor uses four red lights to show water level in sequence as water drains away. Complete unit includes control box, bezel plate, and stainless steel sensor. *Ship. wt. 1 lb.*

Specify: 12 or 24-volt, positive or negative ground & tank dimensions

R157	Water Level Monitor	\$189.95
-------------	---------------------	----------

Service Kit for R157 includes: 4-domed lenses, 4-replacement bulbs, 2-plate screws & 1-bulb extracting tool

AB016	Service Kit for Water Level Monitor	\$19.95
--------------	-------------------------------------	---------

R157

Tachometer Gauge

Modernize your present apparatus with these precision gauges. Accurate within 2% of full scale on conventional and transistorized 12-volt positive or negative ground ignition. Chrome-plated brass with double-strength, curved glass window. The pointer is painted fluorescent red for easy visibility. Will not produce radio interference. Easily installed and comes complete. Measures 3³/₁₆" in diameter. *Ship. wt. 1 lb.*

- ▶ Highest quality components
- ▶ Meets rigid specifications
- ▶ Shock and vibration-proof
- ▶ Guaranteed waterproof

L918	Tachometer, RPM Range 0-6000, for 4-6-8 Cylinder Vehicles	\$38.95
W483	Tachometer, RPM Range 0-4000, for Diesel Engines, with Sender	\$79.95



Liquid-Filled Gauges

Eliminates Needle Pulsation for Accurate and Easy Readings

Crystal-clear Interlube keeps needle fluctuation to a minimum. The SUBZ II freeze-proof isolator keeps gauge working down to -40°F. It's also weathertight so there is no condensation; stops corrosion. Lubricates internal parts, stops wear, maintains accuracy under temperature fluctuations. Zytel (nylon) case with bright stainless steel trim ring has plexiglass lens. 6" gauge has cast aluminum case. Gauges measure 0-600 psi and up to 30" vacuum. *Ship. wt. 5 lbs.*

Black and white face gauges without logo are available

T179	2 ¹ / ₂ " Liquid-Filled Compound Gauge	\$45.95
AK075	2 ¹ / ₂ " Liquid-Filled Compound Gauge with Bottom Connection	\$43.95
T180	3 ¹ / ₂ " Liquid-Filled Compound Gauge	\$71.95
AK076	3 ¹ / ₂ " Liquid-Filled Compound Gauge with Bottom Connection	\$71.95
T181	4 ¹ / ₂ " Liquid-Filled Compound Gauge	\$96.95
U966	Similar to T181 but with 1000 psi	\$96.95
U967	6" Liquid-Filled Compound Gauge	\$264.95



Panel Hole Size Needed for Gauge Installation:

2.5"	3.5"
2.69" (68.33mm)	3.78" (96.01mm)
4.5"	Tolerance
4.85" (123.19mm)	-.020" (0.51mm)