

## Portable Drum Lifter/Rotator/Transporter

The multifunctional unit, *model DRUM-LRT*, features a hand pump to lift drums from ground level to a raised height of 68" to bottom of drum in horizontal position. For use with 55-gallon steel, plastic, and fiber drums. A hand crank gear mechanism provides the controlled 360° rotation of the drum. A floor lock is standard to stabilize the unit in a fixed position.

*Model DRUM-LRT-DC* has a 12V DC battery powered lift operation and a hand crank gear mechanism rotation (on-board charger standard). Minor assembly required.

MODEL NUMBER	OVERALL SIZE (W x D x H)	RAISED HEIGHT	CAPACITY (POUNDS)	NET WT. (POUNDS)
<b>MANUAL OPERATION</b>				
<b>DRUM-LRT</b>	36¼" x 61" x 88"	68"	550	402
<b>12V DC POWER</b>				
<b>DRUM-LRT-DC</b>	36¼" x 61" x 88"	64"	550	629



DC POWER LIFT  
model DRUM-LRT-DC

HAND PUMP LIFT  
model DRUM-LRT

## Economical Mechanical Drum Transporters

48 Hours  
to Ship

Unique portable unit designed to lift and transport plastic, steel, and fiber drums with a top lip. Steel jaw securely grips the top lip of the drum. Available with either a manual mechanical ratchet or a foot pump hydraulic lift mechanism. Straddle legs rotate for access to drums on pallets. Unit rolls on (4) 8" x 2" phenolic casters. The push handle folds down for easy access to ratchet and foot pump. All welded steel construction. Powder coated with a safety yellow finish. Optional scale weighs drums to an accuracy of +/-0.5 lbs. Optional scale includes (6) D cell batteries and an AC adaptor.

MODEL NUMBER	DESCRIPTION	JAW SERVICE RANGE	CAPACITY (POUNDS)	NET WT. (POUNDS)
<b>DCR-880-M</b> Ⓢ	HAND RATCHET	27" TO 47"	880	170
<b>DCR-880-H</b> Ⓢ	FOOT PUMP	27" TO 47"	1,500	190
<b>DCR-880-H-HP</b> Ⓢ	FOOT PUMP	27" TO 74"	880	240
<b>DCR-SCALE</b>	WEIGHT SCALE ADD-ON			70



model  
DCR-SCALE



model  
DCR-880-H

POWDER  
COATED  
TOUGH



model  
DCR-880-M



DVD or VIDEO  
AVAILABLE



model  
DCR-880-H-HP

## Portable Drum Jacks

These Drum Jacks are the perfect solution to any of your drum transporting needs. Compact design allows for maximum maneuverability in restrictive areas. All steel construction.

*Model DRUM-55-36* accepts both 30 and 55-gallon plastic, steel, and fiber drums with a top lip. The front rigid wheels are 6" x 2", while the rear swivel casters are 3" x 1½".

*Model DRUM-55FP* has an adjustable beak design which allows it to grab 30 and 55-gallon steel, plastic, or fiber drums. Drums can easily be placed on or removed from pallets, spill containers, and scales. Available with built-in scale feature, see below.

*Model DRUM-55S* has a unique grapple to hold 55-gallon drums securely into the steel saddle prior to lifting it vertically. The drum is held in this position during transit, enabling open drums to be handled without spillage.

*Model DRUM-55-PY* has the capability to move plastic drums conveniently with minimum effort.

*Model DRUM-SCLG* & *DRUM-SCLF* have a scale readout built into Drum Jack model DRUM-55FP. The scale allows the drum to be weighed and moved all with the same piece of equipment. The scale features a capacity of 1,000 pounds with an accuracy of +/-0.5 lbs. 12V DC operation with battery and charger included. Stainless steel scale components. NEMA 4 scale read-out housing swivels 360° for maximum viewing convenience.

MODEL NUMBER	OVERALL SIZE (W x D)	LIFT HEIGHT	CAPACITY (POUNDS)	NET WT. (POUNDS)
<b>DRUM-55-36</b>	34¾" x 29"	18"	500	168
<b>DRUM-55FP</b>	43½" x 39"	20"	1,000	373
<b>DRUM-55S</b>	29" x 41"	4"	1,000	180
<b>DRUM-55-PY</b>	29" x 41"	4"	660	220
<b>DRUM-SCLG</b>	DRUM-55FP WITH GENERAL READOUT SCALE			389
<b>DRUM-SCLF</b>	DRUM-55FP WITH INTRINSICALLY SAFE READOUT SCALE			397



model DRUM-55FP



model DRUM-55-36

New



model DRUM-55-PY



model DRUM-55S



model DRUM-55FP  
SHOWN WITH SCALE,  
model DRUM-SCLF



model DRUM-SCLG



model DRUM-SCLF