

Modular Guard Systems

Modular Guard System can be ordered to fit almost any application. Designed for quick and easy assembly. Railing sections are installed and secured to each post with a single bolt. Select from different railing lengths to custom fit your application. Railing systems are made from heavy-duty 3" square steel tubing. Wall mounting posts may be used to secure guard assembly to a wall. Durable safety yellow powder coat finish. Steel construction. All components sold separately.

RAILING SECTION				
MODEL NUMBER	EFFECTIVE LENGTH	OVERALL LENGTH	SQUARE TUBE (O.D.)	NET WT. (POUNDS)
MG-R-4	48"	56"	3"	26
MG-R-6	72"	80"	3"	38
MG-R-8	96"	104"	3"	49
MG-R-10	120"	128"	3"	60
MG-R-12	144"	152"	3"	71


MOUNTING POSTS				
MODEL NUMBER	DESCRIPTION	STYLE	OVERALL HEIGHT	NET WT. (POUNDS)
MG-CP-36-1	CORNER POST	SINGLE RAIL	36"	37
MG-CP-36-2	CORNER POST	DOUBLE RAIL	36"	49
MG-SP-36-1	STRAIGHT POST	SINGLE RAIL	36"	37
MG-SP-36-2	STRAIGHT POST	DOUBLE RAIL	36"	49

MOUNTING OPTIONS		
MODEL NUMBER	DESCRIPTION	NET WT. (POUNDS)
MG-WP-A	WALL MOUNTING POST - POST TUBING	7
MG-WP-B	WALL MOUNTING POST - RAILING SECTION TUBING	8
MG-KIT	CONCRETE ANCHOR BOLTS (4 ANCHORS)	4



Fits against walls to protect drains or piping

Individual Components are Installed On-Sight



DOUBLE RAIL CORNER POST model MG-CP-36-2

SINGLE RAIL STRAIGHT POST model MG-SP-36-1



WALL MOUNT series MG-WP



RAILING SECTION series MG-R

Adjustable Steel Safety Railings

The Adjustable Railing can be used to create walking paths or as a sliding gate for continuous run handrail systems. 1 3/4" square tubing is painted safety yellow for high visibility. Unit stands 42" high and has a 21" mid-rail. Optional 96" long toe board is available. Safety yellow powder coat finish.

MODEL NUMBER	DESCRIPTION	SERVICE RANGE	NET WT. (POUNDS)
ASR-96	WITHOUT TOEBOARD	96" TO 168"	54
ASR-96-4-TB	WITH 4" HIGH TOEBOARD	96" TO 168"	61



Heavy Duty Column Protectors

Two-piece design for protecting in-plant columns and other vertical support members. Hardware is included to connect both pieces together. Heavy-duty welded steel construction. Each base plate includes (4) pre-drilled mounting holes. Concrete installation hardware sold separately. Powder coat safety yellow finish.

MODEL NUMBER	HEIGHT	INSIDE WIDTH	INSIDE LENGTH	NET WT. (POUNDS)
CGP-24	24"	20"	20"	132
CGP-36	36"	20"	20"	150
CGP-48	48"	20"	20"	168
CGP-ABK	CONCRETE ANCHOR BOLTS (8) 3/4" x 4"			4



POWDER COATED TOUGH

Gantry/Jib Guard

Prevent costly damage to steel columns, pipe, and tubing from carts and fork trucks. Solid steel design is constructed of 1/2" thick material for maximum strength. Ideal for fixed jibs and gantry cranes. Mounting plate measures 16" wide by 13 1/2" deep and features (6) pre-drilled mounting holes.

MODEL NUMBER	INSIDE WIDTH	INSIDE DEPTH	OVERALL HEIGHT	NET WT. (POUNDS)
CG-42	10-1/4"	10-1/8"	42"	150
CG-ABK	CONCRETE ANCHOR BOLTS (6) 3/4" x 4"			4



POWDER COATED TOUGH

48 Hours to Ship