Folding Security Trucks

This portable cart is designed to safely hold your valuable equipment. All welded components and wire mesh walls combine to make this truck extremely tough and strong. Center shelf folds down to create (2) $32\frac{1}{2}$ "H areas or remains in the up position to provide full $66\frac{1}{2}$ "H area of storage. Special door locking latch and padlock clasp (padlock not included) for securing stored contents. Rolls on 6" x 2" molded-on rubber casters, 4 swivel. The overall size is 27"W x 44"L x $76\frac{1}{2}$ "H. The usable size with shelf down is $24\frac{1}{2}$ "D x $42\frac{1}{2}$ "W x $32\frac{1}{2}$ "H and with the shelf up 24"D x $41\frac{1}{2}$ "W x $66\frac{1}{2}$ "H. Unit will fold down to 51"D x 76"W x 12"H for storage or transport.

MODEL Number	FINISH	OVERALL SIZE (W x L x H)	CAPACITY (POUNDS)	NET WT. (POUNDS)
FST-2744-2	PAINTED GREY	44" x 27" x 76½"	2,000	240
FST-2744-2-SS	STAINLESS STEEL	44" x 27" x 761/2"	2,000	255

Traction-Drive Carts

Unique carts feature built-in traction-drive system for easy transportability. Ideal for applications including mail rooms, hospitals, supermarkets, hotels and warehouses. Features 450W electric drive motor with two 40Ah batteries for power. 110V AC internal battery charger is included. Variable throttle speed control for precise maneuvering and positioning is located in the handle. Units roll smoothly on (2) 8" rubber front wheels and (2) 10" pneumatic rear wheels. Walking speed is 0-3.7 mph when unloaded and 0-2.5 mph when loaded. Speed control is conveniently located in handle. Handle pivots back towards operator and includes horn and emergency stop. Each shelf includes a non-slip rubber top surface. Includes on-board charger.

MODEL Number	PLATFORM Size (W x L)	SHELF HEIGHT	BOTTOM SHELF Capacity (LBS.)	TOP SHELF Capacity (LBS.)	NET WT. (LBS.)
E-CART	28" x 52"	13¾"	770		280
E-CART-2	28" x 52"	13¾"/40½"	770	220	325

DVD or VIDEO AVAILABLE

Off-Road Traction Drive Powered Cart

Ideal on the farm or in the factory. Features a robust 24 volt DC 600 watt drive motor (2) 12 volt batteries, low/high speed, headlights, wire storage, basket, and forward/reverse. Low speed is $1\frac{1}{2}$ m.p.h. High speed is $1\frac{1}{8}$ m.p.h. (reverse is $1\frac{1}{2}$ m.p.h.). Unit runs for approximately 4 hours before it needs charged.

MODEL	PLATFORM SIZE	CAPACITY	WHEEL SIZE	NET WT.
Number	(W x L x H)	(Pounds)		(LBS.)
OROAD-400	33½" x 72" x 17"	400	3½" x 12" rear 6" x 14" front	326

Manual Scooter with Brake

Get where you need to be quickly and safely with our manually powered Scooter. Sturdy foot rest includes a manually operated rear brake that safely stops the Scooter at your destination. Fixed height handle bars control front wheel maneuvering through narrow aisles and doorways. A 14" long x 18" wide front platform holds up to 55 lbs., ideal for crates, boxes, and other small loads. Rolls on high performance 3" polyurethane wheels. Ships knockdown. Optional bolt-on basket available separately. Capacity of the basket is 15 lbs.

MODEL Number	TOTAL CAPACITY (POUNDS)	OVERALL SIZE (W x L)	PLATFORM SIZE (W x L)	NET WT. (LBS.)
SCOOT-500®	250	18" x 36"	18" x 14"	30
SCOOT-BSK®	OPTIONAL BOLT-ON WIRE BASKET			4

Industrial Bicycles

A quick, easy and safe way to move around large facilities. Built with rider friendly features and the ability to handle various loads while moving through a facility with ease and efficiency. A three wheel design includes hand brakes for sure stopping. Adjustable height seat for different sized people. Large payload / cargo area included. Additional options available, contact factory.

MODEL Number	OVERALL SIZE (W x L x H)	CAPACITY (POUNDS)	COLORS	NET WT. (LBS.)
IBIKE-3-DC-R	29" x 70" x 43"	250	RED	65
IBIKE-3-DC-B	29" x 70" x 43"	250	BLUE	65
IBIKE-3-DC-G	29" x 70" x 43"	250	GREEN	65
IBIKE-3-DC-P	29" x 70" x 43"	250	PURPLE	65
IBIKE-2-DCHH-Y	29" x 70" x 43"	350	YELLOW	81
IBIKE-2-DCHH-BL	29" x 70" x 43"	350	BLACK	81
IBIKE-3-HH-Y	33½" x 79" x 45"	500	YELLOW	106
IBIKE-3-HH-BL	33½" x 79" x 45"	500	BLACK	106







