


OUTSIDE MOUNTING (STANDARD)



Manual Built-In Carousel for Scissor Tables

Position pallets, boxes, or crates without ever stepping around the table. This sleek flush mounted carousel smoothly rotates 360°. Easy to use operation. Capacity is 4,000 lbs. Carousel adds 1" to scissor table service range. Carousel diameter is 45". Platform size is 48" x 48". Scissor table not included. Option for new table purchase only.

MODEL Number	DESCRIPTION	
ROTATE	MANUAL BUILT-IN CAROUSEL FOR SCISSOR TABLE	

Accordion Skirting

Accordion Skirts have a functional purpose as well as a safety purpose. Complies with the OSHA pinch point specifications. The functional advantage is minimizing dirt and debris accumulation under the platform. Dirt can contaminate electrical and hydraulic components. Life expectancy of both can be substantially reduced by this contamination. Debris such as raw materials, boards, or pallets can restrict the scissor or table movement. Accordion skirts serve to keep debris from damaging the operating mechanism, hydraulic components, or electrical parts. Safety is enhanced by keeping arms, legs, fingers, and toes out from under the table. Standard electric toe-guards are not included when scissor table is fitted with accordion skirt option.

TABLE SPECIFICATIONS:

1) TABLE WIDTH, W =	
2) TABLE LENGTH, L =	
3) TABLE RAISED HEIGHT, H =	"
4) TABLE LOWERED HEIGHT, D =	"

CALCULATION FORMULA: (3" convolutions)

All Dimensions are in Inches

W = Width of Platform L = Length of Platform H = Raised Height

ACCORDION SKIRTING

CUSTOMER INSTALLED (including hardware)

ACCORDION SKIRTING

FACTORY INSTALLED (includes extra packaging)

 $((W'' + W'' + L'' + L'') \times H'') \div 144 = Square Feet$

WEIGHT:

0.5 lbs./ft2

REPAIR KIT FOR ACCORDION SKIRTING model AC-RK

Rigid PVC and Roller Curtains Also Available - Contact Factory



WIRELESS REMOTE CONTROL IS FACTORY INSTALLED

Wireless Remote Controls

Put the power in your hands with the Wireless Remote Control System, series RC-460. This lightweight, two-button, remote control gives you the freedom to control your scissor table from a range up to 150 feet (range can be adjusted for optimum signal strength and can be reduced if required). Unit is also available in a four-button model for lift and tilt tables. The remote control measures 4" wide x 6" high x 2" thick.

Approved to meet part 15 of the Federal Communications Code. Designed to prevent crosstalk and false triggering from stray radio frequency. Scissor table not included.

MODEL NUMBER	DESCRIPTION	NET WT. (POUNDS)
RC-460-2	2-BUTTON CONTROL (LIFT-HOLD-LOWER CIRCUIT)	1
RC-460-4	4-BUTTON CONTROL (LIFT AND TILT CIRCUIT)	1

RETROFIT AVAILABLE - CONTACT FACTORY