

Fully Powered Electric Pallet Trucks

Fully powered pallet truck for easy and quick operation. Includes fingertip raise and lower buttons. Easy-to-operate throttle for forward and reverse direction. Throttle offers infinite forward and reverse speeds. Safety features include a horn and belly reverse button. Units run off 24V batteries with battery charger standard. The 3,000 pound capacity models use two 12V batteries with 70Ah rating. The 4,500 pound capacity models use four 12V batteries with 180Ah rating. Units will typically achieve a minimum of eight (8) hours of service on one full charge.

MODEL NUMBER	CAPACITY* (Pounds)	FORK SIZE (W x L)	SERVICE Range	OVERALL SIZE (W x L x H)	NET WT. (LBS.)
EPT-2047-30	3,000	20" x 47"	3.2" to 7.8"	28" x 65" x 49"	660
EPT-2547-30	3,000	25" x 47"	3.2" to 7.8"	28" x 65" x 49"	671
EPT-2048-45	4,500	20" x 48"	3.4" to 8"	30" x 78½" x 49"	990
EPT-2748-45	4,500	27" x 48"	3.4" to 8"	30" x 78½" x 49"	1012

*CONTINUOUS DUTY RATING / ADD 500 LBS. CAPACITY FOR INTERMITTENT DUTY RATING

Wheel Nose Pallet Trucks

- Take the Guess Work Out of Close Pallet Placement
- Optimize Floor and Truck Space with this Innovative Pallet Truck

The Wheel Nose Pallet Truck is designed to position pallets or skids closely together. The fork end is set back from the front rollers allowing for one pallet pick up at a time. The unit has a rubber grip handle with a three position lever for easy operation and maneuvering. This heavy-duty unit is rated at 5,000 pounds capacity and has a service range from $3\frac{1}{2}$ " to 8". Unit includes two articulating steering wheels and two front load rollers. Spring loaded loop handle automatically returns to vertical position when not in use. 38" forks are used for maneuvering in tight spaces.

MODEL NUMBER	DESCRIPTION	CAPACITY (POUNDS)	OVERALL FORK SIZE (W x L)	SERVICE Range	NET WT. (POUNDS)
PM5-2038-WN	WHEEL NOSE	5,000	20" x 38"	31/2" to 8"	260
PM5-2738-WN	WHEEL NOSE	5,000	27" x 38"	31/2" to 8"	280



• Pallet Trucks for Corrosive and Sanitary Environments

STAINLESS STEEL AND STAINLESS STEEL FRAME & FORKS

Ideal for sanitary, pharmaceutical, medical, food, and wet environments. Choose either type 304 stainless steel frame and forks only or 100% type 304 stainless steel pallet truck for long life in even the most harsh environments. 5,500 lbs. capacity.

GALVANIZED, ZINC AND CHROME PLATED

Designed for corrosive or wet environments, these full-featured pallet trucks were designed for chemical, pharmaceutical and wash-down applications. 5,500 lbs. capacity.

MODEL		OVERALL FORK	FORK	NET WT.
NUMBER	DESCRIPTION	DIMENSIONS	SERVICE RANGE	(LBS.)
PM5-2048-SS	STAINLESS STEEL	20"W x 48"L	2-7/8" to 7-3/4"	300
PM5-2748-SS	STAINLESS STEEL	27"W x 48"L	2-7/8" to 7-3/4"	327
PM5-2748-SFF	SS FRAME & FORKS	27"W x 48"L	2-7/8" to 7-3/4"	327
PM5-2748-S-G	GALVANIZED	27"W x 48"L	2-7/8" to 7-3/4"	327
PM5-2748-S-Z	ZINC COATED	27"W x 48"L	2-7/8" to 7-3/4"	322
PM5-2748-CP	CHROME PLATED	27"W x 48"L	2-7/8" to 7-3/4"	322

Skid Adapters for Pallet Trucks

Increase your pallet truck service by 3" to handle skids with the Skid Adapter. Adapts to model PM5- "Pallet Master Pallet Trucks" only with an overall fork width of either 20" or 27" and a minimum fork length of 48". Skid adapter may be rotated into vertical position for normal pallet truck use.

MODEL NUMBER	DESCRIPTION	ACCOMMODATES Fork dimensions	INCREASED HEIGHT	NET WT. (POUNDS)
PM5-20SA	SKID ADAPTERS	20"W x 48"L	3"	60
PM5-27SA	SKID ADAPTERS	27"W x 48"L	3"	75



