## **Self-Elevating Spring Tables**

Self-Elevating Tables are designed to automatically raise or lower as materials are removed or added to the platform, keeping material at an ergonomic work height. These tables increase productivity while reducing potentially harmful bending and twisting motions. The counter balance springs can easily be added or removed to adjust weight-to-height sensitivity. This feature allows the user to conveniently set the table to fit each application. The ETS-230/460 has polyurethane casters while the ETS-840/1120 rolls smoothly on mold-on-rubber casters.

MODEL NUMBER	PLATFORM Size (W x L)	CAPACITY (POUNDS)	SERVICE Range	CASTER SIZE	OVERALL SIZE (W x L x H)	NET WT. (POUNDS)
ETS-230	20" x 20"	230	11" to 33"	4" x 11/4"	21" x 28" x 37"	189
ETS-460	20" x 20"	460	11" to 33"	4" x 11/4"	21" x 28" x 37"	216
ETS-840-30	30" x 30"	840	15" to 38"	4" x 2"	31" x 38" x 52"	448
ETS-1120-18	18" x 18"	1,120	15" to 38"	4" x 2"	19" x 26" x 52"	380
ETS-1120-24	24" x 24"	1,120	15" to 38"	4" x 2"	25" x 32" x 52"	385



## **Auto-Hite Carts**

The Auto-Hite Cart raises or lowers as materials are removed or added to the platform, keeping material at an ergonomic work height. Increase efficiency while reducing potentially harmful bending and twisting motions. Carts utilize tension springs which can be adjusted in order to fit each particular application. All steel construction with removable handle. Polyurethane casters are 5" x 2", (2) rigid and (2) swivel with brake. Overall height is 38".

MODEL Number	PLATFORM Size (W x L)	CAPACITY (POUNDS)	SERVICE Range	MOVEMENT* LBS. / INCH	OVERALL Size (W x L)	NET WT. (LBS.)
SCSC-500-2040®	20" x 40"	500	14" to 34"	25# / 1"	20" x 45"	359
SCSC-500-4242	42" x 42"	500	14" to 34"	25# / 1"	42" x 45"	366
SCSC-1000-4242®	42" x 42"	1,000	14" to 34"	50# / 1"	42" x 45"	368
SCSC-1000-4848	48" x 48"	1,000	14" to 34"	50# / 1"	48" x 53"	419
SCSC-2000-4848	48" x 48"	2,000	14" to 34"	100# / 1"	48" x 53"	531

<sup>\*</sup>APPROXIMATE RATIO



## **Self-Elevating Lift Carts**

These carts raise and lower as materials are removed or added to the platform. Automatic height adjustment provides ergonomic work positioning to increase productivity and decrease work related repetitive motion injuries. Heavy-duty steel construction with removable bolt-on handle. 5" x 1" poly-on-steel, 2 rigid and 2 swivel casters with brake standard.

MODEL Number	PLATFORM SIZE (W x L)	CAPACITY (POUNDS)	SERVICE Range	OVERALL SIZE (W x L x H)	NET WT. (POUNDS)
SCSC-400-2032	20" x 32"	400	13¾" to 30"	20" x 40" x 301/2"	200
SCSC-800-2040	20" x 40"	800	141/2" to 31"	20" x 48" x 35½"	300



## **Long Deck Carts**

The Long Deck Cart is perfect for sheet and strip handling, ergonomic load positioning, and handling long awkward material loads. Platform height is adjusted with manual hydraulic foot pump. Structural steel base helps to distribute the load evenly. Unit comes standard with (4) swivel 5" x 2" polyurethane casters and dual floor locks. (1/4" thick deck)

MODEL Number	PLATFORM SIZE (W x L)	CAPACITY (POUNDS)	RAISED HEIGHT	LOWERED HEIGHT	NET WT. (POUNDS)
LDLT-3060	30" x 60"	2,000	48"	31"	518
LDLT-3072	30" x 72"	2,000	48"	31"	563
LDLT-3096	30" x 96"	2,000	48"	31"	638
LDLT-30120	30" x 120"	2,000	48"	31"	771

AC POWER 115, 208-230, 460V - 1 OR 3 PHASE, MODEL LDLT-AC



DC POWER WITH BATTERY, MODEL LDLT-DC FACTORY AIR/OIL, MODEL LDLT-AIR