



Experience Drying On a Whole New Level.

Products

Service

Financing

About ADC

Careers

EcoSmart Dryers
Coin-Op
On-Premise Laundry
Industrial
Contamination Control
Custom Applications
Product Literature
Request a Dealer
Industry Links



ES-30
ES-30/30
ES-3131
ES-50
ES-76
SL-20
SL-2020
SL-31
SL-3131
SL-50
SL-75
AD-25V
AD-30V
AD-285
AD-50V
AD-758V
AD-78
AD-115
AD-120
AD-170

The premise is reliability. The maker is ADC.

From hotels to hospitals and nursing homes to health clubs, efficient and reliable on-premise laundry facilities are a critical component of the overall operations. Most businesses and institutions can't afford to experience downtime and at ADC we don't think they should have to. That's why we offer a variety of different dryer models that perform flawlessly even when demands are high. If you're looking for efficiency and round-the-clock reliability, look to ADC.



SL-20

- **Capacity:** 20-lb (9.07 kg)
- **Tumbler Volume:** 7-1/2 cu ft (212.38 L)
- **Heat Input:** 40,000 Btu/hr (10,080 kcal/hr)
- **Airflow (60 Hz):** 230 cfm (6.51 cmm)
Airflow (50 Hz): 191 cfm (5.40 cmm)



SL-2020

- **Capacity:** 20-lb (9.07 kg) per pocket
- **Tumbler Volume:** 7-1/2 cu ft (212.38 L) per pocket
- **Heat Input:** 40,000 Btu/hr (10,080 kcal/hr) per pocket
- **Airflow (60 Hz):** 230 cfm (6.51 cmm) per pocket
Airflow (50 Hz): 191 cfm (5.40 cmm) per pocket



SL-31

- **Capacity:** 30-lb (13.61 kg)
- **Tumbler Volume:** 11.04 cu ft (312.62 L)
- **Heat Input:** 55,000 Btu/hr (13,860 kcal/hr)
- **Airflow (60 Hz):** 360 cfm (10.19 cmm)
Airflow (50 Hz): 300 cfm (8.49 cmm)

SL-3131

- **Capacity:** 30-lb (13.61 kg) per pocket
- **Tumbler Volume:** 11.04 cu ft (312.62 L) per pocket



- Heat Input: 55,000 Btu/hr (13,860 kcal/hr) per pocket
- Airflow (60 Hz): 360 cfm (10.19 cmm) per pocket
- Airflow (50 Hz): 300 cfm (8.49 cmm) per pocket

SL-2929

- Capacity: 30-lb (13.61 kg) per pocket
- Tumbler Volume: 10.25 cu ft (290.25 L) per pocket
- Heat Input: 50,000 Btu/hr (12,600 kcal/hr) per pocket
- Airflow (60 Hz): 200 cfm (5.66 cmm) per pocket

SL-50

- Capacity: 50-lb (22.68 kg)
- Tumbler Volume: 16.02 cu ft (453.64 L)
- Heat Input: 90,000 Btu/hr (22,680 kcal/hr)
- Airflow (60 Hz): 525 cfm (14.87 cmm)
- Airflow (50 Hz): 437 cfm (12.37 cmm)

SL-75

- Capacity: 75-lb (34.02 kg)
- Tumbler Volume: 22.09 cu ft (625.52 L)
- Heat Input: 110,000 Btu/hr (27,720 kcal/hr)
- Airflow (60 Hz): 560 cfm (15.86 cmm)
- Airflow (50 Hz): 466 cfm (13.19 cmm)

AD-25V

- Capacity: 25-lb (11.3 kg)
- Tumbler Volume: 9.26 cu ft (262.0 L)
- Heat Input: 78,000 Btu/hr (19,656 kcal/hr)
- Airflow (60 Hz): 460 cfm (13 cmm)

AD-30V

- Capacity: 30-lb (13.6 kg)
- Tumbler Volume: 12.5 cu ft (353.96 L)
- Heat Input: 100,000 Btu/hr (25,200 kcal/hr)
- Airflow (60 Hz): 460 cfm (13 cmm)

AD-285

- Capacity: 30-lb (13.6 kg)
- Tumbler Volume: 10.18 cu ft (288.0 L)
- Heat Input: 72,000 Btu/hr (18,144 kcal/hr)
- Airflow (60 Hz): 375 cfm (11 cmm)

AD-50V





- Capacity: 50-lb (22.68 kg)
- Tumbler Volume: 18.30 cu ft (518.20 L)
- Heat Input: 150,000 Btu/hr (37,799 kcal/hr)
- Airflow (60 Hz): 750 cfm (21.24 cmm)
Airflow (50 Hz): 625 cfm (17.70 cmm)

AD-4545



- Capacity: 45-lb (20.41 kg) per pocket
- Tumbler Volume: 14.6 cu. ft. (413.43 kg) per pocket
- Heat Input: 112,000 btus/hr (28,230 kcal/hr) per pocket
- Airflow (60 Hz): 600 cfm (16.99 cmm) per pocket
Airflow (50 Hz): 500 cfm (14.16 cmm) per pocket

AD-758V



- Capacity: 75-lb (34.02 kg)
- Tumbler Volume: 21.50 cu ft (608.81 L)
- Heat Input: 175,000 Btu/hr (44,099 kcal/hr)
- Airflow (60 Hz): 1,000 cfm (28.32 cmm)
Airflow (50 Hz): 833 cfm (23.60 cmm)

AD-78



- Capacity: 75-lb (34.02 kg)
- Tumbler Volume: 22.40 cu ft (634.30 L)
- Heat Input: 204,000 Btu/hr (51,407 kcal/hr)
- Airflow (60 Hz): 1,200 cfm (33.98 cmm)
Airflow (50 Hz): 1,000 cfm (28.31 cmm)

AD-115



- Capacity: 115-lb (52.16 kg)
- Tumbler Volume: 33.10 cu ft (937.29 L)
- Heat Input: 343,000 Btu/hr (86,435 kcal/hr)
- Airflow (60 Hz): 2,100 cfm (59.47 cmm)
Airflow (50 Hz): 1,750 cfm (49.55 cmm)

AD-120



- Capacity: 120-lb (54.43 kg)
- Tumbler Volume: 38.10 cu ft (1,078.87 L)
- Heat Input: 375,000 Btu/hr (94,498 kcal/hr)
- Airflow (60 Hz): 2,150 cfm (60.88 cmm)
Airflow (50 Hz): 1,791 cfm (50.71 cmm)

AD-170

- Capacity: 170-lb (77.11 kg)
- Tumbler Volume: 51.20 cu ft (1,449.82 L)
- Heat Input: 550,000 Btu/hr (138,598 kcal/hr)



- **Airflow (60 Hz) Gas/Electric:** 3,700 cfm (104.77 cmm)
Airflow (50 Hz) Gas/Electric: 3,083 cfm (87.30 cmm)
Airflow (60 Hz) Steam: 4,400 cfm (124.59 cmm)
Airflow (50 Hz) Steam: 3,666 cfm (103.80 cmm)

[Products](#) | [Service](#) | [Financing](#) | [About ADC](#) | [Careers](#) | [Distributor Login](#)

© 2009 American Dryer Corporation