Traffic Safety Equipment



BARRICADE LIGHTS

ITE approved 6V or 12V with or without photo cell. High-impact plastic case with 7" diameter lexan lens and solid state transistor circuit.

ltem #	Description
BL-6V	6 Volt
BL-6VP	6 Volt with Photocell
BL-12V	12 Volt
BL-12VP	12 Volt with Photocell

Barricade Light Bulbs

Item #	Description
BLB-6	6 Volt Bulb
BLB-12	12 Volt Bulb

6 Volt Lantern Battery

Item #	Description
BAT-6V	Takes 2 Batteries for
	Barricade Light



Airport Wands

Hand held, battery powered warning light wands for directing aircraft as well as vehicle traf c. Translucent white wand is 21" long and can be operated in 3 states: ashing red strobe, steady red or steady blue. Holds two C cell batteries and has a belt clip. Translucent red wand is 16¼" long and can be operated as a ashing red strobe or a steady red. Holds two D cell batteries. Both with attached lanyard.

Item #	Description
WAND-W	21 " Translucent White Plastic Wand
WAND-RO	16¼" Translucent Red Plastic Wand

Batteries not included.

STROBE LIGHTS

Compare our quality! All our Strobe Lights feature:

Made in the USA, 2 yr. warranty on power supply. Xenon plug-in ash tube.

Heavy duty strobe light reduces returns and service. All major components are eld serviceable.



Magnum™ "Double" Flash Strobe Light

The high power strobe features a ange mount for easy mounting without disassembly. Powerful proven reliability insures one of the most ef cient Double Flash Strobes available. Flash rate: 80 double ashes per minute. Mounting: Two ¼" dia. holes 6⁷8" apart. Size: 8½"H, 6¾" dia. Weight: 2.75 pounds.

Voltage: 6, 12, 24, 36, 48. Lights are shipped 12V with amber lens.

Item #	Description	
MSL-FM	Flat mount	
MSL-PM	Pipe mount	
MSL-MM	Magnet mount w/Cigar plug	



Penetrator™ "Double Flash" Strobe Light

Low pro le strobe with universal mounting base. Low pro le, rugged die-cast base. Mounting holes 6½" centers. Size: 4"H. Lights shipped 12V with amber lenses.

ltem #	Description
PSL-FM	Flat mount
PSL-PM	Pipe mount
PSL-MM	Magnetic mount w/Cigar plug & hook & loop dash mount

Anodized aluminum housing (Heavy duty strobe has lexan housing).

Solid State circuitry double epoxy dipped.

Reverse polarity, ash tube failure & over voltage protection. Hardware & mounting instructions provided.

S.A.E. & A.A.M.V.A. approved (reduces liability).



Heavy Duty Strobe (Low Profile)

Ideal for forklifts, electric vehicles, contractors trucks and equipment. Flash rate: 60 per minute. Low pro le diameter: 35 g" dia. x 4"H. Lights are shipped 12V with amber lens.

Item #	Description
HDS-FM	Flat mount
HDS-PM	Pipe mount (Base threaded for ½" pipe)
HDS-MM	Magnetic mount w/Cigar plug



Defender™ "Two" Bulb Rotating Light

90 Flashes per minute. S.A.E. approved double light design offers dependable service for municipal, industrial, & automotive applications. Size: 8" diameter, height 8". Voltages: 12-24 VDC. Lens: amber, blue, red, clear. Lights are shipped 12V with amber lens.

ltem #	Description	
DRL-FM	Flat mount	
DRL-PM	Pipe mount	
DRL-MM	Magnetic mount w/Cigar plug	