


Type A



Type B

Deluxe Spring Driven Low Pressure Hose Reels

Keep air hoses off the floor and out of the way. Minimize labor, save storage space, protect against trip hazards and damaged hoses. For use with air and water only. Solid steel construction with heavy-duty brackets to resist hose pull. All reels have a full shaft and swivel to assure maximum product delivery. Maximum temperature is 150° F. Maximum pressure is 300 psi / 21 bar. Includes self retracting hose.

TYPE	MODEL NUMBER	OVERALL SIZE (W x D x H)	INSIDE HOSE DIAMETER	LENGTH OF HOSE	NET WT. (LBS.)
A	VHR-20-44	12½" x 5½" x 13"	1/4"	20 FOOT	19
A	VHR-35-44	12½" x 5½" x 13"	1/4"	35 FOOT	21
A	VHR-17-46	12½" x 5½" x 13"	3/8"	17 FOOT	20
A	VHR-25-46	12½" x 5½" x 13"	3/8"	25 FOOT	22
A	VHR-50-56	16½" x 6" x 17½"	3/8"	50 FOOT	40
A	VHR-35-58	16½" x 6" x 17½"	1/2"	35 FOOT	39
B	VHR-50-78	19" x 7" x 20¼"	1/2"	50 FOOT	57

Standard Spring Driven Low Pressure Hose Reels

Keep air hoses off the floor and out of the way. Minimize labor, save storage space, protect against trip hazards and damaged hoses. Maximum pressure is 300 psi / 20 bar. Includes self retracting hose.

Model SHR-P-38-50 is constructed of durable, high quality impact resistant polypropylene. A positive latching mechanism automatically locks hose at a desired length. A safety lock prevents the hose from moving in either direction. An integral wall/overhead swivel bracket and 36" lead hose are included. Maximum temperature is 140° F.

Models SHR-S-38-25 and SHR-S-38-50 are constructed of heavy-duty steel with corrosion resistant powder coat finish. Four-direction non-sag rollers reduce hose wear abrasion. Multi-position ratchet lock and easy tension adjustment is standard. Spring is fully enclosed and lubricated. Full flow swivel prevents leakage. Guide arm is adjustable for handling up to 9 positions and permits wall, ceiling, and floor mount.



SHR-P-38-50
PLASTIC



SHR-S-38-25
STEEL



SHR-S-38-50
STEEL

MODEL NUMBER	DESCRIPTION	OVERALL SIZE (W x D x H)	INSIDE HOSE DIAMETER	LENGTH OF HOSE	NET WT. (POUNDS)
SHR-P-38-50	PLASTIC	15¾" x 9" x 18½"	3/8"	50 FOOT	23
SHR-S-38-25	STEEL	15¾" x 7" x 17"	3/8"	25 FOOT	30
SHR-S-38-50	STEEL	20½" x 9¼" x 22¼"	3/8"	50 FOOT	50

Air Hose Reels

Help eliminate twists and tangles of hoses, save storage space, protect against trip hazards and damaged hoses with these economical Air Hose Reels.

Arm Style, model REEL-16L, is constructed of all steel. Quick and simple manual hand crank and spring loaded axle helps reel in up to 100 feet of 3/8" hose or 50 feet of 1/2" hose. Valve assembly is rated at 100 psi and 25 cfm. Unit can be mounted both vertically or horizontally. The wall bracket measures 7"W x 3"H. Hose is not included.

Cylinder Style, model REEL-18, has a holding capacity of 100 feet of 3/8" hose. Easy hand crank operation along with a smooth manual rewind. Constructed of durable steel. The wall bracket measures 13¾"W x 3¼"H. Hose is not included.



model
REEL-16L

48 Hours
to Ship



model
REEL-18

MODEL NUMBER	DESCRIPTION	OVERALL SIZE (W x D x H)	USABLE SPACE	NET WT. (POUNDS)
REEL-16L	ARM STYLE	14" x 17¾" x 18"	5"	19
REEL-18	CYLINDER STYLE	19½" x 10¾" x 11½"	9"	21

- Swivel Hook
- Push Button
- Safety Cable Provision
- Rotate Clockwise to Increase Tension
- Adjustable Safety Stop



- Snap Hook

Tool Balancers

Tool Balancers are the economical choice for balancing heavy tools. The molded plastic housing has a smooth exterior with rounded edges for maximum ergonomic convenience. Hand-windable spring tension adjustment knob is flush with the housing. Push-button tension release simplifies decrease in tension. Adjustment screw adds drag to spool for fine tuning of tension. Rugged steel upper swivel hook. Oversized cable opening with direct in-line pull to reduce cable wear. Adjustable cable stop and lower safety snap hook. Spring operation - no electricity needed.

MODEL NUMBER	CABLE LENGTH (FEET)	MINIMUM LOAD (POUNDS)	MAXIMUM LOAD (POUNDS)	NET WT. (POUNDS)
TBR-1	6	1	3	1
TBR-3	6	1½	3	2
TBR-5	6	3	5	2
TBR-10	8	5	10	7