



ROUGH TEXTURE

## Heavy-Duty Fiberglass Walk Ramps

Load and unload equipment from trucks using these Heavy-duty Fiberglass Walk Ramps. Reinforced fiberglass construction provides up to 3,000 pounds capacity. Abrasive surface provides good traction in wet or dry conditions. 1" high curb on each side of ramp. Not for use with fork trucks or pallet trucks.

MODEL NUMBER	OVERALL WIDTH	OVERALL LENGTH	CAPACITY (POUNDS)	MAXIMUM WORKING HEIGHT	NET WT. (POUNDS)
FWR-3010-50	30"	10'	3,000	30"	124
FWR-3012-50	30"	12'	3,000	35"	161
FWR-3610-50	36"	10'	3,000	30"	156
FWR-3612-50	36"	12'	3,000	35"	180
FWR-3614-50	36"	14'	3,000	45"	204



## Fiberglass Autoloader Ramps

The Autoloader Ramp can be separated in half to provide two ramps that may be used to load automobiles and other vehicles. Each half is 18" wide and handles 2,500 pounds. To separate simply remove center hinge pins.

MODEL NUMBER	OVERALL WIDTH	OVERALL LENGTH	CAPACITY (POUNDS)	MAXIMUM WORKING HEIGHT	NET WT. (POUNDS)
FAL-3610-50	36"	10'	5,000	30"	162
FAL-3612-50	36"	12'	5,000	35"	186
FAL-3614-50	36"	14'	5,000	45"	210
FAL-3616-50	36"	16'	5,000	50"	264



## Aluminum Vehicle Twin Ramps

Provide a safe means for driving vans, pick-up trucks and some passenger vehicles from ground level into and out of high building entrances. Ramps can be securely fastened to dock with pin locks. To avoid hang-ups measure under clearance and wheelbase of vehicle. The overall width is 18" with a usable width of 14". Side curbs are 1 1/4" high. Welded aluminum construction.

MODEL NUMBER	LOAD CAPACITY PER PAIR (LBS.)	WORKING HEIGHT (MAX TO MIN)	LENGTH	NET WT. (LBS. EACH)
VTR-7-14-8	7,000	17 1/2" to 12 1/2"	8'	62
VTR-5.5-14-10	5,500	22 1/2" to 16"	10'	77
VTR-7-14-12	7,000	27" to 19"	12'	126
VTR-6-14-14	6,000	32" to 22 1/2"	14'	144
VTR-5.5-14-16	5,500	36 1/2" to 25 1/2"	16'	166
VTR-6-14-18	6,000	41" to 29"	18'	201
VTR-5.5-14-20	5,500	46" to 32 1/2"	20'	228
VTR-5.5-14-24	5,500	55 1/2" to 39"	24'	288

## Wheel Alignment Curbs

Ideal for properly aligning trailers at loading docks. All welded steel construction suitable for indoor or outdoor use. Units must be secured to surface. Heavy-duty welded-steel construction with yellow powder-coat finish. 10" x 10" base plates with pre-drilled holes standard.



MODEL NUMBER	HEIGHT	LENGTH	DIAMETER	NET WT. (POUNDS)
SWAC-92	11"	92"	5"	133
SWAC-144	11"	144"	5"	193
SWAC-ABK	(8) 3/4" x 4" CONCRETE ANCHOR BOLTS			4