

Festoon System

Designed to keep power cords out of danger when using electric trollies and/or hoists. Easily retrofits to any gantry or jib crane up to 240" (20 ft.) in length. 115V AC cord supplied.

MODEL NUMBER	DESCRIPTION	NET WT. (POUNDS)
FES-KIT	KEEP POWER CORDS OUT OF DANGER	15



Work Area Portable Gantry Cranes

Designed to maximize material handling requirements in light-duty lifting applications. Lightweight fixed height design allows for easy mobility. Includes four polyurethane-on-steel swivel casters. Welded steel construction. The straddle width is 68". Powder coat finish. Hoist and trolley can be ordered separately.

MODEL NUMBER	UNDER I-BEAM TO GROUND	I-BEAM (FLANGE x HEIGHT)	BASE WIDTH	CAPACITY (POUNDS)	NET WT. (POUNDS)
FPG-3	90"	2.66" x 4"	48"	300	288
FPG-6	90"	2.66" x 4"	48"	600	300
FPG-10	90"	2.66" x 4"	48"	1,000	329
FPG-20	90"	2.66" x 4"	48"	2,000	340



Mini Overhead Cantilever Jibs

Utilize this unique jib in work cells and work areas. Unique fixed-height design allows for outriggers to be mounted underneath a work bench. Easily lift product from cart to workbench. Straddle width is 48" (ID). Hoist and trolley can be ordered separately. Steel construction.

MODEL NUMBER	UNDER I-BEAM TO GROUND	I-BEAM USABLE LENGTH	I-BEAM (FLANGE x HEIGHT)	CAPACITY (POUNDS)	NET WT. (POUNDS)
CJIB-3	84"	54"	2.66" x 4"	300	204
CJIB-6	84"	54"	2.66" x 4"	600	216
CJIB-10	84"	54"	2.66" x 4"	1,000	299
CJIB-20	84"	54"	2.66" x 4"	2,000	414



Extra Travel Tri-Post Jibs

This unique jib was designed for use in workstations. Place over the top workbench. Extra travel fixed-height I-beam overhangs workbench to allow lifting of products from cart to bench. Straddle width is 40" (ID). Hoist and trolley can be ordered separately. Not compatible with the Eye Manual Trollies. Steel construction.

MODEL NUMBER	UNDER I-BEAM TO GROUND	I-BEAM USABLE LENGTH	I-BEAM (FLANGE x HEIGHT)	CAPACITY (POUNDS)	NET WT. (POUNDS)
TJIB-3	76"	80"	2.66" x 4"	300	248
TJIB-6	76"	80"	2.66" x 4"	600	260
TJIB-10	76"	80"	2.66" x 4"	1,000	343
TJIB-20	76"	80"	2.66" x 4"	2,000	458



Floor Mounted Jibs

This fixed height floor mounted jib adapts well to many applications. Full 360° rotation allows personnel to completely utilize their workstation. Solid steel construction will assist workers in lifting awkward material. The overall I-beam length is 80" with a usable length of 70". Requires reinforced concrete pad for installation. Hoist and trolley can be ordered separately.

MODEL NUMBER	UNDER I-BEAM FLOOR	I-BEAM (FLANGE x HEIGHT)	OVERALL HEIGHT	CAPACITY (POUNDS)	NET WT. (POUNDS)
JIB-FM-3	99-1/2"	2.660" x 4"	103½"	300	405
JIB-FM-6	99-1/2"	3.332" x 6"	105½"	600	443
JIB-FM-10	99-1/2"	3.332" x 6"	105½"	1,000	468
JIB-FM-20	99-1/2"	4.000" x 8"	107½"	2,000	609

