

PORTABLE FIRE EXTINGUISHERS

POTTER-ROEMER



A Division of Smith Industries, Inc.

ABC MULTI-PURPOSE DRY CHEMICAL



FUNCTION: Used to provide protection against class A, B, and C fires.

REGULARLY FURNISHED: Red glossy polyester-coated steel cylinder with pressure gauge, wall mounting bracket and hose or nozzle as indicated. Contents stored under pressure at approximately 195 PSI/13.4 bars.

Model No.	Size (lbs.) kg	UL Listed (Minimum Rating)	FM Approval	Height in. cm	Dia. in cm	Range of Stream ft. m	Type Discharge
3002	2½ 1.1	1A:10B:C	YES	14¾ 37.1	3 7.6	9 - 15 2.7 - 4.5	Nozzle
3005	5 2.3	2A:10B:C	YES	15¾ 39.7	4¼ 10.7	12 - 18 3.6 - 5.4	Hose
3005-3	5 2.3	3A:40B:C	NO	16 40.6	4¼ 10.7	12 - 18 3.6 - 5.4	Hose
3006	6 2.7	3A:40B:C	YES	16 40.6	5 12.7	12 - 18 3.6 - 5.4	Hose
3010	10 4.5	4A:60B:C	YES	20 50.8	5 12.7	15 - 21 4.5 - 6.4	Hose
3020	20 9	20A:120B:C	YES	23¼ 59	7 17.8	15 - 21 4.5 - 6.4	Hose



3000 SERIES

PRESSURIZED WATER



FUNCTION: Used to provide protection against class A fires.

REGULARLY FURNISHED: Stainless steel shell with pressure gauge and wall mounting bracket. Shipped empty, to be charged at destination by authorized personnel.

OPTION: -AF Anti-freeze charge

Model No.	Size (gal.) (L)	UL Listed (Minimum Rating)	FM Approval	Height in. cm	Dia. in. cm	Range of Stream ft. m	Type Discharge
3202	2½ 9.4	2A	YES	24½ 62.6	7 17.8	30 - 45 9.1 - 13.7	Hose



3202

FFFP FOAM



FUNCTION: FFFP is an effective agent in extinguishing class A and B fires. Superior to water in wetting and penetration. Aids in extinguishing deep seated class A fires. An aqueous film forms and floats over the fuel surface in extinguishing class B fires. The agent base is Angus Alcolseal® Film Forming Fluoroprotein.

REGULARLY FURNISHED: Stainless steel shell with pressure gauge, combination cartridge holder and nozzle cartridge and wall mounting bracket. Shipped empty, to be charged at destination by authorized personnel.

Model No.	Size (lbs.) L	UL Listed (Minimum Rating)	Height in. cm	Dia. in. cm	Overall Width in. cm	Range of Stream ft. m	Type Discharge
3252	2½ 9.4	3A:20B	24½ 62.2	7 17.8	9½ 24.1	10 - 15 3 - 4.5	Hose



3252

NOTE: FOR PROPER SELECTION OF CABINET, REFER TO SECTION 1000. All dimensions in English and Metric.



PORTABLE FIRE EXTINGUISHERS



BC DRY-CHEMICAL



FUNCTION: Used to provide protection against class B and C fires.

REGULARLY FURNISHED: Red glossy polyester-coated steel cylinder with pressure gauge, wall mounting bracket and hose or nozzle as indicated. Contents stored under pressure at approximately 195 PSI/13.4 bars.

Model No.	Size (lbs.) kg	UL Listed (Minimum Rating)	FM Approval	Height in. cm	Dia. in. cm	Range of Stream ft. m	Type Discharge
3302	2½ 1.1	10B:C	YES	14½ 37.1	3 7.6	9 - 15 2.7 - 4.5	Nozzle
3305	5 2.3	10B:C	YES	15¼ 38.7	4¼ 10.7	12 - 18 3.6 - 5.4	Nozzle
3305-3	5½ 2.5	40B:C	YES	15¼ 38.7	4¼ 10.7	12 - 18 3.6 - 5.4	Hose
3306	6 2.76	40B:C	YES	15½ 39.3	5 12.7	14 - 20 4.2 - 6.1	Hose
3310	10 4.5	60B:C	YES	20 52	5 12.7	15 - 21 4.5 - 6.4	Hose
3320	20 9	120B:C	YES	24 61	7 17.8	15 - 21 4.5 - 6.4	Hose



3300 SERIES



PURPLE-K – CARTRIDGE OPERATED DRY-CHEMICAL



FUNCTION: Used to provide protection against class B and C fires. Outside cartridge offers ease of recharge where frequent usage is a consideration.

REGULARLY FURNISHED: Red glossy polyester-coated steel cylinder with hose, squeeze grip control nozzle and wall mounting bracket. Carbon dioxide gas contained in outside cartridge at approximately 850 PSI/58.5 bars (70° F/21°C) provides cylinder pressurization and agent discharge upon activation.

Model No.	Size (lbs.) kg	UL Listed (Minimum Rating)	Height in. cm	Dia. in. cm	Overall Width in. cm	Range of Stream ft. m	Type Discharge
3352	9 4	60B:C	18½ 46.9	5¼ 13.3	10¼ 27.3	18 - 22 5.4 - 6.7	Hose
3354	18 8.1	80B:C	21½ 54.6	6¾ 17.1	10¼ 27.3	18 - 22 5.4 - 6.7	Hose
3356	27 12.2	120B:C	26¼ 66.6	6¾ 17.1	10¼ 27.3	18 - 22 5.4 - 6.7	Hose



3350 SERIES



CARBON DIOXIDE



FUNCTION: Used to provide protection against class B and C fires.

REGULARLY FURNISHED: Red glossy polyester-coated aluminum cylinder with discharge horn and wall bracket. Contents pressurized at approximately 735 PSI/50.6 bars (70° F/21° C).

Model No.	Size (lbs.) kg	UL Listed (Minimum Rating)	FM Approval	Height in. cm	Dia. in. cm	Overall Width in. cm	Range of Stream ft. m	Type Discharge
3405	5 2.3	5B:C	YES	17¾ 4.5	5¼ 13.3	8¼ 20.9	3 - 8 0.91 - 2.4	Horn
3410	10 4.5	10B:C	YES	24 61	7 17.8	12 30.4	3 - 8 0.91 - 2.4	Hose & Horn
3415	15 6.8	10B:C	YES	30 76.2	7 17.8	12 30.4	3 - 8 0.91 - 2.4	Hose & Horn
3420	20 9	10B:C	YES	30 76.2	8 20.3	13 33	3 - 8 0.91 - 2.4	Hose & Horn



3400 SERIES