

Options for Electric Hydraulic Scissor Lift Tables

Mechanical Options

- REMOVABLE 42" HIGH HANDRAIL INCLUDING 21" MIDRAIL & NON-REMOVABLE TOE-BOARD
- NON-REMOVABLE 42" HIGH HANDRAILS INCLUDING 21" MIDRAIL AND TOE-BOARD
- 42" HIGH SELF LOCKING GATE UP TO 6 FEET WIDE
- LINK CHAIN CLOSURE GATE WITH SNAP HOOK ENDS FOR MAXIMUM 6 FEET OPENING
- 4-WAY ANTI-SKID STEEL TREADPLATE DECK/PLATFORM
- SEMI-PORTABILITY OPTION (INCLUDES TWO RIGID WHEELS WITH A TWO WHEEL DOLLY JACK)
- FULL-PORTABILITY OPTION FOR 1,000 TO 3,000 LBS. CAPACITY UNITS UP TO 90" LONG. (INCLUDES TWO RIGID & TWO SWIVEL CASTERS) WITH A NON-REMOVABLE PUSH HANDLE, REINFORCED FRAME AND FOOT OPERATED FLOOR LOCK)
- NFPA-701 FIRE RETARDANT ACCORDION SKIRTING - CUSTOMER INSTALLED (INCLUDES HARDWARE)
- NFPA-701 FIRE RETARDANT ACCORDION SKIRTING - FACTORY INSTALLED
(PLEASE NOTE: SKIRTING DOES NOT ALLOW FOR ELECTRIC TOEGUARDS)
- 12" LENGTH SPLIT HINGED BRIDGE WITH RUNOFF GUARDS AND LIFTING CHAINS (72" WIDE)
STEEL
ALUMINUM
- 18" LENGTH SPLIT HINGED BRIDGE WITH RUNOFF GUARDS AND LIFTING CHAINS (72" WIDE)
STEEL
ALUMINUM
- CAROUSEL (CA-SERIES) MOUNTING TO DECK (DOES NOT INCLUDE CAROUSEL)
- POWERED CAROUSEL ELECTRIC HYDRAULIC DRIVEN, FIXED-SPEED, HAND CONTROL, MIN. DECK SIZE 54" x 54",
MAXIMUM CAPACITY 4,000 LBS. (ADD 3-1/2" TO LOWERED HEIGHT (WEIGHT 210 LBS.))
- AIR CASTER BEARINGS, MANUAL ROTATION CAROUSEL (ADD 3" LOWERED HEIGHT)

Control Options *(available for most powered products)*

ADDITIONAL 24V PENDANT HAND CONTROL ON 8 FOOT COIL CORD
2 PUSH-BUTTON CONTROL
4 PUSH-BUTTON CONTROL

24V NEMA 4 WALL MOUNT CONTROL STATION
2 PUSH-BUTTON CONTROL
4 PUSH-BUTTON CONTROL

ADDITIONAL 24V FOOT CONTROL WITH SAFETY GUARD ON 8 FOOT CORD
2 PEDAL CONTROL FOR LIFT-HOLD-LOWER CIRCUITS
4 PEDAL CONTROL FOR LIFT-AND-TILT CIRCUITS

WIRELESS REMOTE CONTROL
2-BUTTON CONTROL FOR LIFT-HOLD-LOWER CIRCUITS
4-BUTTON CONTROL FOR LIFT AND TILT CIRCUITS

Motor/Power Options *(available for most powered products)*

- 3 HP / 1-PHASE / 115/208-230V MOTOR @ 1½ GPM EXTERNAL - UPGRADE FROM 2 HP (35 AMP DRAW AT 115V)
- 6.5 HP / 3-PHASE / 208/230-460V MOTOR @ 4 GPM (INCLUDES 15 GALLON TANK)
- NEMA-4 UPGRADE FOR WASH DOWN APPLICATIONS (INCLUDES SPECIAL MOTOR AND ENCLOSURE)
- ROTARY AIR/OIL POWER UNIT (WARRANTY VOID IF USED W/OUT FILTER - REGULATOR - LUBRICATOR (FRL)) (Call factory for decibel rating)
(AIR REQUIREMENTS 70 CFM @ 70 PSI)
2-BUTTON CONTROL FOR LIFT-HOLD-LOWER CIRCUIT (INCLUDES TOEGUARDS IF STANDARD)
4-BUTTON CONTROL FOR LIFT-AND-TILT CIRCUITS
2 PEDAL CONTROL WITH SAFETY GUARDS
4 PEDAL CONTROL WITH SAFETY GUARDS
1/2" NPT FILTER-REGULATOR-LUBRICATOR (FRL) - VOID WARRANTY IF USED WITHOUT
- RECIPROCATING AIR/OIL POWER UNIT, FOOT TREADLE CONTROL, FOR 1-3K CAPACITY (NO TOEGUARDS)
1/4" NPT FILTER - REGULATOR - LUBRICATOR (FRL) - VOID WARRANTY IF USED WITHOUT (AIR REQUIREMENTS 15 CFM @ 100 PSI)
- HAZARDOUS LOCATION POWER UNIT FOR LIFT-HOLD-LOWER CONTROL (REMOTELY LOCATED)
(NO TOEGUARDS; **DIVISION 2 LOCATIONS ONLY**)

Miscellaneous Options *(available for most powered products)*

- WARNING LIGHT - OPERATES WHEN UP/DOWN BUTTON IS PRESSED
- WARNING BEEPER - OPERATES WHEN UP/DOWN BUTTON IS PRESSED
- HIGH CYCLE BEARING PACKAGE (EHLT SERIES) - AVAILABLE ON TABLES WITH A 36" OR 48" VERTICAL TRAVEL NOT EXCEEDING A CAPACITY OF 4,000 POUNDS (ADDS 3" TO LOWERED HEIGHT)(EHLT only)

CONTACT MANUFACTURER FOR OTHER OPTIONS SUCH AS: 2-SPEED PUMPS, ADDITIONAL LIMIT SWITCHES, APPROACH RAMPS, PAINT OPTIONS, REMOVABLE TOEBOARDS, CONVEYORS, RAILS OR TURNABLES (MANUAL OR POWERED) ATTACHED TO DECK OR SPECIAL DECK SIZES.