

136

Fork Truck Drum Carrier/Rotators

This product allows you to easily transport and rotate 55-gallon steel drums using a fork truck. Drums are held securely in place by a durable chain locking system. Each unit is provided with a 15 foot long chain to allow the drum to be rotated up to 360° from the fork truck operator's seat. Fork pockets measure $7\frac{1}{2}$ " wide by $2\frac{1}{2}$ " high usable. Safety chain is used to secure unit to fork truck. Bung Nut Wrench, model BNW-I, is also included for opening and closing drums.

MODEL NUMBER	CRANK TURNS PER 90° ROTATION	ROTATION Method	CAPACITY (Pounds)	NET WT. (POUNDS)
DCR-205-8®	10	15' CHAIN	800	221
DCR-205-15®	10	15' CHAIN	1,500	259
DCR-205-20	15	15' CHAIN	2,000	280

OPTIONAL 12V DC POWERED OPERATION, suffix DC, (1,200 lbs. maximum capacity) DRUM MUST BE FULL TO ROTATE AT RATED CAPACITY

Manual Drum Carrier/Rotator

Here is an efficient, economical way to handle 55-gallon steel drums. Sturdy handle provides leverage for heavy lifting and easily locks drum in position 5" to 11" off floor. Drum rotates 360°. Rolls smoothly on 8" front wheels and a 4" rear swivel caster. Not for use with drums on pallets.

	MODEL NUMBER	ACCEPTABLE Drum types	ROTATION METHOD	CAPACITY (POUNDS)	NET WT. (POUNDS)
	DCR-110-55	55-GALLON STEEL	MANUAL	800	159
DRUM MUST BE FULL TO BOTATE AT BATED CAPACITY					

DRUM MUST BE FULL TO ROTATE AT RATED CAPACITY

Hoist Mounted Drum Carrier/Rotators

Rotate and position a fully loaded 55-gallon steel drum with ease. Best when used with an overhead hoist. Features a chain crank that allows the operator to rotate 360° drums that are out of reach. Drums are held in place with a drum locking system.

MODEL NUMBER	ACCEPTABLE DRUM TYPES	ROTATION METHOD	CAPACITY (POUNDS)	NET WT. (POUNDS)
DCT-75	55-GALLON STEEL	10' CHAIN	800	97
DCT-85	55-GALLON STEEL	10' CHAIN	1,500	102

DRUM MUST BE FULL TO ROTATE AT RATED CAPACITY

Plastic & Fiber Drum Adapters and Upgrades

Designed to hold and support fiber and plastic drums. Each adapter can be utilized in conjunction with models HDC-305, DCR-205, DCR-110, and DCT.

Model FDA-800 comes complete with both an adjusting arm and a high strength nylon strap. Fits drums measuring 12" to 21" in diameter and 28" to 36" high.

30-gallon Adapter, *model FDC-30*, attaches to the inner rim of the drum saddle so a 30-gallon steel drum can be used.

Dual Ratchet Strap, model FDRS, accommodates 30 and 55-gallon drums.

MODEL NUMBER		
FDA-800®	FIBER DRUM ADAPTER	
FDA-550	ADJUSTING ARM (SOLD SEPARATELY)	24
FDA-250	NYLON STRAP (SOLD SEPARATELY)	12
FDC-30	STEEL SADDLE	36
FDRS	DUAL RATCHET STRAP (FACTORY INSTALLED ONLY)	12

Drum Positioners

Allows fork truck driver to rotate standing drums to the horizontal racking position and vice-versa. Positive latching system ensures safe handling of drums weighing up to 800 lbs. Slide the positioner extensions over the vertical drum. With the aid of the Drum Positioner, rotate drum to horizontal position. Latching system will engage to allow horizontal positioning of drum. It's now ready to slide into the rack. Mechanical operation relies on fork truck to rotate and lift drums. Fork pockets measure $6\frac{1}{2}$ "W x $2\frac{1}{2}$ "H usable on $19\frac{1}{2}$ " centers.

MODEL NUMBER	DESCRIPTION	CAPACITY (POUNDS)	NET WT. (LBS.)
DRUM-P-55	55-GALLON STEEL DRUMS	800	321
DRUM-P-30	30-GALLON STEEL DRUMS	800	315
DRUM-P-55-SB	Spacer for use on drums with drum faucets installed		4
DRUM-P-30-SB	Spacer for use on drums with drum faucets installed		4