


## Foot Pump Scissor Lift Tables

Foot pump activated lift tables. Used by all types of manufacturing and warehousing facilities. Features torsion tubes for side to side stability, pressure flow control valve for controlled lowering, and foot pump. Optional power-lift feature available (on-board charger included on DC option). Scissor tables can be made mobile with the optional handle and caster kit. Rugged welded steel construction. Painted blue finish.

48 Hours  
to Ship



SCTAB-400  
SCTAB-800D (double) (not shown)



SCTAB-500



SCTAB-1000  
(Shown with  
Caster/Handle Kit)

MODEL NUMBER	PLATFORM SIZE (W x L)	CAPACITY (POUNDS)	RAISED HEIGHT	LOWERED HEIGHT	# OF PUMPS AT HIGH/LOW SPEED	NET WT. (POUNDS)
SCTAB-400	17½" x 27½"	400	29"	8¼"	19	164
SCTAB-500	20" x 33"	500	28"	6"	13 / 26	274
SCTAB-750D	20" x 40"	750	35"	7"	8 / 16	284
SCTAB-800D	20" x 35½"	800	51"	13"	12 / 39	274
SCTAB-1000	20" x 40"	1,000	32"	8"	8 / 16	270
SCTAB-2000	42" x 42"	2,000	32"	8"	16 / 32	386

**LINE-X**  
Custom Finish Available

DVD or VIDEO AVAILABLE



SCTAB-750D



SCTAB-750D  
(shown with DC power option and  
caster handle kit)

### FOOT PUMP SCISSOR TABLE OPTIONS

MODEL NUMBER	DESCRIPTION	NET WT. (POUNDS)
SCTAB-DC*	12V DC HAND CONTROL WITH DEEP CYCLE BATTERY	54
SCTAB-AC*	24V AC HAND CONTROL WITH 115V 1 PHASE POWER	36
SCTAB-AIR*	FACTORY AIR OVER OIL WITH FOOT TREADLE CONTROL	18
SCTAB-CHK-1*	CASTER & HANDLE KIT (500, 750D & 1000 only)	18
SCTAB-CHK-2*	CASTER & HANDLE KIT (2000) (FACTORY INSTALLED ONLY) ADD 6½" TO RAISED AND LOWERED HEIGHTS	18
SCTAB-HDS	HIGH DENSITY PVC SURFACE	4
SCTAB-BC*	BENCH TOP STYLE BATTERY CHARGER	8
SCTAB-BCI*	BATTERY CHARGE INDICATOR	1


\*NOT AVAILABLE ON THE SCTAB-400 AND SCTAB-800D



DVD or VIDEO AVAILABLE

## Ground Lift Scissor Tables

Designed for use when fork trucks are not available. Pallets can be loaded onto platform with pallet trucks and raised to an ergonomic working height. Safety features include; entry-side electric toe guard to protect pinch points during lowering of the table, velocity fuse to maintain platform height regardless of hydraulic pressure, foot control, maintenance prop, and upper travel limit switch to stop table at maximum height reducing motor wear. 2HP, 208-230/460V, 3-phase, 60 Hz totally enclosed motor is standard, other voltages available. Remote power unit can be located up to eight feet away from table. 3000 psi hydraulic components rating. Optional accordion skirting available, contact factory.



ACCORDION SKIRT AVAILABLE,  
CONTACT FACTORY

MODEL NUMBER	PLATFORM SIZE (W x L)	CAPACITY (POUNDS)	RAISED HEIGHT	LOWERED HEIGHT	OVERALL SIZE (W x L x H)	NET WT. (POUNDS)
EHLTG-4450-2-36	44" x 50"	2,000	36"	1/2"	67" x 56" x 8½"	1620
EHLTG-4450-4-36	44" x 50"	4,000	36"	1/2"	67" x 56" x 8½"	1690
EHLTG-5250-2-36	52" x 50"	2,000	36"	1/2"	75" x 56" x 8½"	1690
EHLTG-5250-4-36	52" x 50"	4,000	36"	1/2"	75" x 56" x 8½"	1890
EHLTG-4470-2-48	44" x 70"	2,000	48"	1/2"	67" x 78" x 10"	1995
EHLTG-4470-4-48	44" x 70"	4,000	48"	1/2"	67" x 78" x 10"	2310
EHLTG-5270-2-48	52" x 70"	2,000	48"	1/2"	75" x 78" x 10"	2205
EHLTG-5270-4-48	52" x 70"	4,000	48"	1/2"	75" x 78" x 10"	2520

### OPTIONS

EHLTG-44-SB	STEEL ROLLOVER BRIDGE FOR 44" WIDE DECKS (8" LONG)	27
EHLTG-52-SB	STEEL ROLLOVER BRIDGE FOR 52" WIDE DECKS (8" LONG)	33



MAINTENANCE DOOR



## Hydraulic Motorcycle Lift

Manual foot pump activated stationary lift. Ideal for casual and professional riders to work on their motorcycles. Features a front tire cradle to hold wheels up to 6" wide. The hinged ramp measures 27½" wide by 21½" long.

MODEL NUMBER	OVERALL SIZE (W x L)	BASE FRAME (W x L)	CAPACITY (POUNDS)	SERVICE RANGE	NET WT. (POUNDS)
MOTO-LIFT-1100	35" x 108"	26¾" x 65"	1,100	7" to 32"	517