



Shown with  
Optional Aluminum Bridge




DVD or VIDEO  
AVAILABLE


## Premium Truck Scissor Dock Lifts

Save time and reduce man-hours where there are no docks. Pit or surface mount with the optional approach ramp. Engineered and designed for maximum safety and efficiency. Checkered plate deck is made of heavy gauge steel for years of use. Hydraulic cylinders feature emergency velocity fuse if line breaks. Complete with upper travel limit switch and overload relief valve. Push-button control is 24V AC on a 20 foot long coil cord. Prewired control box includes magnetic starter and overload fuse. High visibility removable handrails with fixed toeboards are standard. Includes beveled toe-guards and electric toe-guards around perimeter of platform. External 6.5 HP 208-230/460V, 3-phase, 60 Hz motor may be located up to 8 feet away from lift (weighs 220 pounds). OSHA and ANSI compliant.

### OPTIONS



A) ALUMINUM BRIDGE • WL-SATB  
B) STEEL BRIDGE • WL-SSTB



REMOVABLE HANDRAILING  
AND TOEBOARDS  
model WL-RHT



STOP SIGNAL SIGN  
model WL-SSS



GALVANIZED FRAME AND DECK  
model SPO-WL-LS-ZRC

MODEL NUMBER	PLATFORM SIZE (W x L)	LOWERED HEIGHT	RAISED HEIGHT	CAPACITY (POUNDS)	OVERALL FRAME SIZE (W x L)	NET WT. (POUNDS)
WL-100-5-48	48" x 96"	8"	68"	5,000	41" x 93"	3125
WL-100-5-68	72" x 96"	8"	68"	5,000	62" x 93"	3485
WL-100-5-78	84" x 96"	8"	68"	5,000	62" x 93"	3706
WL-100-5-88	96" x 96"	8"	68"	5,000	86" x 93"	3952
WL-100-5-610	72" x 120"	8"	68"	5,000	62" x 93"	3823
WL-100-5-710	84" x 120"	8"	68"	5,000	62" x 93"	4027
WL-100-5-810	96" x 120"	8"	68"	5,000	86" x 93"	4107
WL-100-6-68	72" x 96"	10"	70"	6,000	62" x 93"	3648
WL-100-6-78	84" x 96"	10"	70"	6,000	62" x 93"	3788
WL-100-6-88	96" x 96"	10"	70"	6,000	86" x 93"	4167
WL-100-6-610	72" x 120"	10"	70"	6,000	62" x 93"	3939
WL-100-6-710	84" x 120"	10"	70"	6,000	62" x 93"	4038
WL-100-6-810	96" x 120"	10"	70"	6,000	86" x 93"	4301
WL-100-8-68	72" x 96"	10"	70"	8,000	62" x 93"	4396
WL-100-8-78	84" x 96"	10"	70"	8,000	62" x 93"	4592
WL-100-8-88	96" x 96"	10"	70"	8,000	86" x 93"	4698
WL-100-8-610	72" x 120"	10"	70"	8,000	62" x 118"	4807
WL-100-8-710	84" x 120"	10"	70"	8,000	62" x 118"	4913
WL-100-8-810	96" x 120"	10"	70"	8,000	86" x 118"	5157
WL-100-10-68	72" x 96"	14"	72"	10,000	62" x 93"	5804
WL-100-10-78	84" x 96"	14"	72"	10,000	62" x 93"	5991
WL-100-10-88	96" x 96"	14"	72"	10,000	86" x 93"	6177
WL-100-10-610	72" x 120"	14"	72"	10,000	62" x 118"	6037
WL-100-10-710	84" x 120"	14"	72"	10,000	62" x 118"	6224
WL-100-10-810	96" x 120"	14"	72"	10,000	86" x 118"	6410
WL-100-10-612	72" x 144"	14"	72"	10,000	62" x 118"	6504
WL-100-10-712	84" x 144"	14"	72"	10,000	62" x 118"	6690
WL-100-10-812	96" x 144"	14"	72"	10,000	86" x 118"	6876
WL-100-12-68	72" x 96"	14"	72"	12,000	62" x 93"	6387
WL-100-12-78	84" x 96"	14"	72"	12,000	62" x 93"	6573
WL-100-12-88	96" x 96"	14"	72"	12,000	86" x 93"	6731
WL-100-12-610	72" x 120"	14"	72"	12,000	62" x 118"	6620
WL-100-12-710	84" x 120"	14"	72"	12,000	62" x 118"	6807
WL-100-12-810	96" x 120"	14"	72"	12,000	86" x 118"	6993
WL-100-12-612	72" x 144"	14"	72"	12,000	62" x 118"	7098
WL-100-12-712	84" x 144"	14"	72"	12,000	62" x 118"	7225
WL-100-12-812	96" x 144"	14"	72"	12,000	86" x 118"	7436

## Premium Truck Scissor Dock Lift Options

**SPLIT ALUMINUM TRUCK BRIDGE:** Standard steel bridge can be replaced with an aluminum bridge 72" wide x 18" long. Ideal for government applications. Good for 5 & 6K. **Model WL-SATB.**

**SPLIT STEEL BRIDGE:** An additional split steel bridge can be added to opposite side of unit. 72" wide x 18" long. **Model WL-SSTB.**

**REMOVABLE HANDRAILS/TOEBOARDS:** When mounting this lift in a pit, this option allows platform to be flush with the floor for fork truck cross traffic. Deduct 7½" from overall width for usable width. **Model WL-RHT.**

**WARNING BEEPER & STROBE:** Sounds and flashes during lifting and lowering operations. 80 decibels. **Model WL-WB.**

**ADDITIONAL HYDRAULIC LINE:** To order, tag model number with suffix WL-HH-(the amount of line needed in feet).

**Model WL-HH.** (8 foot hose standard)

**APPROACH RAMP FOR 8" LOWERED HEIGHT LIFTS:** 60" wide x 65" long. 7° ramp angle. 308 lbs. **Model WL-AR8.**

**APPROACH RAMP FOR 10" LOWERED HEIGHT:** 60" wide x 82" long. 7° ramp angle. 395 lbs. **Model WL-AR10.**

**APPROACH RAMP FOR 12" LOWERED HEIGHT:** 60" wide x 98" long. 7° ramp angle. 474 lbs. **Model WL-AR12.**

**\*\*APPROACH RAMPS MUST BE ANCHORED TO THE FLOOR\*\***