



DVD or VIDEO AVAILABLE

## Mechanical Docklevelers

- Easy truck loading and unloading with this rugged dockleveler
- Engineered and designed for minimum maintenance
- Features a smooth pull chain operation

All heavy-duty construction features ¼" checkered plate deck (55,000 PSI) steel. 6" structural steel support understructure for long life. Lip is 16" long. Includes telescopic steel toe guards on both sides, flush with platform edge. Service range 12" above and below dock. Includes (2) laminated bumpers. Capacities available up to 50,000 pounds.



RATCHET CONTROL AND ACTUATION SPRINGS



EASY OPERATION

MODEL NUMBER	OVERALL SIZE WITH LIP	OPERATION	CAPACITY (POUNDS)	NET WT. (POUNDS)
RR-65	6'W x 5'4"L	Pull Chain	20,000	1405
RR-66	6'W x 6'4"L	Pull Chain	20,000	1600
RR-68	6'W x 8'4"L	Pull Chain	20,000	1900
RR-610	6'W x 10'4"L	Pull Chain	20,000	2310
RR-76	7'W x 6'4"L	Pull Chain	20,000	1850
RR-78	7'W x 8'4"L	Pull Chain	20,000	2625
RR-710	7'W x 10'4"L	Pull Chain	20,000	2940

CONTACT FACTORY FOR CUSTOM-BUILT APPLICATIONS

LOADING DOCK EQUIPMENT



## Electric Hydraulic Docklevelers

- State-of-the-Art Hydraulic Design
- Simple Operation with the Push of a Button

Electric Hydraulic Dockleveler is ideal for high usage dock areas. Easy to operate unit. Operator pushes and holds the "raise" button which activates the hydraulic pump and raises the deck. When the deck reaches the raised position the lip automatically extends. The operator releases the "raise" button and deck descends to rest on the trailer. Control box includes red emergency stop button standard. When the truck pulls away, the deck descends to full down position, trips the limit switch and returns automatically to the level support cross traffic position. Available in 115/208/230V, 1 phase, or 208/230/460V, 3 phase power options. Includes (2) laminated bumpers and a service range of +/- 12". Capacities available up to 80,000 pounds.

MODEL NUMBER	OVERALL SIZE WITH LIP	OPERATION	CAPACITY (POUNDS)	NET WT. (POUNDS)
EH-66	6'W x 6'4"L	ELECTRIC HYDRAULIC	20,000	1575
EH-68	6'W x 8'4"L	ELECTRIC HYDRAULIC	20,000	1890
EH-610	6'W x 10'4"L	ELECTRIC HYDRAULIC	20,000	2310
EH-76	7'W x 6'4"L	ELECTRIC HYDRAULIC	20,000	1785
EH-78	7'W x 8'4"L	ELECTRIC HYDRAULIC	20,000	2625
EH-710	7'W x 10'4"L	ELECTRIC HYDRAULIC	20,000	2940



DVD or VIDEO AVAILABLE

CONTACT FACTORY FOR CUSTOM-BUILT APPLICATIONS



STATE-OF-THE-ART HYDRAULIC DESIGN

MECHANICAL & ELECTRIC HYDRAULIC DOCKLEVELER OPTIONS		
MODEL NUMBER	DESCRIPTION	NET WT. (POUNDS)
WS-DV	DUAL VINYL WEATHER STRIPPING PRE-INSTALLED	-
ES	EMERGENCY STOP (MECHANICAL ONLY)	54
CAS	CURB ANGLE SET (FOR ANY SIZE DOCKLEVELER)	216
SPO	SHALLOW PIT OPTION (17½" MINIMUM DEPTH)	-
MCTS	MANUAL CROSS TRAFFIC RETURN SYSTEM "EH" SYSTEM ONLY	-
FI	UNDER DECK FOAM INSULATION	-
18" LIP/6	18" LONG LIP FOR 6' WIDE DOCKLEVELER	31
18" LIP/7	18" LONG LIP FOR 7' WIDE DOCKLEVELER	36
30K/6	30,000 POUND CAPACITY FOR 6' LENGTH	118
30K/8	30,000 POUND CAPACITY FOR 8' LENGTH	158
30K/10	30,000 POUND CAPACITY FOR 10' LENGTH	199
FOD/6'	LEG OPTION FOR IN FRONT OF DOCK PLACEMENT (6' LENGTH)	240
FOD/8'	LEG OPTION FOR IN FRONT OF DOCK PLACEMENT (8' LENGTH)	240
FOD/10'	LEG OPTION FOR IN FRONT OF DOCK PLACEMENT (10' LENGTH)	240
SS/65	STEEL SHELL FOR 6' x 5' POUR IN PLACE INSTALLATION	265
SS/66	STEEL SHELL FOR 6' x 6' POUR IN PLACE INSTALLATION	276
SS/68	STEEL SHELL FOR 6' x 8' POUR IN PLACE INSTALLATION	288
SS/610	STEEL SHELL FOR 6' x 10' POUR IN PLACE INSTALLATION	345
SS/76	STEEL SHELL FOR 7' x 6' POUR IN PLACE INSTALLATION	299
SS/78	STEEL SHELL FOR 7' x 8' POUR IN PLACE INSTALLATION	311
CWO	COLD WEATHER OIL - GOOD TO -10°F (ELECTRIC DOCKLEVELER)	-
LIP-EX	LIP EXTEND BUTTON (ELECTRIC DOCKLEVELER)	-
EH-TL*	ELECTRIC INTERLOCK (EH DOCKLEVELER & TRAILER RESTRAINT)	-

\*TRAILER RESTRAINT SOLD SEPARATELY