

## Hand Chain Hoists

These portable, lightweight hoists are durable and easy to operate. Compact design and low headroom allow installation in confined areas. Enclosed double ratchet pawls with self adjusting disc brake standard. Designed with a safety factor 4 times the rated capacity. Individually tested at 150% of the rated capacity. Features grade 80 black chain tempered to ISO 3077, galvanized pull chain, hardened two-stage gears, and forged steel upper and lower hooks with safety latches. Constructed of high quality steel components ideal for industrial applications. Meets ANSI B30.16-2003 requirements.

MODEL NUMBER	CAPACITY (POUNDS)	LIFT (FEET)	HEADROOM (INCHES)	NET WT. (POUNDS)
HCH-1-10	1,000	10	11	22
HCH-1-15	1,000	15	11	26
HCH-1-20	1,000	20	11	30
HCH-2-10	2,000	10	12	26
HCH-2-15	2,000	15	12	34
HCH-2-20	2,000	20	12	42
HCH-4-10	4,000	10	14½	45
HCH-4-15	4,000	15	14½	54
HCH-4-20	4,000	20	14½	63



1 YEAR WARRANTY

HAND CHAIN HOIST series HCH

## Professional Lever Hoists (disc brake)

- 50% wider hardened ratchet gear
- Grade 100 alloy chain for more strength with less weight
- Chain guide system allows for horizontal operation
- High impact resistant gear case and brake cover
- Precision Bearings
- Disc Brake
- Braking capacity is 4 times rated capacity
- Manufactured to ISO-9002 quality standard
- Triple chain guide for consistent up and down FREE WHEELING with one hand

MODEL NUMBER	CAPACITY (POUNDS)	STANDARD LIFT (FEET)	MINIMUM DISTANCE BETWEEN HOOKS	HANDLE LENGTH	NET WT. (POUNDS)
PLH-15-5	1,500	5	11"	11"	15
PLH-15-10	1,500	10	11"	11"	18
PLH-15-20	1,500	20	11"	11"	22
PLH-30-5	3,000	5	15-1/2"	16"	23
PLH-30-10	3,000	10	15-1/2"	16"	27
PLH-30-20	3,000	20	15-1/2"	16"	35
PLH-60-5	6,000	10	22-7/16"	16"	35
PLH-60-10	6,000	15	22-7/16"	16"	42
PLH-60-20	6,000	20	22-7/16"	16"	49

ADDITIONAL 12 POCKET TOOL STORAGE BAG, model BAG-12



Each unit comes standard with a rugged storage bag. Additional bags are available, model BAG-12

5 YEAR WARRANTY

PROFESSIONAL LEVER HOIST series PLH

## Economy Lever Hoists (weston brake)

- Completely enclosed Weston-Type brake
- Deformation indicators on throat opening of both hooks
- Drop forged hooks have durable latches and swivel 360 degrees
- Written test certificate for 150% of rated capacity with individual serial numbers.
- Free wheeling chain in neutral position to quickly take up chain slack
- Alloy steel chain grade 80

MODEL NUMBER	CAPACITY (POUNDS)	STANDARD LIFT (FEET)	MINIMUM DISTANCE BETWEEN HOOKS	HANDLE LENGTH	NET WT. (POUNDS)
ELH-05-5	500	5	9.45"	6"	5
ELH-15-5	1,500	5	12.8"	11"	18
ELH-15-10	1,500	10	12.8"	11"	21
ELH-15-20	1,500	20	12.8"	11"	25
ELH-30-5	3,000	5	15.0"	16"	30
ELH-30-10	3,000	10	15.0"	16"	35
ELH-30-20	3,000	20	15.0"	16"	45
ELH-60-5	6,000	5	19.0"	16"	52
ELH-60-10	6,000	10	19.0"	16"	59
ELH-60-20	6,000	20	19.0"	16"	72

ADDITIONAL 12 POCKET TOOL STORAGE BAG, model BAG-12



MIGHTY-MINI LEVER HOIST model ELH-05-5

1 YEAR WARRANTY



ECONOMY LEVER HOIST series ELH

Each unit comes standard with a rugged storage bag. Additional bags are available, model BAG-12