



Wall Jibs (for low ceilings)

Designed to assist workers in the maneuvering of materials as well as achieving maximum headroom where low ceilings are of concern. This cantilever style jib crane mounts to true vertical wall members. Increases personnel productivity by lifting awkward materials. The overall I-beam length is 92" with a usable length of 80". Hoist and trolley can be ordered separately.

MODEL NUMBER	UNDER I-BEAM TO BOTTOM FRAME	I-BEAM (FLANGE x HEIGHT)	OVERALL HEIGHT	CAPACITY (POUNDS)	NET WT. (POUNDS)
JIB-LC-3	48"	2.660" x 4"	57"	300	164
JIB-LC-6	48"	3.332" x 6"	57"	600	215
JIB-LC-10	48"	3.332" x 6"	57"	1,000	265
JIB-LC-20	48"	4.000" x 8"	57"	2,000	378



Tie Rod Jibs (for high ceilings)

Achieve maximum floor space and utilize wasted air space. Mount to walls or columns to increase hook coverage over workstations. Unit rotates 180°. All steel construction provides years of service. Hoist and trolley can be ordered separately.

MODEL NUMBER	OVERALL LENGTH	CABLE SUPPORT LENGTH	OVERALL HEIGHT	I-BEAM (FLANGE x HEIGHT)	CAPACITY (POUNDS)	NET WT. (POUNDS)
JIB-HC-3	89"	85"	43"	2.66" x 4"	300	144
JIB-HC-6	89"	85"	43"	2.66" x 4"	600	180
JIB-HC-10	89"	85"	43"	2.66" x 4"	1,000	204
JIB-HC-20	89"	85"	43"	2.66" x 4"	2,000	216




Quick Install Manual Trolleys

These trolleys are dependable, easy, and safe to use. Designed to easily adjust to the width of virtually any S, H, W, and M type I-beam. Width is adjusted with manual screw mechanism. Includes locking ring to prevent trolley width from changing accidentally. Manual screw mechanism may also be tightened to prevent trolley from moving (similar to a Beam Clamp). Each trolley includes four rollers with sealed bearings for long life. A lifting eye is located at the bottom of the trolley for attaching a hoist (sold separately). Steel construction and painted finish.

MODEL NUMBER	FITS BEAM FLANGE WIDTH	HEADROOM	CAPACITY (POUNDS)	NET WT. (LBS)
QIT-1	2½" - 4"	5.000"	1,000	15
QIT-2	2½" - 4"	6.250"	2,000	20
QIT-4	2½" - 7"	7.125"	4,000	25
QIT-6	3" - 7½"	7.687"	6,000	45
QIT-8	3¼" - 11½"	8.875"	8,000	70



PLAIN EYE MANUAL TROLLEY model E-MT-1



GEARED EYE MANUAL TROLLEY model E-MT-1-C

Eye Manual Trolleys

These trolleys have been designed to quickly install on virtually any S type I-beam. The width of the trolley is adjusted by rotating the center rod with lifting eye clockwise or counterclockwise. Once hoist (sold separately) is attached, center rod cannot be rotated which prevents trolley width from accidentally changing. Choose either plain trolley or geared trolley. Geared trolley is ideal for use when precise positioning of the trolley is required. The trolley includes four rollers with sealed bearings for long life. A lifting eye is located at the bottom of the trolley for attaching a hoist (sold separately). Steel construction and painted finish.

MODEL NUMBER	DESCRIPTION	I-BEAM FLANGE	CAPACITY (POUNDS)	NET WT. (LBS)
E-MT-1	PLAIN	2" - 7"	1,000	20
E-MT-2	PLAIN	2" - 7"	2,000	25
E-MT-4	PLAIN	2½" - 7"	4,000	35
E-MT-6	PLAIN	3" - 9"	6,000	60
E-MT-8	PLAIN	3" - 9"	8,000	105
E-MT-1-C	GEARED	1¾" - 8¾"	1,000	25
E-MT-2-C	GEARED	2½" - 8¾"	2,000	30
E-MT-4-C	GEARED	2½" - 7"	4,000	45
E-MT-6-C	GEARED	3" - 7"	6,000	70
E-MT-8-C	GEARED	3" - 7"	8,000	100