



Contact Factory for Special Design Requirements

48 Hours to Ship



Electric Hydraulic Scissor Lift Tables

Full featured electric hydraulic scissor lift tables are used by all types of manufacturing and warehouse facilities. Safety features include: electric toe guard to protect pinch points during lowering of the table, brass velocity fuse to maintain platform height regardless of hydraulic pressure, 24V AC push-button hand control, maintenance prop, and upper travel limit switch to stop table at maximum height, reducing motor wear. 2HP, 460V, 3 phase, 60 Hz totally enclosed motor standard, other voltages available. 3000 psi hydraulic component rating.

QUICKSHIP (460V 3 PHASE ONLY)						
MODEL NUMBER	PLATFORM SIZE (W x L)	LOWERED HEIGHT	RAISED HEIGHT	CAPACITY (POUNDS)	VOLTAGE PHASE	NET WT. (POUNDS)
EHLT-2448-3-43	24" x 48"	7"	43"	3,000	460/3	700
EHLT-3060-3-43	30" x 60"	7"	43"	3,000	460/3	725
EHLT-4048-3-43	40" x 48"	7"	43"	3,000	460/3	800
EHLT-4848-3-43	48" x 48"	7"	43"	3,000	460/3	825
EHLT-4872-3-43	48" x 72"	7"	43"	3,000	460/3	975
EHLT-2448-4-43	24" x 48"	7"	43"	4,000	460/3	775
EHLT-3060-4-43	30" x 60"	7"	43"	4,000	460/3	800
EHLT-4048-4-43	40" x 48"	7"	43"	4,000	460/3	850
EHLT-4848-4-43	48" x 48"	7"	43"	4,000	460/3	910
EHLT-4872-4-43	48" x 72"	7"	43"	4,000	460/3	1005

OTHER MOTOR VOLTAGE & PHASE ONE ADDITIONAL WEEK TO LEAD TIME, model EHLT-VCC

Model Number Format


EHLT - (width)(length) - capacity - raised height

STANDARD FEATURES

- Patented Pinch Point Perimeter Guards for OSHA Compliance
- Fused 24 Volt Push Button Control on 8 ft. Cord
- Adjustable Upper Travel 24V Limit Switch
- Internal Brass Velocity Fuse
- (2HP) 56 Frame Electric Motor
- Pressure Plated Pump & Manifold System
- Robust Heavy Capacity Tables
- Displacement Style Hydraulic Cylinder
- State-of-the-Art Lifetime Lubricated Bearings
- Integral Maintenance Prop



LINE-X® spray on Polyurea/Polyurethane coating available on most Scissor Tables. Contact factory for additional information.



- Optional Foot Control model EHLT-FC

VERTICAL TRAVEL	PLATFORM WIDTH	PLATFORM LENGTH	CAPACITY (POUNDS)	RAISED HEIGHT	LOWERED HEIGHT	TRAVEL (^) TIME (SEC)	NET WT. (POUNDS)
36"	24" - 48"	48" - 72"	1,000	43"	7"	7	945
36"	24" - 48"	48" - 72"	2,000	43"	7"	11	966
36"	24" - 48"	48" - 72"	3,000	43"	7"	16	987
36"	24" - 48"	48" - 72"	4,000	43"	7"	22	1008
36"	36" - 48"	48" - 72"	5,000	44"	8"	32	1029
36"	36" - 48"	48" - 72"	6,000	44"	8"	32	1050
36"	36" - 48"	48" - 72"	*8,000	44"	8"	15	1281
33"	40" - 60"	48" - 72"	*10,000	43"	10"	15	1438
33"	40" - 60"	48" - 72"	*12,000	43"	10"	15	1596
48"	24" - 48"	64" - 90"	1,000	55"	7"	11	1155
48"	24" - 48"	64" - 90"	2,000	55"	7"	16	1176
48"	24" - 48"	64" - 90"	3,000	55"	7"	22	1197
48"	36" - 48"	64" - 96"	4,000	56"	8"	32	1218
48"	36" - 48"	64" - 96"	5,000	56"	8"	32	1239
48"	36" - 48"	64" - 96"	6,000	56"	8"	48	1260
48"	36" - 48"	64" - 96"	*8,000	56"	8"	15	1501
45"	40" - 60"	64" - 96"	*10,000	55"	10"	15	1659
45"	40" - 60"	64" - 96"	*12,000	55"	10"	20	1816
60"	24" - 48"	84" - 108"	1,000	67"	7"	16	1785
60"	24" - 48"	84" - 108"	2,000	67"	7"	14	1806
60"	24" - 48"	84" - 108"	3,000	67"	7"	16	1827
60"	48" - 72"	96" - 120"	*4,000	68"	8"	26	1848
60"	48" - 72"	96" - 120"	*5,000	68"	8"	26	1869
60"	48" - 72"	96" - 120"	*6,000	70"	10"	30	1890
60"	62" - 72"	96" - 120"	*8,000	70"	10"	30	2131
60"	62" - 72"	96" - 120"	*10,000	72"	12"	30	2289
60"	62" - 72"	96" - 120"	*12,000	72"	12"	30	2446
72"	24" - 48"	102" - 120"	1,000	79"	7"	12	2047
72"	24" - 48"	102" - 120"	2,000	79"	7"	16	2068
71½"	48" - 72"	120" - 144"	*3,000	82"	10½"	16	2089
71½"	48" - 72"	120" - 144"	*4,000	82"	10½"	26	2110
71½"	48" - 72"	120" - 144"	*5,000	82"	10½"	26	2131
71½"	48" - 72"	120" - 144"	*6,000	82"	12"	30	2152
71½"	62" - 72"	120" - 144"	*8,000	82"	12"	30	2415

(^*) TRAVEL TIME BASED ON 460V THREE-PHASE MOTOR
 *DENOTES 6.5 HP 208-230/460V 3 PHASE (EXTERNALLY MOUNTED)