


**POWDER COATED TOUGH**



**CASTERS ARE NOT ATTACHED FOR SHIPPING PURPOSES**

## Ergo-Handle Carts

The Ergo-Handle Cart is constructed of heavy-duty steel to handle loads up to 4,000 pounds. The patented ergonomic handle decreases fatigue by allowing the operator to easily maneuver the cart. Rolls on 2 rigid, 2 swivel 8" x 2" casters with roller bearings. Invertible bolt-on chrome ergonomic handle designed for individual height comfort and handling of long loads.

MODEL NUMBER	PLATFORM SIZE (W x L)	SHELF CLEARANCE	TOP SHELF HEIGHT	TOTAL CAPACITY	NET WT. (LBS.)
<b>8" x 2" PHENOLIC CASTERS</b>					
<b>2-SHELF UNITS</b>					
DH-PH4-2436	24" x 36"	22"	36"	4,000 lbs.	225
DH-PH4-2448	24" x 48"	22"	36"	4,000 lbs.	253
DH-PH4-2460	24" x 60"	22"	36"	4,000 lbs.	275
DH-PH4-2472	24" x 72"	22"	36"	4,000 lbs.	280
<b>3-SHELF UNITS</b>					
DH-PH4-2436-3	24" x 36"	9¾"	36"	4,000 lbs.	270
DH-PH4-2448-3	24" x 48"	9¾"	36"	4,000 lbs.	288

MODEL NUMBER	PLATFORM SIZE (W x L)	SHELF CLEARANCE	TOP SHELF HEIGHT	TOTAL CAPACITY	NET WT. (LBS.)
<b>8" x 2" POLYURETHANE CASTERS</b>					
<b>2-SHELF UNITS</b>					
DH-PU2.4-2436	24" x 36"	22"	36"	3,600 lbs.	230
DH-PU2.4-2448	24" x 48"	22"	36"	3,600 lbs.	250
DH-PU2.4-3060	30" x 60"	22"	36"	3,600 lbs.	304

MODEL NUMBER	PLATFORM SIZE (W x L)	SHELF CLEARANCE	TOP SHELF HEIGHT	TOTAL CAPACITY	NET WT. (LBS.)
<b>8" x 2" MOLD-ON-RUBBER CASTERS</b>					
<b>2-SHELF UNITS</b>					
DH-MR2-2436	24" x 36"	22"	36"	2,400 lbs.	199
DH-MR2-2448	24" x 48"	22"	36"	2,400 lbs.	229
DH-MR2-3060	30" x 60"	22"	36"	2,400 lbs.	365



ALUMINUM THREE SHELF series SPA3



**POWDER COATED TOUGH**

STEEL TWO SHELF series SPS2

**CASTERS ARE NOT ATTACHED FOR SHIPPING PURPOSES**

## Stockpicker Trucks

Combine the mobility of a cart with the versatility of a step ladder with our Stockpicker Trucks. Designed to minimize any risk of injuries that can occur when attempting to stock or unstock shelves from a ladder while pushing a cart. Convenient spring loaded step ladder holds the cart securely in place while a person is standing on the ladder. Crutch tip ladder prevents the cart from moving while stocking. Springs then return the ladder to the raised position once personnel exit the step. All shelves have a 2" lip turned up to prevent items from falling off. Standard casters are 4" x 2" mold-on-rubber, two rigid and two swivel with wheel brakes. Steel units are powder coated blue as are the ladders of the aluminum units.

MODEL NUMBER	BOTTOM SHELF SIZE (W x L)	SHELF CLEARANCE	TOP SHELF HEIGHT	CAPACITY PER SHELF	TOTAL CAPACITY	NET WT. (LBS.)
<b>ALUMINUM CONSTRUCTION</b>						
<b>2-SHELF UNITS</b>						
SPA2-2236	22" x 36"	27"	35"	330 lbs.	660 lbs.	98
SPA2-2840	28" x 40"	27"	35"	330 lbs.	660 lbs.	135
SPA2-2848	28" x 48"	27"	35"	330 lbs.	660 lbs.	147
<b>3-SHELF UNITS</b>						
SPA3-2236	22" x 36"	13½"	35"	330 lbs.	1,000 lbs.	125
SPA3-2840	28" x 40"	13½"	35"	330 lbs.	1,000 lbs.	150
SPA3-2848	28" x 48"	13½"	35"	330 lbs.	1,000 lbs.	180
<b>STEEL CONSTRUCTION</b>						
<b>2-SHELF UNITS</b>						
SPS2-2236	22" x 36"	27"	35"	550 lbs.	1,000 lbs.	200
SPS2-2840	28" x 40"	27"	35"	550 lbs.	1,000 lbs.	210
SPS2-2848	28" x 48"	27"	35"	550 lbs.	1,000 lbs.	225
<b>3-SHELF UNITS</b>						
SPS3-2236	22" x 36"	13½"	35"	550 lbs.	1,000 lbs.	260
SPS3-2840	28" x 40"	13½"	35"	550 lbs.	1,000 lbs.	275
SPS3-2848	28" x 48"	13½"	35"	550 lbs.	1,000 lbs.	298