Laminated Dock Bumpers

Laminated style dock bumpers provide durable, economical protection for your loading dock and trailers. Units are constructed of fabric reinforced rubber from recycled truck tires. Pads are laminated between painted structural angles and held together with 3/4" steel tie rods. Installation is quick and easy by bolting or welding units to the dock. Width is bolt hole center to bolt hole center. Bolt holes are 13/16" in diameter. Installation hardware available separately, see below. Recommended installation with laminated pads in vertical position as shown.

| 4.5" PROJECTION LAMINATED DOCK BUMPERS | | | | | | | |
|--|-----------------------|-----------------|-------|---------|--|--|--|
| | MODEL | OVERALL SIZE | SHIPS | NET WT. | | | |
| TYPE | NUMBER | (H x W x P) | VIA | (LBS.) | | | |
| Α | 1012-4.5 _® | 10" x 12" x 4½" | UPS | 29 | | | |
| Α | 1014-4.5⊕ | 10" x 14" x 4½" | UPS | 32 | | | |
| Α | 1018-4.5 _® | 10" x 18" x 4½" | UPS | 36 | | | |
| Α | 1024-4.5 _® | 10" x 24" x 4½" | UPS | 47 | | | |
| Α | 1030-4.5 | 10" x 30" x 4½" | UPS | 60 | | | |
| Α | 1036-4.5 | 10" x 36" x 4½" | UPS | 72 | | | |
| Α | 1096-4.5* | 10" x 96" x 4½" | TRUCK | 216 | | | |
| Α | 1212-4.5 | 12" x 12" x 4½" | UPS | 30 | | | |
| Α | 1214-4.5 | 12" x 14" x 4½" | UPS | 35 | | | |
| Α | 1218-4.5 | 12" x 18" x 4½" | UPS | 42 | | | |
| Α | 1224-4.5 | 12" x 24" x 4½" | UPS | 57 | | | |
| Α | 1230-4.5 | 12" x 30" x 4½" | UPS | 66 | | | |
| Α | 1236-4.5⊛ | 12" x 36" x 4½" | UPS | 85 | | | |
| Α | 1296-4.5* | 12" x 96" x 4½" | TRUCK | 333 | | | |
| Α | 624-4.5 | 6" x 24" x 4½" | UPS | 32 | | | |
| Α | 636-4.5⊚ | 6" x 36" x 4½" | UPS | 45 | | | |
| С | 1014-4.5F | 10" x 14" x 4½" | UPS | 32 | | | |
| С | 1214-4.5F | 12" x 14" x 4½" | UPS | 36 | | | |
| В | V-1120-4.5® | 20" x 11" x 4½" | UPS | 48 | | | |
| В | V-1124-4.5 | 24" x 11" x 4½" | UPS | 57 | | | |
| В | V-1130-4.5* | 30" x 11" x 4½" | TRUCK | 72 | | | |
| В | V-1136-4.5* | 36" x 11" x 4½" | TRUCK | 86 | | | |
| | | 36" x 11" x 4½" | TRUCK | 86 | | | |

*DIMENSIONS REFLECT RUBBER PORTION ONLY

Specialty Molded Dock Bumpers

• Will Not Warp, Rust, Rot or Harden • High Impact Resistance

Manufactured from fiber reinforced prime rubber containing nylon and polyester. These molded bumpers are built to endure years of abusive pounding. All units have pre-drilled countersunk mounting holes for easy installation. Units are drilled to accept 3/4" anchor bolts. Plastic face bumper, model B-1213-4PF, features two piece construction fully assembled and ready for installation.

| TYPE | MODEL Number | DESCRIPTION | NET WT. (LBS.) |
|------|-----------------|--|-------------------|
| Α | B-1224-3® | 24"W x 12"H x 3"P - RECTANGULAR SHAPED BUMPER | 33 |
| Α | B-1224-6® | 24"W x 12"H x 6"P - RECTANGULAR SHAPED BUMPER | 55 |
| В | T-22® | 22"W x 22"H x 3"P - T-SHAPED MOLDED BUMPER | 43 |
| С | B-1213-4® | 12"W x 13"H x 4"P - MOLDED BUMPER | 24 |
| D | B-1213-4PF | 12"W x 13"H x 4"P - PLASTIC FACE MOLDED BUMPER | 24 |
| D | RF | REPLACEMENT FACE (FOR B-1213-4PF ONLY) | 1 |
| Е | L-1818-4® | 18"W x 18"H x 4"P - L-SHAPED MOLDED BUMPER | 36 |
| F | B-516 | 16"W x 5"H x 2"P - RECTANGULAR SHAPED BUMPER | 7 |
| G | B-818® | 18"W x 8"H x 2"P - RECTANGULAR SHAPED BUMPER | 14 |
| | B-516-SF | 5"W x 16"H x 2"P - STEEL FACED MOLDED BUMPER | 24 |
| | B-818-SF | 8"W x 18"H x 2"P - STEEL FACED MOLDED BUMPER | 44 |

Installation Hardware

Installing bumpers is no longer a chore with concrete anchor bolts. Use 4" long anchors with Laminated Bumpers and 6" long anchors for Molded Bumpers. Sold individually.

| MODEL NUMBER | CONCRETE ANCHOR BOLTS Size & Bumper It Accommodates | NET WT. (LBS.) |
|-----------------|--|-------------------|
| AS-344® | LAMINATED BUMPERS, 3/4" x 4" | 1 |
| AS-346⊚ | MOLDED BUMPERS, 3/4" x 6" | 1 |
| AS-584 | EXTRUDED BUMPERS, 5/8" x 4" | 1 |
| BIT-3/4® | MASONRY BIT 3/4" DIAMETER | 1 |







VERTICAL BUMPER TYPE B



ANGLE FLAT BUMPER

| 6" PROJECTION LAMINATED DOCK BUMPERS | | | | | | | |
|--------------------------------------|---------------------|-----------------------------|--------------|-------------------|--|--|--|
| TYPE | MODEL Number | OVERALL SIZE (H x W x P) | SHIPS VIA | NET WT. (LBS.) | | | |
| Α | 1012-6 | 10" x 12" x 6" | UPS | 32 | | | |
| A | 1014-6 | 10" x 14" x 6" | UPS | 35 | | | |
| Α | 1018-6 _® | 10" x 18" x 6" | UPS | 40 | | | |
| Α | 1024-6 | 10" x 24" x 6" | UPS | 62 | | | |
| Α | 1030-6 | 10" x 30" x 6" | UPS | 73 | | | |
| Α | 1036-6 | 10" x 36" x 6" | UPS | 84 | | | |
| Α | 1212-6 | 12" x 12" x 6" | UPS | 36 | | | |
| Α | 1214-6 | 12" x 14" x 6" | UPS | 46 | | | |
| A | 1218-6 | 12" x 18" x 6" | UPS | 55 | | | |
| Α | 1224-6 | 12" x 24" x 6" | UPS | 66 | | | |
| Α | 1230-6 | 12" x 30" x 6" | UPS | 87 | | | |
| Α | 1236-6 | 12" x 36" x 6" | TRUCK | 105 | | | |
| Α | 1296-6* | 12" x 96" x 6" | TRUCK | 280 | | | |
| В | V-1120-6 | 20" x 11" x 6" | TRUCK | 68 | | | |
| В | V-1124-6 | 24" x 11" x 6" | TRUCK | 82 | | | |
| В | V-1130-6* | 30" x 11" x 6" | TRUCK | 105 | | | |
| В | V-1136-6* | 36" x 11" x 6" | TRUCK | 127 | | | |

*DIMENSIONS REFLECT RUBBER PORTION ONLY







TYPE C





TYPE D TYPE E







