



model YR-15-7230

## Steel Yard Ramps

Quickly load and unload trucks, trailers and rail cars from ground level when no freight dock exists. Increase productivity while reducing material handling costs. Great for construction sites. A manual two-speed hand crank for easy one person height adjustment offers a service range of 45" to 62". Available in 30 foot of straight ramp or 36 foot overall length; 30 foot of straight ramp and 6 foot level off. Standard features include: 9" steel wheels, positive traction open steel grating, safety locking chains, 4" high steel safety curbs, rubber bumpers, 15" overlap lip, and welded steel construction. Painted neutral earth-tone brown.



MANUAL HAND CRANK & 9" STEEL WHEELS



SAFETY LOCKING CHAINS WITH 15" OVERLAP LIP

### OPTIONS



27" PNEUMATIC TIRES



HYDRAULIC HAND PUMP model YR-HL



TOW BAR HITCH model YR-TB-H



TOW LOOP model YR-TB



FORK LIFT PICK-UP SLOTS model YR-FS



HANDRAIL (welded) model YR-HDRL



Stationary ramps, series YRDS, include an Edge-Of-Dock Leveler at the truck end. Ramp height is fixed at 50". Leveler offers service range of +/- 5".

### PORTABLE STEEL YARD RAMP

MODEL NUMBER	CAPACITY (POUNDS)	OVERALL** RAMP WIDTH	USABLE RAMP WIDTH	LENGTH (FEET)	NET WT. (POUNDS)
YR-16-7230	16,000	72"	67"	30	3780
YR-16-8430	16,000	84"	78"	30	4095
YR-16-7236	16,000	72"	67"	36	4725
YR-16-8436	16,000	84"	78"	36	5040
YR-20-7330	20,000	73"	67"	30	4515
YR-20-8530	20,000	85"	78"	30	4830
YR-20-7336	20,000	73"	67"	36	5565
YR-20-8536	20,000	85"	78"	36	5985
YR-25-7330	25,000	73"	67"	30	4725
YR-25-8530	25,000	85"	78"	30	5040
YR-25-7336	25,000	73"	67"	36	5880
YR-25-8536	25,000	85"	78"	36	6300
YR-30-7330	30,000	73"	67"	30	4935
YR-30-8530	30,000	85"	78"	30	5250
YR-30-7336	30,000	73"	67"	36	6300
YR-30-8536	30,000	85"	78"	36	6720

\*\*ADD 19" TO OVERALL RAMPING WIDTH FOR MAXIMUM OVERALL WIDTH. INCLUDES LANDING GEAR AND CRANK MECHANISM.

### PORTABLE STEEL YARD RAMP WITH HAND PUMP HYDRAULIC EDGE-O-DOCK

MODEL NUMBER	CAPACITY (POUNDS)	OVERALL WIDTH	USABLE WIDTH	LENGTH (FEET)	NET WT. (POUNDS)
YRD-16-7236-H	16,000	72"	66"	36	5670
YRD-16-8436-H	16,000	84"	78"	36	6090
YRD-20-7336-H	20,000	73"	66"	36	5880
YRD-20-8536-H	20,000	85"	78"	36	6300
YRD-25-7336-H	25,000	73"	66"	36	6090
YRD-25-8536-H	25,000	85"	78"	36	6510
YRD-30-7336-H	30,000	73"	66"	36	6300
YRD-30-8536-H	30,000	85"	78"	36	6720

LEVELER IS 64" WIDE ON 72" & 73" MODELS AND 75" WIDE ON 84" & 85" MODELS

### STATIONARY STEEL YARD RAMP WITH EDGE-O-DOCK

MODEL NUMBER	CAPACITY (POUNDS)	OVERALL WIDTH	USABLE WIDTH	LENGTH (FEET)	NET WT. (POUNDS)
<b>MECHANICAL EDGE-O-DOCK AT TRUCK END</b>					
YRDS-16-7236-M	16,000	72"	66"	36	5905
YRDS-16-8536-M	16,000	85"	78"	36	6325
YRDS-20-8536-M	20,000	85"	78"	36	6535
<b>HAND PUMP HYDRAULIC EDGE-O-DOCK AT TRUCK END</b>					
YRDS-16-7236-H	16,000	72"	66"	36	5890
YRDS-16-8536-H	16,000	85"	78"	36	6310
YRDS-20-8536-H	20,000	85"	78"	36	6520

LEVELER IS 64" WIDE ON 72" & 73" MODELS AND 75" WIDE ON 84" & 85" MODELS

### STEEL YARD RAMP OPTIONS

MODEL NUMBER	DESCRIPTION	NET WT. (POUNDS)
YR-HL	Pneumatic Tire & Hand Pump Hydraulic Lift (5 mph max. tow speed) (NOT AVAILABLE ON YRD MODELS)	230
YR-HL-DC*	Pneumatic Tire & 12V DC Hydraulic Lift (5 mph maximum tow speed) (NOT AVAILABLE ON YRD MODELS)	288
YR-FS	Fork Lift Pickup Slots (7½"W x 2½"H Usable on 24" Centers)	460
YR-TB	Tow Loop	60
YR-TB-H	Tow Bar Hitch	72
YR-HDRL	42" High Handrails with 21" Midrail (welded) (NON-REMOVABLE)	12 per ft.
YRD-MD	Mechanical Dockleveler in Lieu of Hydraulic (ON 16,000, 20,000, AND 25,000 LBS. CAPACITIES)	
YR-DH	Holes in Lip to Lag Ramp to Top of Dock	

\*INCLUDES ON-BOARD CHARGER