



## Multi-Station Transportable Jib Cranes

Designed for use in multiple locations, includes jib crane and one base socket. Extra base sockets may be purchased for use in other locations. Friction brake design allows positive locking and controlled rotation of heavy loads. 360° continuous rotation of heavy loads. Handle most applications up to 1,000 lbs. and up to 120" radius reach. Standard 4" high I-beam on all units with 2.663" flange width. Rugged welded steel construction. Hoist and trolley sold separately.

MODEL NUMBER	SPAN (FEET)	USABLE HEIGHT (FEET)	CAPACITY (POUNDS)	NET WT. (POUNDS)
JIB-P-10-6-6	6	6	1,000	568
JIB-P-10-6-8	6	8	1,000	608
JIB-P-10-6-10	6	10	1,000	648
JIB-P-10-8-6	8	6	1,000	600
JIB-P-10-8-8	8	8	1,000	640
JIB-P-10-8-10	8	10	1,000	680
JIB-P-10-10-6	10	6	1,000	632
JIB-P-10-10-8	10	8	1,000	672
JIB-P-10-10-10	10	10	1,000	712
JIB-P-B	EXTRA BASE SOCKET, 31"H WITH 12" x 12" BASE			145



18"H base requires (41) 60 lbs. bags of Sakrete mix  
36"H base requires (82) 60 lbs. bags of Sakrete mix

**New**

## Portable Jib Cranes with optional cement counterbalance base

Unique design allows for easy transportation of jib crane with a fork truck. Standard base included with jib crane is not filled with concrete (instructions included for proper filling). Base may be ordered pre-filled with concrete for immediate use. Base measures 42" x 42" and includes built-in fork tubes. Fork tubes are 7½"W x 2½"H usable. Fixed length I-beam will pivot 360° for complete access. Upright vertical column bolts to base. Steel construction. Units ship knocked down. Not for use as a fork truck attachment.

MODEL NUMBER	CAPACITY (POUNDS)	I-BEAM LENGTH (FT.)	I-BEAM HEIGHT	I-BEAM FLANGE WIDTH	BASE HEIGHT	NET WT. (LBS.)
JIB-CB-25-8-10	250	8	6"	3.38"	18"	413
JIB-CB-25-10-10	250	10	6"	3.56"	18"	433
JIB-CB-50-8-10	500	8	6"	3.56"	18"	463
JIB-CB-50-10-10	500	10	8"	4.00"	36"	483
JIB-CB-100-8-10	1000	8	8"	4.13"	36"	585
JIB-CB-18-B	Optional concrete-filled counterbalance base with fork pockets				18"	2,815
JIB-CB-36-B					36"	5,630



model VAN-J-DC

**New**



model VAN-J

## Lifter Jibs

Lift items from the ground to van floor height, then rotate into cargo area. Hand crank winch is standard, battery powered winch is optional. Battery powered winch includes 36" long leads - battery not included. Van floor to raised hook height is 38". Double-pivot arm for use in tight spaces. Overall height is 47". Mounting plate measures 8" x 8". Steel construction. Painted finish.

MODEL NUMBER	DESCRIPTION	SWING REACH (MIN x MAX)	MAXIMUM HOOK HEIGHT	CAPACITY (POUNDS)	NET WT. (LBS.)
VAN-J	MANUAL	0" to 42"	36"	400	120
VAN-J-DC*	DC POWERED	0" to 42"	28"	400	160
VAN-BB	BATTERY BOX				5
VAN-BATT	BATTERY				55
BC	BENCH TOP STYLE BATTERY CHARGER				8

\*VAN-J-DC INCLUDES BATTERY-POWERED WINCH

## Winch Operated Truck Jib Crane

Installed in your pick-up truck bed, this winch operated jib crane will help lift loads up to 1,000 pounds. Lift items from ground to truck bed height, then rotate into cargo area. Includes telescopic boom design with manual hydraulic hand pump to pivot boom up and down. Manual cable winch (with ¼" cable diameter) to lift and lower loads. Unit comes with one grab hook, one chain slot lock, and one sling hook with latch. Mounting plate is 10½" by 10½". Base height is 12½". Overall height is 56". The crane swivels on a 360° base. Safety yellow in color. Welded steel construction.



MODEL NUMBER	BOOM	CAPACITY (POUNDS)	REACH	ADJUSTABLE HEIGHT	NET WT. (LBS.)
WTJ-2	EXTENDED	500	49¼"	0 TO 105"	141
	RETRACTED	1,000	32¾"	13" TO 90½"	