



ECO CANISTER SYSTEM

ADHESIVE NF 22-17

COLOR

Clear

SERVICE TEMPERATURE

-20° to 200° F

PERCENT SOLIDS

30-32 %

BONDING TIME

0 to 5 minutes Time will vary due to temperature and humidity conditions. Best results can be achieved when adhesive and substrates are 60° F or higher.

SAFETY

FLAMMABILITY:

Flammable liquefied gas propellant.
Flammable per industry standard flame projection test.

LIMITATIONS

Do not store at temperatures over 120° F. Do not store directly on concrete floor. Avoid exposure to direct sunlight. Keep at 70° F for optimum performance. Not suitable for some plastics. Test compatibility before using.

WARNING

Use with adequate ventilation. Contains Methylene Chloride. Refer to (MSDS) Material Safety Data Sheet. Avoid prolonged or repeated breathing of vapor. Avoid prolonged or repeated contact with skin. Do not take internally. In an emergency call a physician. Keep out of reach of children.

DESCRIPTION

22-17 Eco-Canister System Adhesive NF is a chlorinated solvent-based contact adhesive in a ready to use portable canister for use in sheet metal shops. It is used to bond closed cell foams and duct liner to sheet metal and other substrates. It is easily sprayed with its specially designed gun and hose assembly sold separately.

METHOD OF APPLICATION

Spray – Uses specifically designed gun & hose.

COVERAGE

Approximately 33 S/F Per Pound

APPLICATION

This product is for industrial use only. It should be applied by trained and qualified craftspeople. Be sure surfaces are clean and dry before application.

When bonding closed cell foam, apply 22-17 to the unfinished side of the closed cell foam or sheet and metal surface to be insulated. Adhere the insulation when adhesive is dry to touch.

When bonding duct liner insulation to itself or sheet metal apply 22-17 in a uniform pattern. Hold the spray gun 8 to 10 inches from surface to be insulated. Press the insulation firmly in place.

After connecting the hose and gun assembly, confirm that all connections are tight. Keep the valve on the canister open and the hose pressurized. DO NOT close valve on canister until ready to connect hose to a new canister.

CLEANUP

Non-Flammable solvent

WARRANTY TERMS: The physical and chemical properties of this product are representative of the typical average values derived in accordance with test methods deemed acceptable, and can vary when subjected to normal manufacturing methods. These values are supplied only as a technical service and are subject to change notice. To be sure information is current call Mon-Eco Industries, Inc.

Terms of Warranty: Warrantor, Mon-Eco Industries, Inc. warrants satisfactory results of this product only when recommendations herein established are followed. The recommendations for use are established upon tests and information deemed reliable. We recommend that adequate testing be made by the user to determine if the product is suitable for the intended purpose and use. Warrantor assumes no responsibility beyond replacement or refund of the purchase price of this product, since warrantor has no control over the methods and application of its product, methods and conditions of transportation, handling and storage of the product. WARRANTOR EXPLICITLY DISCLAIMS ALL LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGE. No agent or representative of Mon-Eco Industries, Inc. has the authority to change or extend these conditions.

3/07

Mon-Eco Industries, Inc.

5 JOANNA COURT • EAST BRUNSWICK, NJ 08816
(732) 257-7942 • 800-899-6326 • FAX (732) 257-6525

www.mon-ecoindustries.com

