



Eco-INSULBOARD ADHESIVE

22-02

COLOR

Off White

SERVICE TEMPERATURE LIMIT

-20°F to 200°F

COVERAGE

25 to 100 sq. ft. per gallon

The coverage is dependent on the surfaces being adhered and method of application.

WEIGHT PER GALLON

12 lbs.

Average Nonvolatile

Approximately 80% by weight

BONDING TIME

1 to 20 minutes

DRYING TIME

30 min. to 24 hours depending on conditions and materials.

SAFETY

Non-Flammable – water based.

APPLICATION METHOD

Caulking gun or trowel.

APPLICATION

This product is for industrial use only. It should be applied by trained and qualified craftspeople. Be sure surfaces are clean and dry. Apply the adhesive to either surface. Press the material firmly in place to assure full contact.

VOC= 0.20 lbs/gal. 24 gms/Liter

DESCRIPTION

Eco-Insulboard Adhesive 22-02 is a water based adhesive designed to adhere polystyrene and other insulation boards to themselves or wood, drywall and masonry surfaces. This adhesive applies easily by trowel or hand or power extrusion. Eco-Insulboard Adhesive 22-02 develops adhesion quickly and dries to form a very strong bond.

LIMITATIONS

Keep from freezing. Before using store material to 60 to 70°F for at least 24 hours.

Do not apply when temperature is below 40°F or above 110°F. Some plastic foams may be warped by water based adhesives. The user should evaluate before using.

CLEAN UP

Wet, warm, soapy water. Dry 4-10

ASBESTOS FREE

CAUTION

Although this product is a water system and considered non-hazardous, good handling practices should be observed. Use with adequate ventilation. Avoid prolonged or repeated breathing of vapor and contact with skin. Do not take internally.

Warranty Terms: The physical and chemical properties of this product are representative of the typical average values derived in accordance with test methods deemed acceptable, and can vary when subjected to normal manufacturing methods. These values are supplied only as a technical service and are subject to change without notice. To be sure information is current call Mon-Eco Industries, Inc.

Terms of Warranty: Warrantor, Mon-Eco Industries, Inc. warrants satisfactory results of this product only when recommendations herein established are followed. The recommendations for use are established upon tests and information deemed reliable. We recommend that adequate testing be made by the user to determine if the product is suitable for the intended purpose and use. Warrantor assumes no responsibility beyond replacement or refund of the purchase price of this product, since warrantor has no control over the methods and application of its product, methods and conditions of transportation, handling and storage of the product. WARRANTOR EXPLICITLY DISCLAIMS ALL LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGE. No agent or representative of Mon-Eco Industries, Inc. has the authority to change or extend these conditions.

Mon-Eco Industries, Inc.

5 Joanna Court • 800-899-6326 • East Brunswick, NJ 08816 732 257-7942 Fax: 732-257-6525