



Model shown: RM-115-10 RM

Islatrol® — RM Series 120 VAC Rackmount

This line of AC surge protectors is ideal for protecting the power feeding valuable rack equipment. All models provide ten protected outlets on the back and two protected convenience outlets on the front. This series provides 40,000 Amps of surge protection and up to 60 dB of high-frequency noise filtering. Status LEDs indicate the correct power is coming to the unit, whether the unit is properly grounded and whether the surge components are still intact. Units are available with an optional digital meter, mounted on the front of the unit, that will monitor the voltage, current and power of the protected equipment.

Features

- 40 kA surge protection
- 60 dB max noise filtering
- 15 A & 20 A models available
- Power, ground and surge status indicators
- Digital meter
- Optional twist lock plug
- 1 year warranty

General Technical Specifications

Part Number	Voltage	Amperage	Plug (NEMA)	Receptacles (NEMA)	Digital Meter	Locking Plug
RM-115-10RM	120 V	15 A	5-15P	5-15R	Yes	No
RM-120-10RM	120 V	20 A	5-20P	5-20R	Yes	No
RM-120-10RML	120 V	20 A	L5-20P	5-20R	Yes	Yes

Rackmount AC Power Protection

Rated Voltage	120 V	Output Receptacles	
Rated Current	15 A & 20 A	15 A Models	Front- (2) NEMA 5-15R Back- (10) NEMA 5-15R
Peak Surge Current	20 kA/mode, 40 kA/phase	20 A Models	Front- (2) NEMA 5-20R Back- (10) NEMA 5-20R
Response Time	<5 ns	Thermal Protection	Thermal Protected MOVs
EMI/RFI Filtering	60 dB Max	Over-current Protection	Circuit
LED Indicators	Green-Power On Green-Ground OK Green-Surge Circuit OK	Dimensions	1.75"H x 19"W x 2.0"D (1U)
Digital Meter	Voltage Amps, Watts, VA, Hz, PF, Kwh, and Clock	Warranty	1 Year
Input Power			
15 A Models	SJT 14/3C Power Cord (15 ft) with NEMA 5-15P Plug		
20A Models	SJT 12/3C Power Cord (15 ft) with NEMA 5-20P Plug NEMA L5-20P Plug- Optional		