



ECO-ADHESIVE 22-33

COLOR

Black

SERVICE TEMPERATURE

-30°F to 170°F
(-34.4°C to 77°C)

COVERAGE

20 to 70 sq. ft./gal.

The coverage rate is dependent on the surfaces being covered and the application method.

WEIGHT PER GALLON

8.3 lbs per gallon (Approx).

AVERAGE NON-VOLATILE

Approximately 70% by weight.

BONDING TIME

3 to 25 minutes, porous surfaces.
20 to 30 minutes, non-porous surfaces.

SAFETY

Wet: Non-Flammable

Dry: Combustible

LIMITATIONS

Keep from freezing

Do not apply below 40°F (4°C) or above 100°F (38°C). Some plastic foams may be warped by water based adhesive. The user should evaluate before using.

CAUTION

Use with adequate ventilation. Avoid prolonged or repeated breathing of vapor. Avoid prolonged or repeated contact with skin. Do not take internally. In case of emergency, call a physician. Keep out of reach of children.

DESCRIPTION

Eco-Adhesive 22-33 is a high solids, water based adhesive designed to adhere low density insulation, such as polystyrene and fiberglass to itself, masonry, wood or other surfaces.

22-33 is something used to attach vapor barrier facings to insulation or building structures.

METHOD OF APPLICATION

Roller, brush or trowel.

MATERIAL PREPARATION

Do not thin.

APPLICATION

This product is for industrial use only. It should be applied by trained and qualified craftspeople.

Be sure surfaces are clean and dry. Apply a full, even coat at the specified coverage. Allow the proper open time, subject to materials and conditions, then press the materials firmly in place to assure full contact.

CLEANUP

Wet: Warm, soapy water.

Dry: Mineral Spirits.

ASBESTOS FREE

Warranty Terms: The physical and chemical properties of this product are representative of the typical average values derived in accordance with test methods deemed acceptable, and can vary when subjected to normal manufacturing methods. These values are supplied only as a technical service and are subject to change without notice. To be sure information is current call Mon-Eco Industries, Inc.

Terms of Warranty: Warrantor, Mon-Eco Industries, Inc. warrants satisfactory results of this product only when recommendations herein established are followed. The recommendations for use are established upon tests and information deemed reliable. We recommend that adequate testing be made by the user to determine if the product is suitable for the intended purpose and use. Warrantor assumes no responsibility beyond replacement or refund of the purchase price of this product, since warrantor has no control over the methods and application of its product, methods and conditions of transportation, handling and storage of the product. WARRANTOR EXPLICITLY DISCLAIMS ALL LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGE. No agent or representative of Mon-Eco Industries, Inc. has the authority to change or extend these conditions.

Mon-Eco Industries, Inc.

5 Joanna Court • 800-899-6326 • East Brunswick, NJ 08816 732 257-7942 Fax: 732-257-6525