



# ECO-EVERFLEX SEALANT 44-33

## COLOR

Gray

## SERVICE TEMPERATURE

-40°F to 200°F

## WEIGHT PER GALLON

12.0 lbs.

## AVERAGE NON VOLATILE

85% by weight

## WATER RESISTANCE

Excellent

## DRYING TIME

Non-Hardening (may be used immediately)

## SAFETY

Flammability

Wet: Non-flammable

Dry: Self-extinguishing

## CAUTION

Although this product is a water system and considered non-hazardous, good handling practices should be observed. Use with adequate ventilation. Avoid prolonged or repeated breathing of vapor and contact with skin. Do not take internally.

## ASBESTOS FREE

MAX V.O.C. = 0.37 lbs/gal; 44 gms/Liter

## DESCRIPTION

Eco-Everflex Sealant 44-33 is a specially designed non-hardening fire resistive, water based sealant. Because it is water based it has no offensive solvent odor and is safe to use in occupied areas. This sealant is easily applied by pump or hand extrusion. It does not string or web during or after application. Eco-Everflex Sealant is ideal for sealing Snap-Lock or Pittsburgh Seams on HVAC ductwork. It is suitable for inline application.

Because of its high solids, low shrinkage, and everflex properties, 44-33 is also used as an acoustical sealant.

It presses into voids and gaps between studs and floors and remains flexible to seal these areas against noise penetration during expansion and contraction.

## LIMITATIONS

Keep from freezing. Apply between 40°F and 110°F. Not formulated for outside U.V. exposure.

## APPLICATION METHOD

Pump or hand extrusion

## CLEANUP

Wet: Hot soapy water

Dry: 44-10

**Warranty Terms:** The physical and chemical properties of this product are representative of the typical average values derived in accordance with test methods deemed acceptable, and can vary when subjected to normal manufacturing methods. These values are supplied only as a technical service and are subject to change without notice. To be sure information is current call Mon-Eco Industries, Inc.

**Terms of Warranty:** Warrantor, Mon-Eco Industries, Inc. warrants satisfactory results of this product only when recommendations herein established are followed. The recommendations for use are established upon tests and information deemed reliable. We recommend that adequate testing be made by the user to determine if the product is suitable for the intended purpose and use. Warrantor assumes no responsibility beyond replacement or refund of the purchase price of this product, since warrantor has no control over the methods and application of its product, methods and conditions of transportation, handling and storage of the product. WARRANTOR EXPLICITLY DISCLAIMS ALL LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGE. No agent or representative of Mon-Eco Industries, Inc. has the authority to change or extend these conditions.

**Mon-Eco Industries, Inc.**

5 Joanna Court • 800-899-6326 • East Brunswick, NJ 08816 732 257-7942 Fax: 732-257-6525