



CB3000PV**3 Coax****Ultra-thin VGA Cable****Common features:**


- 3 coaxes + 7 wires
- Safety approval: UL2919, UL CL2
- Nominal O.D.: 0.18in (4.6mm)
- Jacket color: black
- Impedance: 75 ohms
- Shield: Tinned copper wire braid/aluminum Mylar tape
- Coax conductor: 32 AWG 7/32 tinned copper
- Wire conductor: 30 AWG 7/30 tinned copper
- Available Spool length: 500ft (152.4m)

Molded VGA 3ft, 6ft and 12ft cables available
(see page 5.9 in stock cable section)

CB4200MR**5 Coax****High Resolution Multi-Channel Coax Cable****Common features:**

- 5 coaxes
- Safety approval: UL2919
- Nominal O.D.: 0.35in (9mm)
- Jacket color: black
- Impedance: 75 ohms
- Shield: Tinned copper/Aluminum foil/Mylar
- Coax conductor: 28WG 7/36tinned copper
- Available Spool length: 500ft (152.4m)

Molded BNC 3ft, 6ft, 12ft, 25ft, 35ft and 50ft cables available
(see page 5.11 in stock cable section)

CB4400MR**5 Coax****Super High Resolution Multi-Channel Coax Cable****Common features:**

- 5 coaxes
- Safety approval: UL2919
- Nominal O.D.: 0.55in (14mm)
- Jacket color: black
- Impedance: 75 ohms
- Shield: Tinned copper/Aluminum foil/Mylar
- Coax conductor: 24WG 7/32 bare copper
- Available Spool length: 500ft (152.4m)

Custom length BNC/VGA cables built in 24hrs