

OutRunner®, the quick-connect cable system from ALTINEX was designed with the rental and staging industry in mind. This unique cable combination allows users to quickly switch between connector types. Switch from BNC connector to S-Video or 15pin HD connector by simply unplugging the short patch cable from your regular cable run. The standard cable lengths offered are 15, 25, 35, 75, 100 and 150ft. Based on the high quality coax cable CB4200MR (non-plenum) and CB5010PL (plenum), both ends of the cable are terminated with 7pin XLR type connectors to assure that a high quality signal is maintained at all time. Extender cables are also available to make cable longer length. The OutRunner cables should be treated the same way as any coax cables on the cable length limitation.



Non-Plenum



Cable spec:

CB4200MR (see page 5.3 in bulk cable section)

7pin XLR Female to 7pin XLR Female:

- CB701-121: 15ft (4.57m)
- CB701-122: 25ft (7.62m)
- CB701-123: 35ft (10.67m)
- CB701-124: 50ft (15.24m)
- CB701-125: 75ft (22.86m)
- CB701-126: 100ft (30.48m)
- CB701-127: 150ft (45.72m)

Plenum

Cable spec:

CB5010PL (see page 5.4 in bulk cable section)

7pin XLR Female to 7pin XLR Female:

- CB701-221: 15ft (4.57m)
- CB701-222: 25ft (7.62m)
- CB701-223: 35ft (10.67m)
- CB701-224: 50ft (15.24m)
- CB701-225: 75ft (22.86m)
- CB701-226: 100ft (30.48m)
- CB701-227: 150ft (45.72m)