




CB5620PL**S-Video****Plenum-Flex Round S-Video Cable****Common features:**


- 2 coaxes
- Safety approval: UL1685
- Nominal O.D.: 0.24in (6.10mm)
- Jacket color: gray
- Impedance: 75 ohms
- Shield: Tinned copper/Aluminum (In)/polyester tape
- Coax conductor: 26 AWG 7/34 tinned copper
- Available Spool length: 500ft (152.4m) and 1000ft (304.8m)

Custom length S-Video cables built in 24hrs

CB3300MR**Multimedia****Non-Plenum 5 Coax + 2TP Video/Audio Cable****Common features:**

- 5 coaxes + 2 twisted pairs
- Safety approval: UL1685
- Nominal O.D.: 0.39in (9.91mm)
- Jacket color: black
- Impedance: 75 ohms
- Shield: Tinned copper/Aluminum (In)/polyester tape
- Coax conductor: 26 AWG 7/34 tinned copper
- Twisted pairs conductor: 24 AWG 7/32 tinned copper
- Available Spool length: 500ft (152.4m) and 1000ft (304.8m)

Custom breakout cables built in 24hrs

CB4600MR**Multimedia****Non-Plenum 7 Coax + 6TP Multimedia Cable****Common features:**

- 7 coaxes + 6 twisted pairs
- Safety approval: UL2919
- Nominal O.D.: 0.57in (14.5mm)
- Jacket color: black
- Impedance: 75 ohms
- Shield: Tinned copper/Aluminum foil/Mylar
- Coax conductor: 28 AWG 7/36 tinned copper
- Twisted pairs conductor: 24 AWG 7/32 tinned copper
- Available Spool length: 500ft (152.4m)