

Common features:

- Open and convenient access to power, AV and network connections
- All connectors pass through to table underside
- AC power cable is 10ft (3.05m) long
- AV connection cables are 6ft (1.83m) long
- Low profile design
- *Factory-configurable with Snap-in Connectors* (see page 2.36 for more details.)

**DS801-121****Standard configuration includes:**

- 1ea US AC receptacle 95~120V/5A, 10ft (3.05m)
- 1ea VGA Computer Video (15pin HD F/M), 6ft (1.83m)
- 1ea Computer/MP3 Audio (3.5mm F/M), 6ft (1.83m)
- 1ea Network (RJ45 F/M), 6ft (1.83m)
- 1ea Telephone (RJ11 F/M), 6ft (1.83m)

Table cutout dimensions:

- Front width: 4.10in (104.15mm)
- Side width: 4.40in (111.76mm)
- Corner radius: 0.50in (12.70mm)

Additional specification:

- Maximum table thickness: 2.25in (57.15mm)
- Factory configurable

Common features:

- Easily installs under a table or inside a podium
- Convenient access to power, AV and network connectors
- Table cutting is not required
- AC power cable is 10ft (3.05m) long for US and 8ft (2.44m) for international versions
- Low profile design

UT240-310**Standard configuration includes:**

- 2ea US AC receptacle 95~120V/2.5A, 10ft (3.05m)
- 2ea VGA Computer Video (15pin HD F/F) gender changer
- 2ea Computer/MP3 Audio (3.5mm F/F), 8in (203.2mm) cable
- 4ea Network RJ45 (F) snap-in connector

Installation dimensions:

- Front width: 10.40in (264.00mm)
- Side width: 3.10in (79.00mm)
- Height: 1.85in (47.00mm)

Additional specification:

- Metallic silver finish
- Single power cord
- Easy to install configuration

UT240-311**Standard configuration includes:**

- 2ea US AC receptacle 95~120V/2.5A, 10ft (3.05m)
- 4ea Network RJ45 (F) snap-in connectors

Installation dimensions:

- Front width: 7.64in (194.00mm)
- Side width: 3.10in (79.00mm)
- Height: 1.85in (47.00mm)

Additional specification:

- Metallic silver finish
- Single power cord
- Easy to install configuration

UT240-312**Standard configuration includes:**

- 4ea US AC receptacle 95~120V/1.2A, 10ft (3.05m)
- 4ea Network RJ45 (F) snap-in connector
- 1ea 15A circuit breaker

Installation dimensions:

- Front width: 10.40in (264.00mm)
- Side width: 3.10in (79.00mm)
- Height: 1.85in (47.00mm)

Additional specification:

- Metallic silver finish
- Single power cord
- Easy to install configuration

UT240-313**Standard configuration includes:**

- 2ea US AC receptacle 95~120V/2.5A, 10ft (3.05m)
- 4ea Network RJ45 (F) snap-in connector
- 2ea Computer (DVI-I F/F) connector
- 2ea VGA Computer Video (15pin HD F/F) connector
- 2ea Computer/MP3 Audio (3.5mm F/F), 8in (203.2mm) cable

Installation dimensions:

- Front width: 11.6in (295.00mm)
- Side width: 3.10in (79.00mm)
- Height: 1.85in (47.00mm)

Additional specification:

- Metallic silver finish
- Single power cord
- Easy to install configuration

UT240-410**Standard configuration includes:**

- 4ea German AC receptacle 220~240V/1.2A, 8ft (2.44m)
- 4ea Network RJ45 (F) snap-in connector
- 1ea 15A circuit breaker

Installation dimensions:

- Front width: 14.29in (363.00mm)
- Side width: 3.10in (79.00mm)
- Height: 2.45in (62.00mm)

Additional specification:

- Metallic silver finish
- Single power cord
- Easy to install configuration

UT240-411**Standard configuration includes:**

- 2ea German AC receptacle 220~240V/2.5A, 8ft (2.44m)
- 4ea Network RJ45 (F) snap-in connector
- 2ea VGA Computer Video (15pin HD F/F) connector
- 2ea Computer/MP3 Audio (3.5mm F/F), 8in (203.2mm) cable

Installation dimensions:

- Front width: 12.40in (315.00mm)
- Side width: 3.10in (79.00mm)
- Height: 2.45in (62.00mm)

Additional specification:

- Metallic silver finish
- Single power cord
- Easy to install configuration

UT240-450**Standard configuration includes:**

- 4ea U.K. AC receptacle 220~240V/1.2A, 8ft (2.44m)
- 4ea Network RJ45 (F) snap-in connector
- 1ea 15A circuit breaker

Installation dimensions:

- Front width: 14.29in (363.00mm)
- Side width: 3.10in (79.00mm)
- Height: 2.45in (62.00mm)

Additional specification:

- Metallic silver finish
- Single power cord
- Easy to install configuration

UT240-451**Standard configuration includes:**

- 2ea U.K. AC receptacle 220~240V/2.5A, 8ft (2.44m)
- 4ea Network RJ45 (F) snap-in connector
- 2ea VGA Computer Video (15pin HD F/F) connector
- 2ea Computer/MP3 Audio (3.5mm F/F), 8in (203.2mm) cable

Installation dimensions:

- Front width: 12.40in (315.00mm)
- Side width: 3.10in (79.00mm)
- Height: 2.45in (62.00mm)

Additional specification:

- Metallic silver finish
- Single power cord
- Easy to install configuration

UT240-510**Standard configuration includes:**

- 4ea Australian AC receptacle 220~240V/1.2A, 8ft (2.44m)
- 4ea Network RJ45 (F) snap-in connector
- 1ea 15A circuit breaker

Installation dimensions:

- Front width: 14.29in (363.00mm)
- Side width: 3.10in (79.00mm)
- Height: 2.45in (62.00mm)

Additional specification:

- Metallic silver finish
- Single power cord
- Easy to install configuration

UT240-511**Standard configuration includes:**

- 2ea Australian AC receptacle 220~240V/2.5A, 8ft (2.44m)
- 4ea Network RJ45 (F) snap-in connector
- 2ea VGA Computer Video (15pin HD F/F) connector
- 2ea Computer/MP3 Audio (3.5mm F/F), 8in (203.2mm) cable

Installation dimensions:

- Front width: 12.40in (315.00mm)
- Side width: 3.10in (79.00mm)
- Height: 2.45in (62.00mm)

Additional specification:

- Metallic silver finish
- Single power cord
- Easy to install configuration

UT240-550**Standard configuration includes:**

- 4ea Universal AC receptacle 220~240V/1.2A, 8ft (2.44m)
- 4ea Network RJ45 (F) snap-in connector
- 1ea 15A circuit breaker

Installation dimensions:

- Front width: 14.29in (363.00mm)
- Side width: 3.10in (79.00mm)
- Height: 2.45in (62.00mm)

Additional specification:

- Metallic silver finish
- Single power cord
- Easy to install configuration

UT240-551**Standard configuration includes:**

- 2ea Universal AC receptacle 220~240V/2.5A, 8ft (2.44m)
- 4ea Network RJ45 (F) snap-in connector
- 2ea VGA Computer Video (15pin HD F/F) connector
- 2ea Computer/MP3 Audio (3.5mm F/F), 8in (203.2mm) cable

Installation dimensions:

- Front width: 12.40in (315.00mm)
- Side width: 3.10in (79.00mm)
- Height: 2.45in (62.00mm)

Additional specification:

- Metallic silver finish
- Single power cord
- Easy to install configuration

TM1278**Standard configuration includes:**

- 1ea VGA Computer Video (15pin HD F/M), 12in (304.8mm) cable
- 1ea Composite Video (BNC F/F) connector only
- 1ea Left Audio (RCA F/F) connector only
- 1ea Right Audio (RCA F/F) connector only
- 1ea Computer/MP3 Audio (3.5mm F/TB) connector only
- 1ea Network RJ45 (F) snap-in connector only
- 1ea Telephone RJ11 (F) snap-in connector only

TM1278AU**TM1278:** 1ea US AC receptacle 95~120V/5A**TM1278AU:** 1ea Australian AC receptacle 220~240V/5A**Installation dimensions:**

- Front width: 7.84in (199.14mm)
- Side width: 2.94in (74.68mm)
- Height: 1.84in (46.84mm)

Additional specification:


- Table thickness should be greater than ½ inch

DA2000TM**VGA/Video + Audio line driver****Standard features:**

- VGA through UXGA, and other analog computer video signals
- Signal present LED
- Buffered video sync signal
- Both video/audio output on terminal blocks
- 9V power supply included

Model no. for other countries:

- DA2000TM-AU:** Australia
- DA2000TM-EU:** Germany/C.E.
- DA2000TM-JP:** Japan
- DA2000TM-UK:** UK

UT250-101**Under Table 8x4 Matrix Switcher****Standard features:**

- VGA through UXGA
- 8 computer video inputs
- 8 stereo inputs converted to mono audio
- 4 VGA video outputs
- 1 balanced mono audio output
- RS-232 control
- Contact closure control "Show me" buttons with LEDs
- 4TP outputs for both video and audio signals
- 12V power supply included

****Available Summer, 2008****