usc

Eclipse[™] ClimaPlus[™]



Fine textured pane

 Non-directional pattern ensures consistent appearance.

- NRC performance of .70 meets general office acoustical needs for sound absorption.
- Available in Standard Colors offering multiple design options.
- Optional FIRECODE[™] formulation designed to meet life safety codes.
- CLIMAPLUS[™] 30-year Lifetime System Warranty to withstand conditions up to 104 °F (40 °C)/95% relative humidity without visible sag when used with USG's DONN[®] Brand Suspension Systems.
- Panel used in RENDITIONS[™]
 Face-Routed Ceiling Systems. (see IC327).

Applications

- Schools
- Hotels
- Lobbies
- General office and conference areas
- Transportation terminals



- May be ordered with the patented protection of the ÆGIS MICROBE
 SHIELD[™] for resistance to mold and mildew growth. Contact your USG sales representative for details.
- Panels are treated on both face and back surfaces for mold resistance.



Eclipse[¬] ClimaPlus[¬]

Technical Service 800 USG.4Y0U Web Site www.usg.com Samples/Literature 888 874.2450 Samples/Literature Fax 888 874.2348 Customer Service 800 950.3839 Literature Number SC1812

CLIMAPLUS		Panel Size		Item No.	<u></u> ሠ ሀL ር	Classified						
Non-Sag Warranty	Edge	Imperial Metric (mm) ¹	Class	Imperial Metric	NRC	CAC Min.	LR ²	Color ³		Grid Options	Recycled Content⁴	Panel Cost
Eclipse ^r " Panels <i>ClimAPLUS</i> " Panels	(SQ)	2′x2′x3/4″	Class A	76575	.70 =()	35	.84	White		A, B, C	78%	\$\$
		2′x4′x3/4″	Class A	78575	.70 (1)	35	.84	White		A, B	78%	\$\$
	(SLT)	2′x2′x3/4″	Class A	76775	.70 (1)	35	.84	White		D	78%	\$\$
		600x600x19		ME76775								
		2′x2′x3/4″		76779	.60	35	.84	White		D	62%	\$\$
		2′x4′x3/4″	Class A	78775	.70 (1)	35	.84	White		D	78%	\$\$
	(FL)	2′x2′x3/4″	Class A	76975	.70	35	.84	White		E, G, H	78%	\$\$
		600x600x19		ME76975	(Standard				
		2′x2′x3/4″		76979	.60	35	.84	White		F, I	62%	\$\$
		2'x4'x3/4"	Class A	78975	.70 (1)	35	.84	White		E, G, H	78%	\$\$
ECLIPSE CLIMAPLUS Panels featuring ÆGIS MICROBE SHIELD [™]	(SLT)	2'x2'x3/4"	Class A	76777	.70 ()	35	.84	White		D	78%	\$\$
	(FL)	2'x2'x3/4″	Class A	76977	.70 L)	35	.84	White		E, G, H	78%	\$\$
Eclipse <i>ClimaPlus</i> Tile⁵	(BESK)	12″x12″x3/4″	Class A	70073	.60	40	.84	White		J	78%	\$\$\$\$
		IS ^{™6}	I									
Patterns												
	38 38 38 38											
	A Donn [®] DX DXL™	®/ Donn DXW™	C Centriciti	EE [™] D Do	NN DX /DXL	E Centrici	TEE	F Centricitee DXLT	G Fineline [®] 1/8	H Fineline	Fineline D	IXLF DONN DX/I Concealed
Grid Profile Options	Q	Q	Q		γ	P		P	P	Γ	P	Π
							1					
	Featuring the patented protection of the Ægis Microbe Shield ⁷											
	Type III, Form 1 or 2, Pattern El 5.07 ASTM E84 surface burning characteristics R-2.		5.07 kg/r Thermal R-2.6 (Cla	etric weight 17 kg/m² (Class A panels) ermal resistance 2.6 (Class A) 2.0 (Firecode)		Patented technology This product's unique combi- nation of sag resistance and sound performance results from a technology covered by U.S.			glue-up applications. om 6. For more information on		2"x12" Follow good safety practices. Read material safety data on sheets and related literature of products before specification and/or installation. rr. ut Mold, els	
	Flame spread: 25 Smoke developed: 25 Imperial weight 1.04 lb./ft.² (Class A panels		Maximu See Warra Mainten Can be cl	R-2.0 (FIRECODE) Maximum backloading See Warranty for details. Maintenance Can be cleaned easily with a soft brush or vacuum.			a technicity covered by 0.5. Patent No. 5,250,153. Panels, see IC327 in Specialty Ceilings bir 1. Metric available in white only. 7. See USG's Facts A 2. LP values shown as averages. information. Mildew and Ceiling P 4. For details, see the Recycled information.			' in USG binder. s About Mold, g Panels		

Content selector.

Manufactured by USG Interiors, Inc. 125 South Franklin Street Chicago, IL 60606 The following are trademarks of USG Interiors, Inc. or a related company: CuMPLUS, CENTROTER, DONN, DX, DXL, DXW, ECLISE, FINELINE, FIRECODE, REINOTIONS, USG. F.GIS MICROBE SHIELD is a trademark of Dow Chemical Corporation.

SC1812/rev. 6-04 © 2004, USG Interiors, Inc. Printed in U.S.A.