



# Summit<sup>™</sup> ClimaPlus<sup>™</sup>



Fine textured panel

## Features and Benefits

- Fine textured cast product with an extremely durable surface that resists scrapes and scratches commonly caused by accessing the ceiling plenum.
- Nearly three times more impact-resistant than typical fine textured ceiling panels (ASTM D5420 Gardner Impact Test).
- Excellent combination of noise reduction (NRC) and sound attenuation (CAC) makes this panel ideal for spaces with both open-plan areas and enclosed offices.
- Achieves 40 CAC when installed with FINELINE<sup>®</sup> or FINELINE 1/8 Suspension System.
- *CLIMAPLUS*<sup>™</sup> 15-Year System Warranty to withstand conditions up to 104 °F (40 °C)/90% relative humidity without visible sag when used with USG's *DONN*<sup>®</sup> Brand Suspension Systems.

## Applications

- Schools
- Airports
- Convention centers
- Conference and lobby areas
- Hotels
- Corridors
- Healthcare
- Open and closed office plans







# Summit<sup>™</sup> ClimaPlus<sup>™</sup>





Acoustical Ceilings

Technical Service 800.USG.4YOU  
Web Site [www.usg.com](http://www.usg.com)  
Samples/Literature 888.874.2450  
Samples/Literature Fax 888.874.2348  
Customer Service 800.950.3839  
Literature Number SC2432



UL Classified

Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR <sup>1</sup>	Color	Grid Options	Recycled Content <sup>2</sup>	Panel Cost
(SLB) 	2' x2' x3/4"	Class A	990	.70 	38 	.82	White	A	56%	\$\$
(FLB) 	2' x2' x3/4"	Class A	991	.70 	38/40 <sup>3</sup> 	.82	White	B, C, D	56%	\$\$

Grid Profile Options	A DONN <sup>®</sup> DX <sup>®</sup> / DXL <sup>™</sup>	B CENTRICITEE <sup>™</sup>	C FINELINE <sup>®</sup> 1/8	D FINELINE
				

**ASTM E1264 classification**  
Type III, Form 4, Pattern E

**ASTM E84 surface burning characteristics**

Class A  
Flame spread: 25  
Smoke developed: 15

**Weight**  
1.75 lb./ft.<sup>2</sup>

**Thermal resistance**  
R-1.6

**Maximum backloading**  
See Warranty for details.

**Maintenance**  
Can be cleaned easily with a soft brush or vacuum.

**Impact resistance**  
ASTM C367 – tested to 260 lbf. for 1/4" depression by a 2" steel ball.

ASTM D1037 – tested to 60 lbf. for 1/4" depression by Janka ball.  
ASTM D5420 – tested to 3.8 in./lbf. for impact resistance.

**Footnotes**

1. LR values are shown as averages.
2. For details, see the Recycled Content selector.
3. Achieves 40 CAC when installed with FINELINE or FINELINE 1/8 Suspension System.

**SAFETY FIRST!**

Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.



Manufactured by  
USG Interiors, Inc.  
125 South Franklin Street  
Chicago, IL 60606

The following are trademarks of USG Interiors, Inc. or a related company:  
CENTRICITEE, CLIMAPLUS, DONN, DX, DXL, FINELINE, SUMMIT, USG.

SC2432/rev. 6-04  
© 2004, USG Interiors, Inc.  
Printed in U.S.A.