



PREMIER NUBBY Panels with *CLIMAPLUS* Performance/
DONN CENTRICITEE DXT Suspension System

LEED Credits

Recycled Content: 29% – 32%
CLIMAPLUS No-Sag Warranty

MR				EQ		
Waste Reduction	Recycled Content	Regional Materials ¹	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
	●	●			●	●

Features and Benefits

- High-quality nubby cloth facing offers consistent, fine-textured appearance.
- Excellent noise reduction with NRC of .85 or .90 meets the demanding sound control needs of open-plan spaces.
- *CLIMAPLUS*™ 30-year system warranty to withstand conditions up to 104 °F (40 °C)/95% relative humidity without visible sag when used with a *DONN*® brand suspension system.
- Lightweight fiberglass basemat makes installation fast and easy.

Applications

- Conference rooms and executive areas
- Gymnasiums and auditoriums
- Open office plans
- Retail stores

Substrate

- Fiberglass

Fine-textured panel

Call 888.874.2450 for samples



White

30
 Year System Warranty
 - No visible sag
 - Mold/mildew protection

Edge	Panel Size	Class	Item No.	UL Classified		LR ²	Color	Grid Options	Anti-Mold & Mildew	Recycled Content ³	Panel Cost
				NRC	CAC Min.						
PREMIER NUBBY CLIMAPlus Panels	SQ 	Class A	7000G	.85 	—	.87	White	A, B		29%	\$\$\$
		Class A	7002G	.90 	—	.87	White	A, B		32%	\$\$\$
		Class A	7012G	.90 	25	.87	White	A, B		32%	\$\$\$
	Foil-Back	Class A	7003G	.90 	—	.87	White	A, B		32%	\$\$\$
	Foil-Back	Class A	7013G	.90 	25	.87	White	A, B		32%	\$\$\$


Legend

CLIMAPlus Inherent Performance⁴
 Fiberglass substrate is inherently resistant to the growth of mold, mildew and bacteria.

A
DX[®]/DXL[™]

B
DXW[™]

Grid Profile Options



Physical Data/ Footnotes

Product literature
 Data sheet: SC1839

ASTM E1264 classification
 Type XII, Form 2, Pattern E

ASTM E84 surface burning characteristics
 Class A

Flame spread: 25
 Smoke developed: 50

Weight
 .38-.50 lb./sq. ft.

Minimum AC
 170 for item #7003G.
 190 for item #7013G.

Thermal resistance
 R-3.3 (3/4" panels)
 R-4.4 (1" panels)

Maximum backloading
 See Warranty for details.

Maintenance
 Can be cleaned easily with a soft brush or vacuum.

Footnotes

1. Dependent on location; see Sustainability selector.
2. LR values are shown as averages.
3. For details, see Sustainability selector.
4. For details, see *Ceiling Systems Warranties and Limitations* (SC2102) and *CLIMAPlus Ceilings Certification of Performance* (SC2451).