

Olympia Micro™ *ClimaPlus*™



10

Year Availability

4211, 4221, 4231, 4411, 4421, 4742, 4744



OLYMPIA MICRO Panels with *CLIMAPLUS* Superior Performance
DONN FINELINE DXF Suspension System

LEED Credits

Recycled Content: 56%
CLIMAPLUS Superior Performance for Mold/Mildew

MR				EQ		
Waste Reduction ¹	Recycled Content	Regional Materials ²	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
●	●	●	●	●	●	●

Features and Benefits

- Nondirectional pattern reduces installation time and waste.
- Economical, fine-textured panel.
- Excellent light reflectance enhances indirect lighting of a space.
- Available with .60 NRC to assist in addressing HIPAA requirements (excludes items 4750 & 4751).
- *CLIMAPLUS* 30-year lifetime system warranty to withstand conditions up to 104 °F (40 °C)/95% relative humidity without visible sag when used with a *DONN*® brand suspension system.

Applications

- Healthcare
- Classrooms
- Hotels
- Reception and lobby areas
- Restaurants
- Retail stores

Substrate

- Water-felted mineral fiber



Fine-textured panel

Call 888.874.2450 for samples



White

UL Classified																					
Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content ⁴	Panel Cost									
<div style="display: flex; align-items: center;"> <div style="border: 1px solid black; border-radius: 50%; width: 30px; height: 30px; display: flex; align-items: center; justify-content: center; margin-right: 10px;">30</div> <div> <p>Year System Warranty</p> <ul style="list-style-type: none"> - No visible sag - Mold/mildew protection </div> </div>																					
OLYMPIA MICRO CLIMAPlus Panels .50 NRC⁷ 	2'x2'x5/8"	Class A	4211	.50	30	.87	White	A, B, C	Low		52%	\$\$									
	2'x4'x5/8"	Class A	4411	.50	30	.87	White	A, B	Low		52%	\$\$									
		2'x2'x5/8"	Class A	4221	.50	35	.87	White	D	Low		52%	\$\$								
		2'x4'x5/8"	Class A	4421	.50	35	.87	White	D	Low		52%	\$\$								
		2'x2'x5/8"	Class A	4231	.50	35	.87	White	E, F, G	Low		52%	\$\$								
		2'x4'x5/8"	Class A	4431	.50	35	.87	White	E, F, G	Low		52%	\$\$								
OLYMPIA MICRO CLIMAPlus Panels .60 NRC⁷ 	2'x2'x3/4"	Class A	4750	.60	33	.87	White	A, B, C			56%	\$\$									
	2'x4'x3/4"	Class A	4751	.60	33	.87	White	A, B			56%	\$\$									
		2'x2'x3/4"	Class A	4752	.60	35	.87	White	D			56%	\$\$								
		2'x4'x3/4"	Class A	4753	.60	35	.87	White	D			56%	\$\$								
		2'x2'x3/4"	Class A	4754	.60	35	.87	White	E, F, G			56%	\$\$								
		2'x4'x3/4"	Class A	4755	.60	35	.87	White	E, F, G			56%	\$\$								
OLYMPIA MICRO CLIMAPlus Illusion Two/24 Panels The look of 2'x2' panels 	2'x4'x3/4"	Class A	4742	.50	35	.87	White	D	Low		52%	\$\$									
		2'x4'x3/4"	Class A	4744	.50	35	.87	White	E, H	Low		52%	\$\$								
Illusion Two/24																					
Patterns 																					
Legend <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> Low Emissions (VOC Class) Classified as low-emitting per standards established by the Collaborative for High-Performance Schools (CHPS), following California Specification 01350 testing methods. </div> <div style="text-align: center;"> CLIMAPlus Superior Performance⁸ Contains a broad-spectrum antimicrobial treatment on the face and back of the panel that provides guaranteed resistance against the growth of mold and mildew. </div> </div>																					
<table border="1" style="width: 100%; text-align: center;"> <tr> <td>A DX[®]/DXL™</td> <td>B DXW™</td> <td>C CENTRICITEE™ DXT</td> <td>D DX/DXL</td> <td>E CENTRICITEE DXT</td> <td>F FINELINE[®] DXF</td> <td>G FINELINE[®] 1/8 DXFF</td> <td>H CENTRICITEE DXT</td> </tr> </table>														A DX [®] /DXL™	B DXW™	C CENTRICITEE™ DXT	D DX/DXL	E CENTRICITEE DXT	F FINELINE [®] DXF	G FINELINE [®] 1/8 DXFF	H CENTRICITEE DXT
A DX [®] /DXL™	B DXW™	C CENTRICITEE™ DXT	D DX/DXL	E CENTRICITEE DXT	F FINELINE [®] DXF	G FINELINE [®] 1/8 DXFF	H CENTRICITEE DXT														
Grid Profile Options 																					

Physical Data/ Footnotes	Product literature Data sheet: SC2180 ASTM E1264 classification Type III, Form 2, Pattern CE ASTM E84 surface burning characteristics Class A Flame spread: 25 Smoke developed: 50	Weight .78-1.03 lb./sq. ft. Thermal resistance R-1.4 (5/8" panels) R-1.7 (3/4" panels) Maximum backloading See Warranty for details. Maintenance Can be cleaned easily with a soft brush or vacuum.	Footnotes 1. Applies when USG acoustical ceilings recycling program is utilized. 2. Dependent on location; see Sustainability selector. 3. LR values are shown as averages. 4. For details, see Sustainability selector. 5. Panels have 15/16" routing. 6. Panels have 9/16" routing. 7. Mixing .50 and .60 NRC panels	in the same ceiling plane is not recommended 8. Panel face and back surfaces treated with a patented, broad-spectrum antimicrobial standard formulation that inhibits and retards the growth of mold and mildew. For details, see <i>Ceiling Systems Warranties and Limitations (SC2102)</i> and <i>CLIMAPlus Ceilings Certification of Performance (SC2451)</i> .
---------------------------------	--	---	--	---