

Olympia Micro™ *ClimaPlus*™



10

Year Availability

4211, 4221, 4231, 4411, 4421, 4742, 4744



OLYMPIA MICRO Panels with *CLIMAPLUS* Superior Performance/
DONN FINELINE DXF Suspension System

LEED Credits

Recycled Content: 52%
CLIMAPLUS Superior Performance for Mold/Mildew

MR				EQ		
Waste Reduction ¹	Recycled Content	Regional Materials ²	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
●	●	●	●	●	●	●

Features and Benefits

- Nondirectional pattern reduces installation time and waste.
- Economical, fine-textured panel.
- Excellent light reflectance enhances indirect lighting of a space.
- *CLIMAPLUS* 30-year lifetime system warranty to withstand conditions up to 104 °F (40 °C)/95% relative humidity without visible sag when used with a *DONN*® brand suspension system.

Applications

- Classrooms
- Hotels
- Reception and lobby areas
- Restaurants
- Retail stores

Substrate

- Water-felted mineral fiber



Fine-textured panel

Call 888 874.2450 for samples



White

30
 Year System Warranty
 - No visible sag
 - Mold/mildew protection

UL Classified													
Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content ⁴	Panel Cost	
OLYMPIA MICRO CLIMAPLUS Panels	SQ	2'x2'x5/8"	Class A	4211	.50	30	.87	White	A, B, C	Low		52%	\$\$
		2'x4'x5/8"	Class A	4411	.50	30	.87	White	A, B	Low		52%	\$\$
	SLT	2'x2'x5/8"	Class A	4221	.50	35	.87	White	D	Low		52%	\$\$
		2'x4'x5/8"	Class A	4421	.50	35	.87	White	D	Low		52%	\$\$
	FLB	2'x2'x5/8"	Class A	4231	.50	35	.87	White	E, F, G	Low		52%	\$\$
		2'x4'x5/8"	Class A	4431	.50	35	.87	White	E, F, G	Low		52%	\$\$
OLYMPIA MICRO CLIMAPLUS Illusion Two/24 Panels The look of 2'x2' panels	SLT ⁵	2'x4'x3/4"	Class A	4742	.50	35	.87	White	D	Low		52%	\$\$
	ILT ⁶	2'x4'x3/4"	Class A	4744	.50	35	.87	White	E, H	Low		52%	\$\$

Illusion Two/24

Patterns



Legend

Low Emissions (VOC Class)

Classified as low-emitting per standards established by the Collaborative for High-Performance Schools (CHPS), following California Specification 01350 testing methods.

CLIMAPLUS Superior Performance⁷

Contains a broad-spectrum antimicrobial treatment on the face and back of the panel that provides guaranteed resistance against the growth of mold/mildew, fungi, yeast, algae, and Gram-positive and Gram-negative odor/stain-causing bacteria.

A	B	C	D	E	F	G	H
DX [®] /DXL™	DXW™	CENTRICITEE™ DXT	DX/DXL	E CENTRICITEE DXT	F FINELINE [®] DXF	G FINELINE [®] 1/8 DXFF	H CENTRICITEE DXT

Grid Profile Options

**Physical Data/
Footnotes**

Product literature
Data sheet: SC2180

ASTM E1264 classification
Type III, Form 2, Pattern CE

ASTM E84 surface burning characteristics
Class A
Flame spread: 25
Smoke developed: 50

Weight
.78-1.03 lb./sq. ft.

Thermal resistance
R-1.4 (5/8" panels)
R-1.7 (3/4" panels)

Maximum backloading
See Warranty for details.

Maintenance
Can be cleaned easily with a soft brush or vacuum.

Footnotes

1. Applies when USG acoustical ceilings recycling program is utilized.
2. Dependent on location; see Sustainability selector.
3. LR values are shown as averages.
4. For details, see Sustainability selector.
5. Panels have 15/16" routing.
6. Panels have 9/16" routing.
7. Panel face and back surfaces treated with a patented, broad-spectrum antimicrobial standard

formulation that inhibits and retards the growth of mold/mildew, fungi, yeast, and odor/stain-causing Gram-positive and Gram-negative bacteria. For details, see *Ceiling Systems Warranties and Limitations* (SC2102) and *CLIMAPLUS Ceilings Certification of Performance* (SC2451).