



FROST Panels/
DOWN Finline DXF Suspension System

LEED Credits
Recycled Content: 70% – 71%

MR				EQ		
Waste Reduction ¹	Recycled Content	Regional Materials ²	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
●	●	●	●	●	●	●

Features and Benefits

- Fine-textured cast product with durable surface that resists scrapes caused by accessing the ceiling plenum.
- Integral color masks nicks and scratches to enhance lifelong panel appearance.
- Optional FIRECODE™ formulation designed to meet life safety codes.
- Nearly two times more impact resistant than typical fine-textured ceiling panels (ASTM C367 – 2" ball hardness test).

Applications

- Conference and lobby areas
- Executive offices
- Hospitality
- Retail stores
- Transportation terminals

Substrate

- Cast mineral fiber



Fine-textured panel

Call 888.874.2450 for samples



White

UL Classified																											
Edge	Panel Size	Class ³	Item No.	NRC	CAC Min.	LR ⁴	Color	Grid Options	VOC Emissions	Abuse-Resistant	Recycled Content ⁵	Panel Cost															
FROST Panels	SLB 	Class A	440	.70	40	.83	White	A	Zero		71%	\$\$															
	Foil-Back																										
	2'x2'x3/4"		415	.55	35	.83	White	A	Zero		70%	\$\$															
	Foil-Back																										
	2'x4'x3/4"	Class A	450	.70	38	.83	White	A	Zero		71%	\$\$															
	Paper-Back																										
	FL 	Class A	460	.70	38	.83	White	B, C, D	Zero		71%	\$\$															
	Paper-Back																										
FROST Pedestals I Panels Triple-step scoring	PE/IL 	Class A	400	.70	35	.83	White	E	Zero		71%	\$\$\$															
	Paper-Back																										
Legend																											
Zero Emissions (VOC Class) Classified as zero-emitting per standards established by the Collaborative for High-Performance Schools (CHPS), following California Specification 01350 testing methods.																											
<table border="1"> <thead> <tr> <th>A</th> <th>B</th> <th>C</th> <th>D</th> <th>E</th> </tr> </thead> <tbody> <tr> <td>DX®/DXL™</td> <td>CENTRICITEE™ DXT</td> <td>FINELINE® DXF</td> <td>FINELINE® 1/8 DXFF</td> <td>CENTRICITEE DXT</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>													A	B	C	D	E	DX®/DXL™	CENTRICITEE™ DXT	FINELINE® DXF	FINELINE® 1/8 DXFF	CENTRICITEE DXT					
A	B	C	D	E																							
DX®/DXL™	CENTRICITEE™ DXT	FINELINE® DXF	FINELINE® 1/8 DXFF	CENTRICITEE DXT																							
Grid Profile Options																											

**Physical Data/
Footnotes**

Product literature
 Data sheet: SC1817

ASTM E1264 classification
 Type III, Form 4, Pattern E

ASTM E84 surface burning characteristics
 Class A
 Flame spread: 25
 Smoke developed: 50

Weight
 1.65-1.7 lb./sq. ft.

Thermal resistance
 R-1.7 (Class A)
 R-1.1 (FIRECODE)

Maximum backloading
 See Warranty for details.

Maintenance

Can be cleaned easily with a soft brush or vacuum.

Impact resistance

ASTM C367 – tested to min. 190 lbf. for 1/4" depression by a 2" steel ball.

Texture

The manufacturing process for cast ceiling panels creates natural, subtle texture variations, which is a distinguishing feature of these products. Because of potential variances between production dates, we recommend ordering and installing cast products by production lot number.

Footnotes

1. Applies when USG acoustical ceilings recycling program is utilized.
2. Dependent on location; see Sustainability selector.
3. Fire-rated items: see UL design details.
4. LR values are shown as averages.
5. For details, see Sustainability selector.