Halcyon[™] ClimaPlus[™] Planks and Large Sizes





Halcyon Planks with *ClimaPlus* Performance/ Donn Centricitee DXT Suspension System

LEED Credits

Recycled Content: 40% – 41% CLIMAPLUS No-Sag Warranty

MR			EQ .			
Waste Reduction	Recycled Content	Regional Materials ¹	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
	•	•			•	•

Features and Benefits

- Range of planks and panels for large-module ceilings.
- Fine, monolithic texture.
- Light reflectance of .88 is part of an "indirect lighting" solution.
- $\, {\sf Exceptional} \,\, {\sf noise} \,\, {\sf reduction}.$
- CLIMAPLUS 30-year lifetime system warranty to withstand conditions up to 104 °F (40 °C)/95% relative humidity without visible sag when used with a DONN® brand suspension system.
- Lightweight fiberglass basemat makes installation fast and easy.

Applications

- Open-plan offices
- Reception and lobby areas
- Corridors
- Convention halls and concourses
- Spaces with indirect or natural lighting

Substrate

- Fiberglass

Call 888 874.2450 for samples



ine-textured panel

Halcyon™ ClimaPlus™ Planks and Large Sizes

Web Sites: usg.com usgdesignstudio.com sustainableceilings.com seismicceilings.com

Technical Service 800 USG.4Y0U Samples/Literature 888 874.2450 Samples/Literature Fax 888 874.2348 Customer Service 800 950.3839

See usa.com for the most up-to-date product information.

					① UL Classified							
30	Edge	Panel Size ^{2,3}	Class	Item No.	NRC	CAC Min.	LR ⁴	Color	Grid Options	Anti-Mold & Mildew	Recycled Content ⁵	Panel Cost
Year System Warranty No visible sag Mold/mildew protection			0		0		0		•	0	(4)	8
Halcyon ClimaPlus Planks	SQ	2'x6'x3/4"	Class A	97262	.90	20	.88	White	A, B	0	40%	\$\$\$
		2'x8'x3/4"	Class A	97263	.90	20	.88	White	A, B	0	40%	\$\$\$
	SL	2'x6'x1"	Class A	99268	.95	20	.88	White	D	0	41%	\$\$\$
		2′x8′x1″	Class A	99269	.95	20	.88	White	D	0	41%	\$\$\$
	FL	2'x6'x1"	Class A	98348	.95	20	.88	White	E, F, G	0	41%	\$\$\$
		2'x8'x1"	Class A	98197	.95	20	.88	White	E, F, G	0	41%	\$\$\$
Halcyon ClimaPlus Large Sizes	SQ	4′x4′x1″	Class A	98441	.95	20	.88	White	A, B	0	41%	\$\$\$
		4′x8′x1″	Class A	98481	.95	20	.88	White	A, B	0	41%	\$\$\$
	SL	4'x4'x1"	Class A	98443	.95	20	.88	White	D	0	41%	\$\$\$
	FL	4'x4'x1"	Class A	98445	.95	20	.88	White	E, F, G	0	41%	\$\$\$
	Legend											
	CLIMAPLUS Inherent Performance ⁵ Fiberglass substrate is inherently resistant to the growth of mold, mildew and bacteria.											
	A DX®/DXL™	B DXW TM	C Centricitee tm DXT	D DX/DXL	E Centricitee DXT	FINELINE® DXF	G Fineline® 1/8 DXFF					
Grid Profile Options												

Physical Data/ Footnotes

Product literature Data sheet: SC2483

ASTM E1264 classification Type XII, Form 2, Pattern G

ASTM E84 surface burning characteristics Class A

Flame spread: 25 Smoke developed: 50

Weight 0.38 lb./sq. ft. (3/4" panels) 0.47 lb./sq. ft. (1" panels)

Thermal resistance R-3.3 (3/4" panels)

R-4.4 (1" panels) Maximum backloading

See Warranty for details.

Can be cleaned easily with a soft brush or vacuum.

Footnotes

 Dependent on location; see Sustainability selector.
2. Custom-size panels available. Please contact your USG sales representative for details.

3. Stabilizer bars recommended for panels 5' and longer. See USG parts list IC532 for details.

4. LR values are shown as averages. 5. For details, see Sustainability

selector.
6. For details, see *Ceiling Systems* Warranties and Limitations (SC2102) and CLIMAPLUS Ceilings Certification of Performance (SC2451).

