



Olympia Micro *ClimaPlus*[™]

Fine textured panel



Features and Benefits

- Economical, fine-textured panel.
- Excellent light reflectance enhances indirect lighting of a space.
- *CLIMAPLUS*[™] 15-year Lifetime System Warranty to withstand conditions up to 104 °F (40 °C)/90% relative humidity without visible sag when used with a USG DOWN[®] Brand Suspension System.

Applications

- Classrooms
- Hotels
- Reception and lobby areas
- Restaurants
- Retail stores

Olympia Micro Panels with *CLIMAPLUS*[™] Performance/DONN[®] Brand FINELINE[®] Suspension System






Olympia Micro ClimaPlus™

Acoustical Ceilings

Technical Service 800 USG.4YOU
Web Site www.usg.com
Samples/Literature 888 874.2450
Samples/Literature Fax 888 874.2348
Customer Service 800 950.3839
Literature Number SC2180




UL Classified









Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR ¹	Color	Grid Options	Recycled Content ²	Panel Cost
Olympia Micro CLIMAPLUS™ Panels 	2' x2' x5/8"	Class A	4211	.50	30	.85	White	A, B, C	52%	\$\$
	2' x4' x5/8"	Class A	4411	.50	30	.85	White	A, B	52%	\$\$
	2' x2' x5/8"	Class A	4221	.50	35	.85	White	D	52%	\$\$
	2' x4' x5/8"	Class A	4421	.50	35	.85	White	D	52%	\$\$
	2' x2' x5/8"	Class A	4231	.50	35	.85	White	E, F, G	52%	\$\$
	2' x4' x5/8"	Class A	4431	.50	35	.85	White	E, F, G	52%	\$\$
Olympia Micro CLIMAPLUS™ Illusion Two/24 Panels The look of 2' x 2' panels 	2' x4' x3/4"	Class A	4742	.50	35	.85	White	D	52%	\$\$
		2' x4' x3/4"	Class A	4744	.50	35	.85	White	H	52%

Illusion Two/24

Patterns



Grid Profile Options

A	B	C	D	E	F	G	H
DONN® DX®/DXL™	DONN DXW™	CENTRICITEE™	DONN DX/DXL	CENTRICITEE	FINELINE®	FINELINE 1/8	CENTRICITEE
							

ASTM E1264 classification

Type III, Form 2, Pattern CE

ASTM E84 surface burning characteristics

Class A

Flame spread: 25

Smoke developed: 10

Weight

0.92 lb./ft.²

Thermal resistance

R-1.4 (5/8" panels)

R-1.7 (3/4" panels)

Maximum backloading

See Warranty for details.

Maintenance

Can be cleaned easily with a soft brush or vacuum.

Footnotes

1. LR values are shown as averages.
2. For details, see the Recycled Content selector.
3. Panels have 15/16" routing.
4. Panels have 9/16" routing.

SAFETY FIRST!

Follow good safety and industrial hygiene practices during handling and installation of all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read material safety data sheets and related literature on products before specification and/or installation.



Manufactured by
USG Interiors, Inc.
125 South Franklin Street
Chicago, IL 60606

The following are trademarks of USG Interiors, Inc. or a related company: CENTRICITEE, CLIMAPLUS, DONN, DX, DXL, DXW, FINELINE, USG.

SC2180/rev. 2-05
© 2005, USG Interiors, Inc.
Printed in U.S.A.