



MILLENNIA Panels with *CLIMAPLUS* Superior Performance/
DONN DX/DXL Suspension System

LEED Credits

Recycled Content: 75%
CLIMAPLUS Superior Performance for Mold/Mildew

MR				EQ		
Waste Reduction ¹	Recycled Content	Regional Materials ²	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
●	●	●	●	●	●	●

Features and Benefits

- Market's fastest-installing fine-textured ceiling is an economical alternative to face-laminated panels.
- NRC meets general office acoustical needs for sound absorption.
- *CLIMAPLUS* 30-year lifetime system warranty to withstand conditions up to 104 °F (40 °C)/ 95% relative humidity without visible sag when used with a DONN® brand suspension system.

Applications

- Retail stores
- Hospitality
- Office and conference areas
- Transportation terminals

Substrate

- X-Technology mineral fiber



Fine-textured panel

Call 888 874.2450 for samples



White

30

Year System Warranty
 - No visible sag
 - Mold/mildew protection

MILLENNIA
 CLIMAPlus Panels

MILLENNIA
 CLIMAPlus Tile 6,7

MILLENNIA CLIMAPlus
 Illusion Two/24
 Panels
 The look of
 2'x2' panels

Patterns

Grid Profile
 Options

Physical Data/
 Footnotes

UL Classified

Edge	Panel Size	Class	Item No.	NRC	CAC Min. ³	LR ⁴	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content ⁵	Panel Cost
SQ	2'x2' x3/4"	Class A	76505	.70	35	.85	White	A, B, C	Low		75%	\$\$
	2'x4' x3/4"	Class A	78505	.70	35	.85	White	A, B	Low		75%	\$\$
SLT	2'x2' x3/4"	Class A	76705	.70	35	.85	White	D	Low		75%	\$\$
	2'x4' x3/4"	Class A	78705	.70	35	.85	White	D	Low		75%	\$\$
FLB	2'x2' x3/4"	Class A	76907	.70	35	.85	White	E, F, G	Low		75%	\$\$
	2'x4' x3/4"	Class A	76901	.70	35	.85	White	E, F, G	Low		75%	\$\$
BESK	12"x12'x3/4"	Class A	70003	.60	40	.85	White	H	Low		75%	\$\$\$\$
SLT ⁸	2'x4' x3/4"	Class A	78780	.70	35	.85	White	D	Low		75%	\$\$
ILT ⁹	2'x4' x3/4"	Class A	78080	.70	35	.85	White	I	Low		75%	\$\$

Illusion Two/24



Legend


Low Emissions (VOC Class)

Classified as low-emitting per standards established by the Collaborative for High-Performance Schools (CHPS), following California Specification 01350 testing methods.

CLIMAPlus Superior Performance¹⁰

Contains a broad-spectrum antimicrobial treatment on the face and back of the panel that provides guaranteed resistance against the growth of mold/mildew.

A	B	C	D	E	F	G	H	I
DX®/DXL™	DXW™	CENTRICITEE™ DXT	DX/DXL	CENTRICITEE DXT	FINELINE® DXF	FINELINE® 1/8 DXFF	DX®/DXL™ Concealed	CENTRICITEE DXT



Product literature
 Data sheet: SC1824
ASTM E1264 classification
 Type III, Form 1, Pattern E, G
ASTM E84 surface burning characteristics
 Class A
 Flame spread: 25
 Smoke developed: 50
Weight
 1.02-1.05 lb./sq. ft. (panels and tile)

Thermal resistance
 R-2.0
Maximum backloading
 See Warranty for details.
Maintenance
 Can be cleaned easily with a soft brush or vacuum.
Patented technology
 This product's unique combination of sag resistance and sound performance results from a technology covered by U.S. Patent No. 5,250,153.

Footnotes
 1. Applies when USG acoustical ceilings recycling program is utilized.
 2. Dependent on location; see Sustainability selector.
 3. Adding sound masking can be as effective as using a ceiling panel with a higher CAC rating, providing increased privacy between enclosed office spaces.
 4. LR values are shown as averages.
 5. For details, see Sustainability selector.
 6. Contact USG for adhesive recommendations for 12"x12" glue-up applications.

7. Not UL Classified for acoustics.
 8. Panels have a 15/16" routing.
 9. Panels have a 9/16" routing.
 10. Panel face and back surfaces treated with a patented, broad-spectrum antimicrobial standard formulation that inhibits and retards the growth of mold/mildew. For details, see *Ceiling Systems Warranties and Limitations* (SC2102) and *CLIMAPlus Ceilings Certification of Performance* (SC2451).

