

Millennia™ *ClimaPlus*™ High-NRC



MILLENNIA High-NRC Panels with *CLIMAPLUS* Superior Performance/
DONN FINELINE DXF Suspension System

LEED Credits

Recycled Content: 75%
CLIMAPLUS Superior Performance for Mold/Mildew

MR				EQ		
Waste Reduction ¹	Recycled Content	Regional Materials ²	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
●	●	●	●	●	●	●

Features and Benefits

- High NRC value without mechanical perforations.
- NRC of .75 meets the demanding sound control needs of open-plan offices.
- Market's fastest-installing fine-textured ceiling is an economical alternative to face-laminated panels.
- *CLIMAPLUS* 30-year lifetime system warranty to withstand conditions up to 104 °F (40 °C)/95% relative humidity without visible sag when used with a DONN® brand suspension system.

Applications

- Libraries
- Open-plan offices
- Reception and lobby areas
- Legal
- Financial institutions

Substrate

- X-Technology mineral fiber



Call 888.874.2450 for samples



White

30
 Year System Warranty
 – No visible sag
 – Mold/mildew protection

UL Classified													
Edge	Panel Size	Class	Item No.	NRC	CAC Min. ³	LR ⁴	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content ⁵	Panel Cost	
MILLENNIA CLIMAPLUS High-NRC Panels	SLT 	Class A	76201	.75 	30	.87	White	A	Low		75%	\$\$	
	FLB 	Class A	76302	.75 	30	.87	White	B, C, D	Low		75%	\$\$	

Legend

Low Emissions (VOC Class)
 Classified as low-emitting per standards established by the Collaborative for High-Performance Schools (CHPS), following California Specification 01350 testing methods.

CLIMAPLUS Superior Performance⁶
 Contains a broad-spectrum antimicrobial treatment on the face and back of the panel that provides guaranteed resistance against the growth of mold/mildew, fungi, yeast, algae, and Gram-positive and Gram-negative odor/stain-causing bacteria.

A DX [®] /DXL [™]	B CENTRICITEE [™] DXT	C FINELINE [®] DXF	D FINELINE [®] 1/8 DXFF

Grid Profile Options

Physical Data/ Footnotes

Product literature
 Data sheet: SC1851

ASTM E1264 classification
 Type III, Form 1, Pattern E, G

ASTM E84 surface burning characteristics
 Class A
 Flame spread: 25
 Smoke developed: 50

Weight
 1.06-1.09 lb./sq. ft.

Thermal resistance
 R-2.0

Maximum backloading
 See Warranty for details.

Maintenance
 Can be cleaned easily with a soft brush or vacuum.

Patented technology
 This product's unique combination of sag resistance and sound performance results from a technology covered by U.S. Patent No. 5,250,153.

Footnotes

1. Applies when USG acoustical ceilings recycling program is utilized.
2. Dependent on location; see Sustainability selector.
3. Adding sound masking can be as effective as using a ceiling panel with a higher CAC rating, providing increased privacy between enclosed office spaces.
4. LR values are shown as averages.
5. For details, see Sustainability selector.

6. Panel face and back surfaces treated with a patented, broad-spectrum antimicrobial standard formulation that inhibits and retards the growth of mold/mildew, fungi, yeast, and odor/stain-causing Gram-positive and Gram-negative bacteria. For details, see *Ceiling Systems Warranties and Limitations* (SC2102) and *CLIMAPLUS Ceilings Certification of Performance* (SC2451).