



Fine textured panel



**Features and Benefits**

- Fine textured cast product with durable surface that resists scrapes commonly caused by accessing the ceiling plenum.
- Integral color masks nicks and scratches to enhance lifelong panel appearance.
- Exceptional light reflectance reduces the number of light fixtures needed, energy usage, and eye strain.
- Excellent noise reduction of .70 provides effective sound control for open-plan office environments.
- *CLIMAPLUS™* 15-year System Warranty to withstand conditions up to 104 °F (40 °C)/90% relative humidity without visible sag when used with USG's *DONN®* Brand Suspension Systems.
- Nearly two times more impact-resistant than typical fine textured ceiling panels. (ASTM C367 – 2" ball hardness test).

**Applications**















- Boutiques
- Schools
- Corridors
- Conference and lobby areas
- Executive offices
- Hotels
- Open-plan offices
- Restaurants

# Frost™ ClimaPlus™

Acoustical Ceilings

Technical Service 800 USG.4YOU  
Web Site www.usg.com  
Samples/Literature 888 874.2450  
Samples/Literature Fax 888 874.2348  
Customer Service 800 950.3839  
Literature Number SC1968



	Panel Size		UL Classified					Color <sup>2</sup>	Grid Options	Recycled Content <sup>3</sup>	Panel Cost
	Edge	Imperial	Class	Item No.	NRC	CAC Min.	LR <sup>1</sup>				
FROST™ CLIMAPLUS™ Panels	(SLB) 	2' x2' x3/4"	Class A	414	.70 	38	.82	White Standard Advantage	A	67%	\$\$
	(FL) 	2' x2' x3/4"	Class A	418	.70 	38/40 <sup>4</sup>	.82	White Advantage	B, C, D	67%	\$\$
	(FLB) 	2' x2' x3/4"	Class A	419	.70 	38/40 <sup>4</sup>	.82	White Advantage	B, C, D	67%	\$\$
FROST™ CLIMAPLUS™ High LR	(SLB) 	2' x2' x3/4"	Class A	490	.70 	35	.88	White	A	67%	\$\$
	(FLB) 	2' x2' x3/4"	Class A	491	.70 	35	.88	White	B, C, D	67%	\$\$
	<b>A</b> DONN® DX®/ DXL™	<b>B</b> CENTRICITEE™	<b>C</b> FINELINE 1/8	<b>D</b> FINELINE							
<b>Grid Profile Options</b>											

**ASTM E1264 classification**

Type III, Form 4, Pattern E

**ASTM E84 surface burning characteristics**

Class A

Flame spread: 25

Smoke developed: 15

**Weight**

1.50 lb./ft.<sup>2</sup>

**Thermal resistance**

R-1.6

**Maximum backloading**

See Warranty for details.

**Maintenance**

Can be cleaned easily with a soft brush or vacuum.

**Texture**

The manufacturing process for cast ceiling panels creates natural, subtle texture variations, which is a distinguishing feature of these products. Because of potential variances between production dates, we recommend ordering and installing cast products by production date code.

**Footnotes**

1. LR values are shown as averages.
2. See color selectors for more information.
3. For details, see the Recycled Content selector.
4. Achieves 40 CAC when installed with FINELINE or FINELINE 1/8 suspension system.

**SAFETY FIRST!**

Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.



Manufactured by  
USG Interiors, Inc.  
125 South Franklin Street  
Chicago, IL 60606

The following are trademarks of USG Interiors, Inc. or a related company:  
CENTRICITEE, CLIMAPLUS, DONN, DX, DXL, FINELINE, FROST, USG.

SC1968/rev. 11-04  
© 2004, USG Interiors, Inc.  
Printed in U.S.A.