

COLD WATER | Gasoline or Diesel Powered | Belt Drive

LIBERTY SERIES



Double-axle, cage design:
Gasoline- or diesel-powered, belt-drive



Single-axle, cage design:
Gasoline-powered, belt-drive

These Liberty Series roll cage models are the most powerful machines in our cold water line, with cleaning power of up to 5000 PSI. Protected by a rugged powder coated roll cage built of 1 1/4" steel, the PB Cage units feature powerful Vanguard, Honda or Lombardini engines, tri-plunger oil bath Kärcher pumps, 13-inch tubed pneumatic tires, and an extra rugged belt-drive assembly with notched V belts and cast iron pulleys. All single- and double-axle models are ETL safety certified.

Features

- Rugged steel chassis & roll cage
- Powerful Honda or Lombardini engine
- Cleaning power up to 5000 PSI
- Electric start on dual-axle models
- Industrial belt-drive Kärcher pump with 7-year warranty
- 13" tubed pneumatic tires

	Model	Order No.	GPM	PSI	Engine	HP	Start	Fuel	Pump	Axles	Ship Wt
KSP	HD 4.4/25 PB Cage	1.575-206.0	4.4	2500	Honda	13	Recoil	Gas	Kärcher KM	1	290 lbs
KSP	HD 3.0/40 PB Cage	1.575-203.0	3.0	4000	Honda	13	Recoil	Gas	Kärcher KM	1	280 lbs
KSP	HD 3.5/32 PB Cage	1.575-204.0	3.5	3200	Honda	13	Recoil	Gas	Kärcher KM	1	290 lbs
	HD 3.7/35 PB Cage	1.575-205.0	3.7	3500	Honda	13	Recoil	Gas	Kärcher KM	1	290 lbs
	HD 4.0/40 PB Cage	1.575-207.0	4.0	4000	Vanguard	16	Recoil	Gas	Kärcher KM	2	315 lbs
	HD 4.0/50 PB Cage	1.575-200.0	4.0	5000	Honda	20	Electric	Gas	Kärcher KH	2	420 lbs
	HD 4.5/50 PB Cage	1.575-201.0	4.5	5000	Honda	24	Electric	Gas	Kärcher KH	2	425 lbs
	HD 3.4/30 DB Cage	1.575-202.0	3.4	3000	Lombardini	10	Electric	Diesel	Kärcher KM	2	430 lbs

Dimensions: Single Axle 42"L x 26"W x 30"H; Double Axle 42"L x 26"W x 36"H

Ship from Springdale, AR

OPTIONS [Field Installed]

PART NO.	DESCRIPTION
9.801-028.0	E-Z Hose Reel Kit, 100 ft., single axle
9.801-029.0	Rapid Reel Hose Reel Kit, 100 ft., 5000 psi, double axle

Note: Hose not included with hose reel kit



Cart design: Gasoline-powered, belt-drive

Our Liberty cold-water belt-drive series provides a broad selection of rugged belt-drive units, all with reliable Honda GX engines, which deliver cleaning volume of up to 3.7 GPM. Each model is ETL certified to UL-1776 safety standards and comes with a rugged steel chassis, cast iron belt pulley system, tubed pneumatic tires, and industrial-grade Kärcher crankcase pump.

Features

- Chrome handles
- Powder coated steel chassis
- Reliable Honda GX engine
- Water volume up to 3.7 GPM
- Industrial belt-drive Kärcher pump
- Tubed pneumatic tires

	Model	Order No.	GPM	PSI	Engine	HP	Pump	Ship Wt
	HD 2.8/20 PB	1.575-150.0	2.8	2000	Honda	5.5	Kärcher KD	155 lbs
KSP	HD 2.5/27 PB	1.575-151.0	2.5	2700	Honda	6.5	Kärcher KD	163 lbs
KSP	HD 3.0/30 PB	1.575-152.0	3.0	3000	Honda	9	Kärcher KD	220 lbs
KSP	HD 3.7/35 PB	1.575-154.0	3.7	3500	Honda	13	Kärcher KM	255 lbs
KSP	HD 3.0/40 PB	1.575-155.0	3.0	4000	Honda	13	Kärcher KM	265 lbs
KSP	HD 3.5/32 PB	1.575-156.0	3.5	3200	Honda	13	Kärcher KM	257 lbs

Machine Dimensions: 5.5/6.5 HP models 37"L x 21"W x 24"H; 9/13 HP models 45"L x 26"W x 24"H

Ship from Springdale, AR

OPTIONS [Field Installed]

PART NO.	DESCRIPTION
9.801-025.0	E-Z Hose Reel Kit, 100 ft. 5000 psi; no hose



What is the Kärcher Stocking Program (KSP)?

The Kärcher Stocking Program was created to ensure timely shipment of equipment by identifying our 50+ most popular models, which are nearly always in stock at our Springdale, AR distribution center. Stocking levels for KSP machines, as well as other Kärcher equipment, are updated and posted daily on the Kärcher dealer website at dealer.karchercommercial.com.